



# Storage Power Measurement

Patrick Stanko

---

**SNIA Emerald™ Training**

*SNIA Emerald Power Efficiency  
Measurement Specification,*  
for use in EPA ENERGY STAR®


**July 14-17, 2014**

---



# Black box boundary

- Clearly define the system which requires power measurement



# Black box boundary continued

- ▶ I/O generator server may be in the same rack
  - ◆ Rack level fans, rack level controller, switch
  - ◆ What is the real system under test



# Redundancy in power supplies

- Measure both power feeds
- Both power supplies operational



# Systems get large

- Multiple racks of equipment to measure
- Use a clamp on the main line feed



# Double check

- Power should be close to what is expected
- Verify power factor
- Three phase setup
- Syncing clocks between power meter and Vdbench

# Input power requirements

## ➤ Input power requirements

NOMINAL INPUT VOLTAGE RANGE	Phases	AC INPUT FREQUENCY RANGE
100-120 VAC RMS	1	47 – 63 Hz
200 – 240 VAC RMS	1	47 – 63 Hz
200 - 480 VAC RMS	3	47 – 63 Hz

# Power meter requirements

## ➤ Power Meter accuracy

Power Consumption (p)	Minimum Accuracy
$p \leq 10 \text{ W}$	$\pm 0.01 \text{ W}$
$10 < p \leq 100 \text{ W}$	$\pm 0.1 \text{ W}$
$p > 100 \text{ W}$	$\pm 1.0 \text{ W}$

- Sampling period of 5 second or less
- Sampling rate of 0.2 samples/second or greater



# Environmental monitoring

- Monitor temperature during the test
  - ◆ Measure in degrees Celsius
  - ◆ Measured in 0.1 degree resolution
  - ◆ Sample in a period not greater than 1 minute
  - ◆ Measured at primary air inlet
    - › Center of the storage configuration

# Difference between Emerald and ENERGY STAR

- ENERGY STAR has tighter input voltage requirements
  - ◆ For systems Equal to or less than 1500W
    - › Standard input voltages with  $\pm 1.0\%$
    - › Total Harmonic Distortion (THD) of 2.0%
  - ◆ For systems greater than 1500W
    - › Standard input voltage  $\pm 5.0\%$
    - › Total Harmonic Distortion (THD) of 5.0%
- With tight THD requirements need to get the power meter as close to the System Under Test
- Temperature sensor
  - ◆ Overall accuracy of  $\pm 0.5C$  or better
  - ◆ 50 mm in front of the main airflow inlet