

Designing High-Performance Non-Volatile Memory-aware RDMA Communication Protocols for Big Data Processing

Talk at Storage Developer Conference | SNIA 2018

by

Xiaoyi Lu

The Ohio State University

E-mail: luxi@cse.ohio-state.edu

<http://www.cse.ohio-state.edu/~luxi>

Dhabaleswar K. (DK) Panda


The Ohio State University

E-mail: panda@cse.ohio-state.edu

<http://www.cse.ohio-state.edu/~panda>


Big Data Management and Processing on Modern Clusters

- Substantial impact on designing and utilizing data management and processing systems in multiple tiers
 - Front-end data accessing and serving (Online)
 - Memcached + DB (e.g. MySQL), HBase
 - Back-end data analytics (Offline)
 - HDFS, MapReduce, Spark



Big Data Processing with Apache Big Data Analytics Stacks

- Major components included:
 - **MapReduce** (Batch)
 - Spark (Iterative and Interactive)
 - HBase (Query)
 - **HDFS** (Storage)
 - RPC (Inter-process communication)
- Underlying **Hadoop Distributed File System (HDFS)** used by MapReduce, Spark, HBase, and many others
- Model scales but high amount of communication and I/O can be further optimized!



Drivers of Modern HPC Cluster and Data Center Architecture




Multi-/Many-core
Processors



High Performance Interconnects –
InfiniBand (with SR-IOV)
<1usec latency, 200Gbps Bandwidth>



Accelerators / Coprocessors
high compute density, high
performance/watt
>1 TFlop DP on a chip



SSD, NVMe-SSD, NVRAM

- Multi-core/many-core technologies
- **Remote Direct Memory Access (RDMA)-enabled networking (InfiniBand and RoCE)**
 - Single Root I/O Virtualization (SR-IOV)
- **NVM and NVMe-SSD**
- Accelerators (NVIDIA GPGPUs and FPGAs)



SDSC Comet



TACC Stamped




The High-Performance Big Data (HiBD) Project


- RDMA for Apache Spark
- RDMA for Apache Hadoop 2.x (RDMA-Hadoop-2.x)
 - Plugins for Apache, Hortonworks (HDP) and Cloudera (CDH) Hadoop distributions
- RDMA for Apache HBase
- RDMA for Memcached (RDMA-Memcached)
- RDMA for Apache Hadoop 1.x (RDMA-Hadoop)
- OSU HiBD-Benchmarks (OHB)
 - HDFS, Memcached, HBase, and Spark Micro-benchmarks
- <http://hibd.cse.ohio-state.edu>
- Users Base: 290 organizations from 34 countries
- More than 27,800 downloads from the project site

Available for InfiniBand and RoCE
Available for x86 and OpenPOWER

**Significant performance improvement
with 'RDMA+DRAM' compared to
default Sockets-based designs;
How about RDMA+NVRAM?**




Non-Volatile Memory (NVM) and NVMe-SSD



3D XPoint from Intel & Micron



Samsung NVMe SSD





Performance of PMC Flashtec NVRAM [*]

- Non-Volatile Memory (NVM) provides byte-addressability with persistence
- The huge explosion of data in diverse fields require fast analysis and storage
- NVMs provide the opportunity to build high-throughput storage systems for data-intensive applications
- Storage technology is moving rapidly towards NVM

[*] <http://www.enterprisetech.com/2014/08/06/flashtec-nvram-15-million-iops-sub-microsecond-latency/>

NVRAM Emulation based on DRAM

- Popular methods employed by recent works to emulate NVRAM performance model over DRAM
- Two ways:
 - Emulate byte-addressable NVRAM over DRAM
 - Emulate block-based NVM device over DRAM




Presentation Outline

- NRCIO: NVM-aware RDMA-based Communication and I/O Schemes
- NRCIO for Big Data Analytics
- NVMe-SSD based Big Data Analytics
- Conclusion and Q&A

Design Scope (NVM for RDMA)

D-to-D over RDMA: Communication buffers for client and server are allocated in DRAM (Common)




D-to-N over RDMA: Communication buffers for client are allocated in DRAM; Server uses NVM

N-to-D over RDMA: Communication buffers for client are allocated in NVM; Server uses DRAM


N-to-N over RDMA: Communication buffers for client and server are allocated in NVM

NVRAM-aware RDMA-based Communication in NRCIO



NRCIO RDMA Write over NVRAM



NRCIO RDMA Read over NVRAM





DRAM-TO-NVRAM RDMA-Aware Communication with NRCIO



- Comparison of communication latency using NRCIO RDMA read and write communication protocols over InfiniBand EDR HCA with DRAM as source and NVRAM as destination
- {NxDRAM} NVRAM emulation mode = Nx NVRAM write slowdown vs. DRAM with clflushopt (emulated) + sfence
- Smaller impact of time-for-persistence on the end-to-end latencies for small messages vs. large messages => larger number of cache lines to flush

NVRAM-TO-NVRAM RDMA-Aware Communication with NRCIO




- Comparison of communication latency using NRCIO RDMA read and write communication protocols over InfiniBand EDR HCA vs. DRAM
- {Ax, By} NVRAM emulation mode = Ax NVRAM read slowdown and Bx NVRAM write slowdown vs. NVRAM
- High end-to-end latencies due to slower writes to non-volatile persistent memory
 - E.g., 3.9x for {1x,2x} and 8x for {2x,5x}

Presentation Outline


- NRCIO: NVM-aware RDMA-based Communication and I/O Schemes
- **NRCIO for Big Data Analytics**
- NVMe-SSD based Big Data Analytics
- Conclusion and Q&A

Opportunities of Using NVRAM+RDMA in HDFS

- Files are divided into fixed sized blocks
 - Blocks divided into packets
- NameNode: stores the file system namespace
- DataNode: stores data blocks in local storage devices
- Uses block replication for fault tolerance
 - Replication enhances data-locality and read throughput
- Communication and I/O intensive
- Java Sockets based communication
- Data needs to be persistent, typically on SSD/HDD



Design Overview of NVM and RDMA-aware HDFS (NVFS)




• Design Features


- RDMA over NVM
- HDFS I/O with NVM
 - Block Access
 - Memory Access
- Hybrid design
 - NVM with SSD as a hybrid storage for HDFS I/O
- Co-Design with Spark and HBase
 - Cost-effectiveness
 - Use-case

N. S. Islam, M. W. Rahman , X. Lu, and D. K. Panda, High Performance Design for HDFS with Byte-Addressability of NVM and RDMA, 24th International Conference on Supercomputing (ICS), June 2016

Evaluation with Hadoop MapReduce



TestDFSIO





OSU Nowlab (4 nodes)

- TestDFSIO on SDSC Comet (32 nodes)
 - Write: NVFS-MemIO gains by **4x** over HDFS
 - Read: NVFS-MemIO gains by **1.2x** over HDFS


- TestDFSIO on OSU Nowlab (4 nodes)
 - Write: NVFS-MemIO gains by **4x** over HDFS
 - Read: NVFS-MemIO gains by **2x** over HDFS

Evaluation with HBase




- YCSB 100% Insert on SDSC Comet (32 nodes)
 - NVFS-BlkIO gains by **21%** by storing only WALs to NVM
- YCSB 50% Read, 50% Update on SDSC Comet (32 nodes)
 - NVFS-BlkIO gains by **20%** by storing only WALs to NVM

Opportunities to Use NVRAM+RDMA in MapReduce




- Map and Reduce Tasks carry out the total job execution
 - Map tasks read from HDFS, operate on it, and write the intermediate data to local disk (**persistent**)
 - Reduce tasks get these data by shuffle from NodeManagers, operate on it and write to HDFS (**persistent**)
- Communication and I/O intensive; Shuffle phase uses HTTP over Java Sockets; I/O operations take place in SSD/HDD typically

Opportunities to Use NVRAM in MapReduce-RDMA Design





NVRAM-Assisted Map Spilling in MapReduce-RDMA



M. W. Rahman, N. S. Islam, X. Lu, and D. K. Panda, Can Non-Volatile Memory Benefit MapReduce Applications on HPC Clusters? PDSW-DISCS, with SC 2016.

M. W. Rahman, N. S. Islam, X. Lu, and D. K. Panda, NVMD: Non-Volatile Memory Assisted Design for Accelerating MapReduce and DAG Execution Frameworks on HPC Systems? IEEE BigData 2017.

Comparison with Sort and TeraSort




- RMR-NVM achieves **2.37x** benefit for Map phase compared to RMR and MR-IPoIB; overall benefit **55%** compared to MR-IPoIB, **28%** compared to RMR

- RMR-NVM achieves **2.48x** benefit for Map phase compared to RMR and MR-IPoIB; overall benefit **51%** compared to MR-IPoIB, **31%** compared to RMR


Evaluation of Intel HiBench Workloads

- We evaluate different HiBench workloads with Huge data sets on 8 nodes
- Performance benefits for Shuffle-intensive workloads compared to MR-IPoIB:
 - Sort: **42%** (25 GB)
 - TeraSort: **39%** (32 GB)
 - PageRank: **21%** (5 million pages)
- Other workloads:
 - WordCount: **18%** (25 GB)
 - KMeans: **11%** (100 million samples)



Evaluation of PUMA Workloads

- We evaluate different PUMA workloads on 8 nodes with 30GB data size
- Performance benefits for Shuffle-intensive workloads compared to MR-IPoIB :
 - AdjList: **39%**
 - SelfJoin: **58%**
 - RankedInvIndex: **39%**
- Other workloads:
 - SeqCount: **32%**
 - InvIndex: **18%**




Presentation Outline

- NRCIO: NVM-aware RDMA-based Communication and I/O Schemes
- NRCIO for Big Data Analytics
- **NVMe-SSD based Big Data Analytics**
- Conclusion and Q&A

Overview of NVMe Standard

- **NVMe** is the standardized interface for PCIe SSDs
- Built on '**RDMA**' principles
 - Submission and completion I/O queues
 - Similar semantics as RDMA send/recv queues
 - Asynchronous command processing
- Up to **64K I/O queues**, with up to **64K** commands per queue
- Efficient small random I/O operation
- **MSI/MSI-X** and interrupt aggregation





NVMe Command Processing

Source: NVMExpress.org


Overview of NVMe-over-Fabric

- Remote access to flash with **NVMe** over the network
- **RDMA fabric** is of most importance
 - Low latency makes remote access feasible
 - 1 to 1 mapping of NVMe I/O queues to RDMA send/recv queues





Design Challenges with NVMe-SSD

- QoS
 - Hardware-assisted QoS
- Persistence
 - Flushing buffered data
- Performance
 - Consider flash related design aspects
 - Read/Write performance skew
 - Garbage collection
- Virtualization
 - SR-IOV hardware support
 - Namespace isolation
- New software systems
 - Disaggregated Storage with NVMe
 - Persistent Caches





Evaluation with RocksDB





- 20%, 33%, 61% improvement for Insert, Write Sync, and Read Write
- Overwrite: Compaction and flushing in background
 - Low potential for improvement
- Read: Performance much worse; Additional tuning/optimization required

Evaluation with RocksDB



- 25%, 50%, 160% improvement for Insert, Write Sync, and Read Write
- Overwrite: Compaction and flushing in background
 - Low potential for improvement
- Read: Performance much worse; Additional tuning/optimization required

QoS-aware SPDK Design



- Synthetic application scenarios with different QoS requirements
 - Comparison using SPDK with Weighted Round Robin NVMe arbitration
- Near desired job bandwidth ratios
- Stable and consistent bandwidth

S. Gugnani, X. Lu, and D. K. Panda, Analyzing, Modeling, and Provisioning QoS for NVMe SSDs, (Under Review)


Conclusion and Future Work

- Big Data Analytics needs high-performance NVM-aware RDMA-based Communication and I/O Schemes
- Proposed a new library, **NRCIO** (work-in-progress)
- Re-design HDFS storage architecture with NVRAM
- Re-design RDMA-MapReduce with NVRAM
- Design Big Data analytics stacks with NVMe and NVMf protocols
- Results are promising
- Further optimizations in NRCIO
- Co-design with more Big Data analytics frameworks
 - TensorFlow, Object Storage, Database, etc.

Thank You!

luxi@cse.ohio-state.edu

<http://www.cse.ohio-state.edu/~luxi>



Network-Based Computing Laboratory

<http://nowlab.cse.ohio-state.edu/>

The High-Performance Big Data Project

<http://hibd.cse.ohio-state.edu/>