



# Swordfish NVMe Model Overview and Mapping Guide

## Version 1.2.2

**ABSTRACT:** The Swordfish NVMe Model Overview and Mapping Guide defines the model to manage NVMe and NVMe-oF storage systems with Redfish and Swordfish. It provides the detailed mapping information between the NVMe, NVMe-oF specifications and the Redfish and Swordfish specifications.

Publication of this Working Draft for review and comment has been approved by the Scalable Storage Management Technical Work Group. This draft represents a 'best effort' attempt by the Scalable Storage Management Technical Work Group to reach preliminary consensus, and it may be updated, replaced, or made obsolete at any time. This document should not be used as reference material or cited as other than a 'work in progress.' Suggestions for revision should be directed to <http://www.snia.org/feedback>.

## Working Draft

*Last Updated 2 March 2021*

# USAGE

Copyright (c) 2020 - 2021 SNIA. All rights reserved. All other trademarks or registered trademarks are the property of their respective owners.

The SNIA hereby grants permission for individuals to use this document for personal use only, and for corporations and other business entities to use this document for internal use only (including internal copying, distribution, and display) provided that:

1. Any text, diagram, chart, table or definition reproduced must be reproduced in its entirety with no alteration, and,
2. Any document, printed or electronic, in which material from this document (or any portion hereof) is reproduced must acknowledge the SNIA copyright on that material, and must credit the SNIA for granting permission for its reuse.

Other than as explicitly provided above, you may not make any commercial use of this document, or any portion thereof, or distribute this document to third parties. All rights not explicitly granted are expressly reserved to SNIA.

Permission to use this document for purposes other than those enumerated above may be requested by emailing [tcmd@snia.org](mailto:tcmd@snia.org). Please include the identity of the requesting individual and/or company and a brief description of the purpose, nature, and scope of the requested use.

All code fragments, scripts, data tables, and sample code in this SNIA document are made available under the following license:

## BSD 3-Clause Software License

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of The Storage Networking Industry Association (SNIA) nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN

CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## DISCLAIMER

The information contained in this publication is subject to change without notice. The SNIA makes no warranty of any kind with regard to this publication, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The SNIA shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use.

Suggestions for revisions should be directed to <http://www.snia.org/feedback/>.

## Current Revision

SNIA is actively engaged in expanding and refining the Swordfish documentation. The most current revision can be found on the SNIA web site at [https://www.snia.org/tech\\_activities/standards/curr\\_standards/swordfish](https://www.snia.org/tech_activities/standards/curr_standards/swordfish).

## Contact SNIA

Current SNIA practice is to make updates and other information available through their web site at <http://www.snia.org>.

## FEEDBACK AND INTERPRETATIONS

Requests for interpretation, suggestions for improvement and addenda, or defect reports are welcome. They should be sent via the SNIA Feedback Portal at <http://www.snia.org/feedback/> or by mail to the Storage Networking Industry Association, 4360 ArrowsWest Drive, Colorado Springs, Colorado 80907, U.S.A.

## INTENDED AUDIENCE

This document is intended for use by individuals and companies engaged in storage management.

## VERSIONING POLICY

This document is versioned material. Versioned material shall have a three-level revision identifier, comprised of a version number ‘v’, a release number ‘r’ and an errata number ‘e’. Future publications of this document are subject to specific constraints on the scope of change that is permissible from one revision to the next and the degree of interoperability and backward compatibility that should be assumed between products designed to this standard. This versioning policy applies to all SNIA Swordfish versioned materials.

**Version Number:** Versioned material having version number ‘v’ shall be backwards compatible with all of revisions of that material that have the same version number ‘v’. There is no assurance of interoperability or backward compatibility between revisions of a versioned material with different version numbers.

**Release Number:** Versioned material with a version number ‘v’ and release number ‘r’ shall be backwards compatible with previous revisions of the material with the same version number, and a lower release number. A minor revision represents a technical change to existing content or an adjustment to the scope of the versioned material. Each minor revision causes the release number to be increased by one.

**Errata Number:** Versioned material having version number ‘v’, a release number ‘r’, and an errata number ‘e’ should be backwards compatible with previous revisions of the material with the same version number and release number (“errata versions”). An errata revision of versioned material is limited to minor corrections or clarifications of existing versioned material. An errata revision may be backwards incompatible, if the incompatibility is necessary for correct operation of implementations of the versioned material.

## Revision History

Revisions to this document are summarized in [Table 1](#).

Table 1: Revision History

Date	Revision	Notes
18 August 2020	1.2.1	Initial Release
31 October 2020	1.2.1c	Released as SNIA Approved Publication
2 March 2021	1.2.2	Added detailed mapping information to match information in NVMe drive profiles for many new referenced properties, and included guidance for mandatory/recommended implementation as reflected in the profiles. Added sections for firmware update, with details for NVMe Drive implementation requirements. Added cross-references to User's Guide NVMe-specific use cases. Errata fixes – correct diagram, correct table headers.

## About SNIA

The Storage Networking Industry Association (SNIA) is a non-profit organization made up of member companies spanning information technology. A globally recognized and trusted authority, SNIA's mission is to lead the storage industry in developing and promoting vendor-neutral architectures, standards and educational services that facilitate the efficient management, movement and security of information.

## Acknowledgements

The SNIA Scalable Storage Management Technical Work Group, which developed and reviewed this work in progress, would like to recognize the significant contributions made by the members listed in [Table 2](#).

Table 2: Contributors

<b>Member</b>	<b>Representatives (* – prior employer)</b>
Broadcom Inc.	Richelle Ahlvers*
Cisco Systems, Inc.	Krishnakumar Gowravaram
Dell Inc.	David Black Jim Pendergraft Michael Raineri
Hewlett Packard Enterprise	Curtis Ballard Jeff Hilland Chris Lionetti
Intel Corporation	Richelle Ahlvers Rajalaxmi Angadi Phil Cayton Slawek Putyrski
Kioxia	Mark Carlson
Lenovo	Keith Campbell
NetApp, Inc.	Don Deel Fred Knight
Samsung Corporation	Lu Fan Bill Martin Tom Rainey
VMware, Inc.	Murali Rajagopal



## Table of Contents

<b>USAGE</b>	<b>2</b>
DISCLAIMER	3
Current Revision	3
Contact SNIA	4
FEEDBACK AND INTERPRETATIONS	4
INTENDED AUDIENCE	4
VERSIONING POLICY	4
Revision History	5
About SNIA	6
Acknowledgements	6
Table of Contents	8
1 Abstract	9
2 Scope	10
2.1 Document Goals	10
2.2 Audience Assumptions	10
3 Normative References	11
3.1 Overview	11
3.2 Approved references	11
3.3 References under development	12
3.4 Other references	12
4 NVMe Model Overview	13
4.1 Introduction	13
4.2 Overall NVMe Subsystem Model	13
5 Example Instances	16
5.1 Introduction	16
5.2 Simple SSD	16
5.3 Complex SSD	17
5.4 Simple SSD with IP (NVMe-oF) Attach	18
5.5 JBOF	21
5.6 Opaque Array	23
5.7 Subsystem (Fabric) Model - NVMe-oF: Fabric Attach Subsystem	24
5.8 NVMe Domains	26
6 Property Mapping	28
6.1 Introduction	28
6.2 Property Mapping Template	28
6.3 NVM subsystem	30
6.4 NVM Controllers	46
6.5 Namespace	152
6.6 Endurance Group	185
6.7 NVM Set	210
6.8 Drive	235
7 Other Feature Mapping	273
7.1 Introduction	273
7.2 Firmware Update	273
Annex A: Objects without a direct mapping to the NVMe model	275
A.1: Overview	275
A.2: Related Use Cases	275
Annex B: Bibliography	276
B.1 Overview	276
B.2 Informational references	276



# 1 Abstract

The Swordfish NVMe Model Overview and Mapping Guide defines the model to manage NVMe and NVMe-oF storage systems with Redfish and Swordfish. It provides the detailed mapping information between the NVMe, NVMe-oF specifications and the Redfish and Swordfish specifications.

## 2 Scope

### 2.1 Document Goals

This document describes how both the NVMe Subsystem model and the NVMe-oF fabric system model should be mapped consistently to Redfish and Swordfish constructs for implementations to be managed within Redfish and Swordfish management environments.

This model and mapping information does not describe or assert any specific implementation recommendation technologies.

This document also provides the mapping information for properties recommended to be implemented in Redfish/Swordfish for NVMe and NVMe-oF devices and the corresponding reference information from the NVMe and NVMe-oF specifications.

### 2.2 Audience Assumptions

This document assumes that the reader of this document is familiar with NVMe and NVMe-oF technologies and concepts. It also assumes the reader has knowledge of the Redfish and Swordfish concepts.

## 3 Normative References

### 3.1 Overview

The documents listed in [Table 3](#) are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

### 3.2 Approved references

Table 3: Approved normative references

Tag	Title (Version)	Author	URL
ISO-8601	Data elements and interchange formats – Information interchange – Representation of dates and times – Part 1: Basic rules	ISO/IEC	<a href="http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?csnumber=70907">http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?csnumber=70907</a> ( <a href="http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?csnumber=70907">http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?csnumber=70907</a> )
ISO-Direct	ISO/IEC Directives, Part 2 Principles and rules for the structure and drafting of ISO and IEC documents (Eighth Edition, 2018)	ISO/IEC	<a href="https://www.iso.org/sites/directives/current/part2/index.xhtml">https://www.iso.org/sites/directives/current/part2/index.xhtml</a> ( <a href="https://www.iso.org/sites/directives/current/part2/index.xhtml">https://www.iso.org/sites/directives/current/part2/index.xhtml</a> )
Redfish	Redfish Scalable Platforms Management API Specification (v1.11.0)	DMTF	<a href="http://www.dmtf.org/sites/default/files/standards/documents/DSP0266_1.4.0.pdf">http://www.dmtf.org/sites/default/files/standards/documents/DSP0266_1.4.0.pdf</a> ( <a href="http://www.dmtf.org/sites/default/files/standards/documents/DSP0266_1.11.0.pdf">http://www.dmtf.org/sites/default/files/standards/documents/DSP0266_1.11.0.pdf</a> )
Swordfish	Swordfish Scalable Storage Management API Specification (v1.2.1)	SNIA	<a href="https://www.snia.org/tech_activities/standards/curr_standards/swordfish">https://www.snia.org/tech_activities/standards/curr_standards/swordfish</a> ( <a href="https://www.snia.org/tech_activities/standards/curr_standards/swordfish">https://www.snia.org/tech_activities/standards/curr_standards/swordfish</a> )

Table 3: Approved normative references, cont.

Tag	Title (Version)	Author	URL
NVMe	NVMe Spec v1.4a	NVM Express	<a href="https://nvmexpress.org/wp-content/uploads/NVM-Express-1_4a-2020.03.09-Ratified.pdf">https://nvmexpress.org/wp-content/uploads/NVM-Express-1_4a-2020.03.09-Ratified.pdf</a> ( <a href="https://nvmexpress.org/wp-content/uploads/NVM-Express-1_4a-2020.03.09-Ratified.pdf">https://nvmexpress.org/wp-content/uploads/NVM-Express-1_4a-2020.03.09-Ratified.pdf</a> )
NVMe-oF	NVMe-oF Spec v1.1	NVM Express	<a href="https://nvmexpress.org/wp-content/uploads/NVMe-over-Fabrics-1.1-2019.10.22-Ratified.pdf">https://nvmexpress.org/wp-content/uploads/NVMe-over-Fabrics-1.1-2019.10.22-Ratified.pdf</a> ( <a href="https://nvmexpress.org/wp-content/uploads/NVMe-over-Fabrics-1.1-2019.10.22-Ratified.pdf">https://nvmexpress.org/wp-content/uploads/NVMe-over-Fabrics-1.1-2019.10.22-Ratified.pdf</a> )

## 3.3 References under development

None defined in this document.

## 3.4 Other references

None defined in this document.

## 4 NVMe Model Overview

### 4.1 Introduction

In order to manage NVMe and NVMe-oF devices and systems in a large scale environment, a higher level management ecosystem is needed. The Redfish/Swordfish management specifications are designed to manage multi-system environments, including multiple types of fabrics, covering not only multiple technologies, but also inclusive of system management, storage management and fabric management, making it the ideal ecosystem in which to add not only the integration of NVMe devices for system and storage management, but NVMe-oF for fabric management.

This document describes how both the NVMe Subsystem model and the NVMe-oF fabric system model should be mapped consistently to Redfish and Swordfish constructs for implementations to be managed within Redfish and Swordfish management environments. This model and mapping information does not describe or assert any specific implementation recommendation technologies.

Similar implementations will have similar Redfish and Swordfish constructs. Mockups are used to show static examples of sample representations. Requirements and recommendations for implementations are provided separately through the Swordfish NVMe and NVMe-oF profiles. The profiles use the Redfish interoperability profile schema to specify the required, recommended and optional properties and schema for specific configurations and functionality that correspond to classes of implementations.

#### 4.1.1 Fundamental Model Design Assertions

- There shall be a unified model across all types of NVMe devices.
- There shall not be a different model for “drives” vs other types of NVMe devices
- The model will cover an appropriate level of abstraction for all types of NVMe devices based on modeling and mockups reflected in the documented permutations (e.g., from simple drives through to complex fabric virtual systems)
  - Simple NVMe drives; complex NVMe drives; JBOFs/EBOFs; Arrays/RBOFs
- The logical model for NVMe-oF shall leverage the NVMe Subsystem model
- Logical subsystems, controllers, and namespaces are the same objects with the same relationships as in the NVMe Subsystem Model. Unneeded objects are not instantiated (e.g., Endurance Groups, sets)
- The NVMe native model should map to the existing Redfish and Swordfish constructs when and where possible
  - Mapping future NVMe / NVMe-oF functionality should follow this principle when and where possible (e.g., firmware update mapping to the RF update service)

### 4.2 Overall NVMe Subsystem Model

Key Tenets:

- Model reflects a unified view of all NVMe device types.
- Devices will instantiate an appropriate subset of the model
- The model diagrams do not reflect all available schema elements.
- Model leverages and coarsely maps to existing (Redfish and) Swordfish storage model

#### 4.2.1 Major NVM Objects Mapped to RF/SF

##### 4.2.1.1 NVM Subsystem

An NVM subsystem includes one or more controllers, zero or more namespaces, and one or more ports. Examples of NVM subsystems include Enterprise and Client systems that utilize PCI Express based solid state drives and/or fabric connectivity.

### 4.2.1.2 NVM Controller (IO, Admin and Discovery)

The interface between a host and an NVM subsystem

Admin controller: controller that exposes capabilities that allow a host to manage an NVM subsystem

Discovery: controller that exposes capabilities that allow a host to retrieve a Discovery Log Page

I/O: controller that implements I/O queues and is intended to be used to access a non-volatile memory storage medium

### 4.2.1.3 Namespace

A quantity of non-volatile memory that may be formatted into logical blocks. When formatted, a namespace of size  $n$  is a collection of logical blocks with logical block addresses from 0 to  $(n-1)$ .

### 4.2.1.4 Endurance Group

A portion of NVM in the NVM subsystem whose endurance is managed as a group

### 4.2.1.5 NVM Set

An NVM Set is a collection of NVM that is separate (logically and potentially physically) from NVM in other NVM Sets.

### 4.2.1.6 NVM Domain

A domain is the smallest indivisible unit that shares state (e.g., power state, capacity information). Domain members can be NVM controllers, endurance groups, sets or namespaces.

## 4.2.2 Unmapped objects

There are a number of objects that are required for the proper integration of NVMe support within Redfish and Swordfish, but which are not supported by an entity that can be mapped directly from the various NVM Specifications. Information about these related but un-mapped objects are defined elsewhere in the documentation provided with each Swordfish release.

They are summarized in [Appendix A](#).

## 4.2.3 NVM Subsystem Model

The following diagram reflects the high level mapping of the key NVM objects into Redfish / Swordfish schema objects. These largely follow existing relationships used by the Swordfish storage specification for non-NVMe implementations as well, which provides a great deal of consistency for storage clients, as well as for implementations such as NVMe arrays that may be delivering solutions that combine NVMe and other technologies.

This model covers a wide range of instantiations ranging from individual SSDs, to multi-rack storage systems. All of these can be represented by this NVM Subsystem model, shown in [Figure 1](#).




Figure 1: Subsystem model

#### 4.2.4 NVMe-oF Subsystem Model

The [Figure 2](#) shows the high level mapping of the key NVMe-oF objects to Redfish / Swordfish schema objects. Following the tenets described in the model overview section, these extend the mapping used in the NVM Subsystem for the logical versions of the objects.

This model also includes the use of the Redfish Fabric model to cover the connectivity aspects of the fabric.

The grey shaded portion of this diagram reflects the logical / exported portion of the NVMe-oF environment represented in Redfish / Swordfish.




Figure 2: NVMe-oF Subsystem Model

## 5 Example Instances

### 5.1 Introduction

This section of the document provides a series of example usages of the model that represent common instantiations of NVMe devices, and how those devices may use the various NVMe, and correspondingly, Redfish and Swordfish objects and schema. This section will not provide comprehensive representations of all potential device types; rather, a representation of several common device types, in order to provide an illustration of the application of the model for those that are unfamiliar with either the NVMe or Redfish / Swordfish ecosystems.

Further, the following sections describe the examples and do not attempt to cover all potential permutations for alternate representations of each device class or possible implementations.

### 5.2 Simple SSD

#### 5.2.1 Overview

Figure 3 shows a sample representation of a simple NVMe SSD, with a PCIe interface. It is implemented with no endurance group or NVM set functionality; it has only a single namespace capability, and a single IO controller.




Figure 3: Simple SSD instance diagram

#### 5.2.2 Explanation of Object use

Simple SSDs are SSDs that do not use Endurance Groups or sets. Correspondingly, they only use Storage, Controllers, Volumes (Namespaces), and the Drive schema to represent the fundamental components.

Many SSD implementations support exactly one namespace. These are described by this model, and the mockups reflect this configuration.

This model can also support extensions to cover dual-ported configurations, as well as support for multiple IO controllers per port.

#### 5.2.3 Redfish / Swordfish Object Representation

Figure 4 shows the representation, as expressed in the mockup indicated below, of a sample instantiation using Redfish / Swordfish objects.

Note that this mockup does not represent a complete service instantiation; it contains only objects of interest for this context.






Figure 4: Simple SSD mockup example

5.2.4 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/simple-ssd-mockups> (<http://swordfishmockups.com/simple-ssd-mockups>).

5.3 Complex SSD

5.3.1 Overview

Figure 5 shows a sample representation of a complex NVMe SSD, with a PCIe interface. This example shares many similarities to the simple device model, but adds the representation of NVMe Endurance Groups and NVM Sets using the Swordfish StoragePool schema, with additional NVMe specific properties.




Figure 5: Complex SSD Model

5.3.2 Explanation of Object use

Complex SSDs are SSDs that use Endurance Groups and NVM sets. They also use Storage, Controllers, Volumes (Namespaces), and the Drive schema to represent the fundamental components.

This model can also support extensions to cover dual-ported configurations, as well as support for multiple IO controllers per port.

Endurance Groups divide the media into distinct wear-leveling domains. How this happens is implementation specific.

NVM Sets further subdivide an endurance group in order to limit performance interference within and across these domains.

When this type of device supports dynamic namespace allocation and NVM Sets, the management of the namespaces is done within an NVM Set as the underlying capacity source (e.g., the storage pool).

### 5.3.3 Redfish / Swordfish Object Representation

Figure 6 shows the representation, as expressed in the mockup indicated below, of a sample instantiation using Redfish / Swordfish objects.

Note that this mockup does not represent a complete service instantiation; it contains only objects of interest for this context.




Figure 6: Complex SSD Model

#### 5.3.3.1 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/simple-ssd-eg-set-mockups> (<http://swordfishmockups.com/simple-ssd-eg-set-mockups>).

## 5.4 Simple SSD with IP (NVMe-oF) Attach

### 5.4.1 Overview

This example reflects an IP-attached drive configuration, with a single ethernet port configured, as illustrated in Figure 7. It includes a drive configured with a default endurance group and NVM Set, and is instantiated in the Storage Collection off the Service Root. The network configuration is modeled in the Chassis.




Figure 7: Simple IP-attached SSD

5.4.2 Explanation of Object use

Simple SSDs with IP attach are also SSDs that do not use Endurance Groups or sets, but that have IP-based network interfaces. Correspondingly, they only use Storage, Controllers, Volumes (Namespaces), and the Drive schema to represent the fundamental components. In addition, they use the Redfish Network Adapter, Port and Network Device Function to model the configuration of the IP interface port(s).


As with the Simple SSD configuration, Many SSD with IP-attach implementations support exactly one namespace. These are described by this model, and the mockups reflect this configuration.

This model can also support extensions to cover multi-ported configurations, as well as support for multiple IO controllers per port.

5.4.3 Redfish / Swordfish Object Representation

Figure 8 shows the representation, as expressed in the mockup indicated below, of a sample instantiation using Redfish / Swordfish objects.

Note that this mockup does not represent a complete service instantiation; it contains only objects of interest for this context.



## 5.4.4 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/ethernet-attach-drive-mockups> (<http://swordfishmockups.com/ethernet-attach-drive-mockups>).



This type of JBOF system uses the Chassis, Storage and Controller objects to reflect physical component modeling, Subsystem and Admin Controller functionality.

The Chassis model and Admin controller represent NVMe's SES (SCSI enclosure services) usage.

### 5.5.3 Redfish / Swordfish Object Representation

Figure 11 shows the representation, as expressed in the mockup indicated below, of a sample instantiation using Redfish / Swordfish objects.

Note that this mockup does not represent a complete service instantiation; it contains only objects of interest for this context.




Figure 11: JBOF system instance

### 5.5.4 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/nvme-jbof-mockups> (<http://swordfishmockups.com/nvme-jbof-mockups>)

## 5.6 Opaque Array

### 5.6.1 Overview

The “opaque” array reflects a system with an NVMe front end, but the internal implementation is vendor specific, and not necessarily presented by the vendor (aka “opaque”). [Figure 12](#) shows a system that presents an NVMe front-end but also exposes a SATA drive backend. This could be done to support both FRU management and volume/namespace creation.




Figure 12: Opaque array example

### 5.6.2 Explanation of Object use

The opaque array example presents NVMe specific information in Redfish/Swordfish objects, using the Storage, Controller, and Volume objects.

In addition, device management information is presented through StoragePool and Drive objects, providing internal, non-NVMe implementation specific information to the user, for configuration, diagnosis and other storage management functions. (This set of objects is subject to the standard Swordfish specification and profiles.)

### 5.6.3 Redfish / Swordfish Object Representation

[Figure 13](#) shows the representation, as expressed in the mockup indicated below, of a sample instantiation using Redfish / Swordfish objects.

Note that this mockup does not represent a complete service instantiation; it contains only objects of interest for this context.




Figure 13: Sample opaque system instance

## 5.6.4 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/nvme-opaque-array-mockups> (<http://swordfishmockups.com/nvme-opaque-array-mockups>).

## 5.7 Subsystem (Fabric) Model - NVMe-oF: Fabric Attach Subsystem

### 5.7.1 Overview

Figure 14 shows a logical/exported NVMe-oF subsystem presenting one logical subsystem, one I/O controller, one namespace, one port and representing one allowed host, using the Redfish Fabric model. The fabric model uses the Connection schema to characterize the allowed host information, and Endpoints and Zones to show the network connectivity from the device's perspective.

This example also includes NVMeDomains. NVMeDomains contain a collection of domain members; these can be NVM controllers, endurance groups, NVM sets, or namespaces.






Figure 14: NVMe-OF subsystem example

### 5.7.2 Explanation of Object use

The fabric attach subsystem example shows the representation of logical, or exported, subsystems, controllers, and namespaces using the Storage, Controller and Volume objects respectively.

It also uses portions of the Redfish fabric model to represent the host attachment information - allowed hosts and logical port - using the Connections and Endpoints objects respectively.

### 5.7.3 Redfish / Swordfish Object Representation

Figure 15 shows the representation, as expressed in the mockup indicated below, of a sample instantiation using Redfish / Swordfish objects.

Note that this mockup does not represent a complete service instantiation; it contains only objects of interest for this context.




Figure 15: NVMe-oF system instance

### 5.7.4 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/nvmeof-mockups> (<http://swordfishmockups.com/nvmeof-mockups>).

## 5.8 NVMe Domains

### 5.8.1 Overview

This example describes NVMeDomains. NVMeDomains contain a collection of domain members; these can be NVM controllers, endurance groups, NVM sets, namespaces, and ports, as illustrated in Figure 16.

Domains are used to subdivide an NVM Subsystem. For example, if there are multiple power sources, the domain is used to represent the scope of each power source.




Figure 16: NVMeDomain example

### 5.8.2 Explanation of Object use

The domain object contains two primary elements: the domain members collection, which contains pointers to the relevant controllers, groups, sets, namespaces, and ports that reflect the appropriate subdivision for the purpose of the domain.

The other primary element includes a set of capacity information properties about this set of domain members.

### 5.8.3 Mockup

A corresponding mockup for this configuration can be found at <http://swordfishmockups.com/nvmeof-mockups> (<http://swordfishmockups.com/nvmeof-mockups>).

## 6 Property Mapping

### 6.1 Introduction

The property mapping provided defines the preferred translation between the Redfish/Swordfish schema objects and properties, and the corresponding NVMe and NVMe-oF specification properties. The information is ordered within the Redfish/Swordfish objects; each cross-referenced property within the Redfish/Swordfish structure therefore contains a detailed reference to its mapped property in the NVMe ecosystem.

Each section also includes a sample Redfish/Swordfish mockup presenting an example usage for that object.

### 6.2 Property Mapping Template

[Table 4](#) provides the template and an example for the property mapping provided in the following sections of this document.

For each property (whether a reference, collection, complex type or actual property), there is a comparison between the property in Redfish/Swordfish to the corresponding property in either the NVMe or NVMe-oF specification. The RF/SF property is provided within its schema context; the NVMe/NVMe-oF specification reference is provided within the table, showing both which specification, as well as the section and, if appropriate, the figure in which the property is specified.

Similarly, the type of each property is correspondingly specified. The RF/SF type is specified, and the NVM Spec property type is shown, as well as, where appropriate, any additional identifying information, such as byte offset and data structure.

The Mandatory field is used to specify whether properties are Mandatory or Optional on the NVMe specification side, and in the rare instance where properties are Mandatory in the Redfish/Swordfish schema. (Recommended / required properties for specific implementation types in Redfish/Swordfish will be done separately, through the use of profiles.)

The Notes field can / will be used to include any relevant information about either the purpose of the property, additional context, or other useful information to implementers, such as inter-relationships with other properties.

Table 4: Property Mapping Template and Example

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<b>Redfish / Swordfish Schema Property:</b> RecommendedArbitrationBurstSize	<b>NVM Spec Property / Field:</b> RecommendedArbitrationBurst(RAB) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2, Figure 249
Type	<b>Redfish / Swordfish Schema Type:</b> String	<b>NVM Spec Property Type:</b> Power of 2: $2^n$ <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 72, IdentifyController data structure
Description	The Recommended Arbitration Burst Size indicates the maximum number of commands that the controller may launch at one time from a particular Submission Queue.	This is the recommended Arbitration Burst size. The value is in commands and is reported as a power of two ( $2^n$ ). This is the same units as the Arbitration Burst size.
LongDescription	This property shall contain the Recommended Arbitration Burst Size indicates the maximum number of commands that the controller may launch at one time from a particular Submission Queue. The value is expressed as a power of two (e.g., 000b indicates one, 011b indicates eight). A value of 111b indicates no limit.	
Mandatory		Mandatory
Notes		

## 6.3 NVM subsystem

The Redfish/Swordfish Storage schema is used to represent an NVM Subsystem.

### 6.3.1 Mockup

The following mockup shows a sample representation of the Storage schema used to represent an NVM Subsystem.

```
{
  "@Redfish.Copyright": "Copyright 2014-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem",
  "@odata.type": "#Storage.v1_9_0.Storage",
  "Id": "1",
  "Name": "NVMe-oF Logical NVM Fabric System",
  "Description": "Mockup of NVMe-oF Logical NVM Fabric System with 1 Logical Subsystem, 1 Logical I/O Controller and 1 Logical port and 1 allowed host.",
  "Status": {
    "State": "Enabled",
    "Health": "OK",
    "HealthRollup": "OK"
  },
  "Identifiers": [{
    "DurableNameFormat": "NQN",
    "DurableName": "nqn.2014-08.org.nvmexpress:uuid:6c5fe566-10e6-4fb6-aad4-8b4159f50245"
  }],
  "Controllers": {
    "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem/Controllers"
  },
  "Volumes": {
    "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem/Volumes/LogicalNamespace1"
  }
}
```

## 6.3.2 Property Mapping

### 6.3.2.1 Actions.#StorageController.SetEncryptionKey

The mapping for `Actions.#StorageController.SetEncryptionKey` is summarized in [Table 5](#).

Table 5: `Actions.#StorageController.SetEncryptionKey` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>Actions.#StorageController.SetEncryptionKey</code>	N/A
Type	Action (Special form of POST)	
Description	The available OEM-specific actions for this resource.	
LongDescription	This property shall contain the available OEM-specific actions for this resource.	
Mandatory	Do not implement (for NVMe Drives).	
Notes		N/A for NVMe (Drives). Drives will generate their own key for <code>CryptoErase</code> , this requires passing a new key.

### 6.3.2.2 Controllers

The mapping for `Controllers` is summarized in [Table 6](#).

Table 6: Controllers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Controllers	Controllers
Type	StorageControllerCollection.	Controller list.
Description	The set of controllers instantiated by this storage subsystem.	A list of controller identifiers in the NVM subsystem that may or may not be attached to namespace(s)
LongDescription	This property shall contain a link to a Resource of type <code>StorageControllerCollection</code> that contains the set of storage controllers allocated to this instance of an storage subsystem.	A Controller List (refer to NVMe Base Specification section 4.11) of up to 2,047 controller identifiers is returned containing a controller identifier greater than or equal to the value specified in the Controller Identifier (CDW10.CNTID) field. The list contains controller identifiers in the NVM subsystem that may or may not be attached to namespace(s).
Mandatory	No	No (see note)
Notes	This is a collection of <code>StorageControllers</code> . Refer to the <code>StorageController</code> schema for details of the instance information. These are used to provide information on NVM IO, Admin and Discovery controllers.	This property is only mandatory for controllers that support the Namespace Management capability - reference NVMe Base Specification section 5.15.2.9 Controller list (CNS 13h)

### 6.3.2.3 Description

The mapping for `Description` is summarized in [Table 7](#).

Table 7: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	N/A
Description	The description of this resource.	N/A
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	N/A
Mandatory	Yes	N/A
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: "An NVM Express Subsystem is an NVMe device that contains one or more NVM Express controllers and may contain one or more namespaces."



### 6.3.2.4 Drives

The mapping for `Drives` is summarized in [Table 8](#).

Table 8: Drives mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Drives	NVM Spec Property / Field: NVM Spec: Section:Figure
Type	Collection(Drive.Drive)	
Description	The set of drives attached to the storage controllers that this resource represents.	N/A
LongDescription	This property shall contain a set of the drives attached to the storage controllers that this resource represents.	
Mandatory	Required (for NVMe Drives)	
Notes	For NVMe Drive implementation, this links to “Drive” object, which contains the physical representation of NVMe Drive information.	

### 6.3.2.5 Identifiers

The mapping for `Identifiers` is summarized in [Table 9](#).

Table 9: Identifiers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	Collection(Resource.Identifier)	An array of identifiers
Description	The Durable names for the subsystem.	An array of identifiers
LongDescription	This property shall contain a list of all known durable names for the associated subsystem.	This specifies the NVM Subsystem NVMe Qualified Name as a UTF-8 null-terminated string. Refer to NVMe Base Specification, section 7.9, for the definition of NVMe Qualified Name. Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2).
Mandatory	Yes	Yes
Notes	This is an array of unique identifiers for the NVM Subsystem.	There will only be one instance in this array for Subsystem. Refer to the Identify Controller data structure (CNS 01h) bits 1023:768 in figure 249 (Identify – Identify Controller Data Structure) of the NVMe Base Specification.

### 6.3.2.6 Identifiers.DurableNameFormat

The mapping for `Identifiers.DurableNameFormat` is summarized in [Table 10](#).

Table 10: Identifiers.DurableNameFormat mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableNameFormat	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	Resource.v1_1_0.DurableNameFormat	There is a single value for this array in Subsystem. The property type is of type NVMe Qualified Name (NQN).
Description	The format of the Durable names for the subsystem.	NVM Subsystem NVMe Qualified Name (SUBNQN)
LongDescription	This specifies the format of the associated NVM Subsystem NVMe Qualified Name of type NQN. Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2).	
Mandatory	No	Yes
Notes	This is an enum with multiple potential values. For this particular usage in Subsystem, there will only be one instance populated, of type NQN.	There will only be one instance in this array for Subsystem. Refer to the Identify Controller data structure (CNS 01h) bits 1023:768 in figure 249 (Identify – Identify Controller Data Structure) of the NVMe Base Specification.

### 6.3.2.7 Identifiers.DurableName

The mapping for `Identifiers.DurableName` is summarized in [Table 11](#).

Table 11: Identifiers.DurableName mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableName	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	Edm.String	The NVM Subsystem NVMe Qualified Name as a UTF-8 null-terminated string
Description	The format of the Durable names for the subsystem.	NVM Subsystem NVMe Qualified Name (SUBNQN)
LongDescription	This specifies the NVM Subsystem NVMe Qualified Name as a UTF-8 null-terminated string. Refer to NVMe Base Specification, section 7.9, for the definition of NVMe Qualified Name. Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2).	
Mandatory	No	Yes
Notes	For this particular usage in Subsystem, there will only be one instance populated in the identifiers array.	There will only be one instance in this array for Subsystem. Refer to the Identify Controller data structure (CNS 01h) bits 1023:768 in figure 249 (Identify – Identify Controller Data Structure) of the NVMe Base Specification.

6.3.2.8 Links.Enclosures

The mapping for Links.Enclosures is summarized in [Table 12](#).

Table 12: Links.Enclosures mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Enclosures	NVM Spec Property / Field: NVM Spec: Section:Figure
Type	Collection(Chassis.Chassis)	
Description	An array of links to the chassis to which this storage subsystem is attached.	N/A
LongDescription	This property shall contain an array of links to resources of type Chassis that represent the physical containers attached to this resource.	
Mandatory	Required	
Notes	For NVMe Drive implementation, this links to a chassis collection that contains the subsystem’s “Drive” object, which contains the physical representation of NVMe Drive information.	

### 6.3.2.9 Links.Enclosures@odata.count

The mapping for `Links.Enclosures@odata.count` is summarized in [Table 13](#).

Table 13: Links.Enclosures@odata.count mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Enclosures@odata.count	
Type	(odata property)int64	
Description	Count of the number of items in the Links.Enclosures array.	
LongDescription		
Mandatory	Required	
Notes		

### 6.3.2.10 Links.SimpleStorage

The mapping for `Links.SimpleStorage` is summarized in [Table 14](#).

Table 14: Links.SimpleStorage mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.SimpleStorage	NVM Spec Property / Field: NVM Spec: Section:Figure
Type	SimpleStorage.SimpleStorage	
Description	The link to the simple storage instance that corresponds to this storage.	N/A
LongDescription	This property shall contain a link to a resource of type SimpleStorage that represents the same storage subsystem as this resource.	
Mandatory	Do not implement	
Notes		

### 6.3.2.11 Name

The mapping for `Name` is summarized in [Table 15](#).

Table 15: Name mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	String	String
Description	The name of the resource or array member.	Uniquely describes the NVM subsystem.
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	The NVM Subsystem NVMe Qualified Name is a UTF-8 null-terminated string used (e.g., by host software) as the unique identifier for the NVM subsystem
Mandatory	Yes	Yes (see note)
Notes	In Redfish, Name is a read-only field.	Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2). Reported in the NVM Subsystem NVMe Qualified Name field of the Identify Controller data structure, bytes 1023:768 (refer to figure 249 in section 5.15.2.1 of the NVMe Base Specification). If the NVM Subsystem NVMe Qualified Name field of the Identify Controller data structure is not supported, then all bytes of this field shall be cleared to 0h. Refer to NVMe Base Specification section 7.9 for the definition of NVMe Qualified Name. Refer to NVMe Base Specification section 7.11 for details on the Unique Identifier, including compatibility with older versions of NVMe Controllers that do not support NVM Subsystem NQNs.

## 6.3.2.12 Status.State

The mapping for `Status.State` is summarized in [Table 16](#).

Table 16: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	N/A
Type	Resource.State (enum)	N/A
Description	The known state of the resource, such as, enabled.	N/A
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but it can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory	No	No
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySpare / InTest / Starting / Absent / UnavailableOffline / Deferring / Quiesced / Updating / Qualified	There is no simple corresponding property or mappable set of information at this time. Current guidance is do not implement this property. Guidance will be added in a future version of this document as this is an important concept for clients and for consistency with traditional storage devices.



### 6.3.2.13 Status.Health

The mapping for `Status.Health` is summarized in [Table 17](#).

Table 17: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	Critical Warning Condition
Type	Resource.Health	Boolean
Description	The health state of this resource in the absence of its dependent resources.	Indicates the NVM subsystem has detected a condition that causes at least one of bits 0 to 4 in the Critical Warning field of the SMART / Health Information log (refer to NVMe Base Specification section 5.14.1.2) to be set to one.
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	Bits in this field represent the associated state at the time of this event. The Additional Hardware Error Information field shall be set at the time of the event using the same format as is specified for the Critical Warning field of the SMART / Health Information.
Mandatory	Yes	Yes
Notes	Possible Values: OK / Warning / Critical	Returned as a Critical Warning Condition (code 06h) in the NVM Subsystem Hardware Error Event data (bytes 01:00) of an NVM Subsystem Hardware Error Event (Event Type 05h) in the Persistent Event Log. Reference NVMe Base Specification 5.14.1.13.1.5 NVM Subsystem Hardware Error Event (Event Type 05h), Figure 221 and Figure 222.

### 6.3.2.14 Status.HealthRollup

The mapping for `Status.HealthRollup` is summarized in [Table 18](#).

Table 18: Status.HealthRollup mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.HealthRollup	Critical Warning
Type	Resource.Health	Boolean
Description	The overall health state from the view of this resource.	Indicates the NVM subsystem reliability has been degraded due to significant media related errors or any internal error that degrades NVM subsystem reliability.
LongDescription	This property shall represent the health state of the resource and its dependent resources. The values shall conform to those defined in the Redfish Specification.	Indicates if the NVM subsystem reliability has been degraded due to significant media related errors or any internal error that degrades NVM subsystem reliability. Critical warnings regarding the health of the NVM subsystem may be indicated via an asynchronous event notification to the host. The warnings that results in an asynchronous event notification to the host are configured using the Set Features command; refer to section 5.21.1.11.
Mandatory	Yes	Yes
Notes	Possible Values: OK / Warning / Critical	Returned in byte 00, bit 1 of the Get Log Page – SMART / Health Information Log. Reference the NVMe Base Specification section 5.14.1.2 - SMART / Health Information (Log Identifier 02h), Figure 196.

### 6.3.2.15 StorageControllers

The mapping for `StorageControllers` is summarized in [Table 19](#).

Table 19: `StorageControllers` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>StorageControllers</code>	<b>NVM Spec Property / Field:</b> <b>NVM Spec:</b> <b>Section:Figure</b>
Type	<code>Storage.StorageControllers</code>	
Description	The set of storage controllers that this resource represents.	N/A
LongDescription	This property shall contain a set of the storage controllers that this resource represents.	
Mandatory	Do not implement	
Notes	Deprecated for NVMe use - replaced by <code>Controllers</code> (type <code>StorageController.StorageController</code> ).	

### 6.3.2.16 StorageGroups

The mapping for StorageGroups is summarized in [Table 20](#).

Table 20: StorageGroups mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	StorageGroups	NVM Spec Property / Field: NVM Spec: Section:Figure
Type	StorageGroup.StorageGroup	
Description	All of the storage groups, each of which contains a set of volumes and endpoints that are managed as a group for mapping and masking, that belong to this storage subsystem.	N/A
LongDescription	This property shall contain a link to a resource collection of type StorageGroupsCollection. This property shall be used when implementing mapping and masking.	
Mandatory	Do not implement	
Notes	N/A for NVMe use cases. Deprecatcd by Connections.	

### 6.3.2.17 Volumes

The mapping for `Volumes` is summarized in [Table 21](#).

Table 21: Volumes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Volumes	Allocated Namespace ID list
Type	VolumeCollection.VolumeCollection	List of namespace IDs
Description	The set of volumes instantiated by this storage subsystem.	A list of Allocated Namespaces for this Subsystem
LongDescription	This property shall contain a link to a Resource of type VolumeCollection that contains the set of storage volumes allocated to this instance of an storage subsystem.	A list of namespace IDs is returned to the host containing allocated NSIDs in increasing order.
Mandatory	No	No
Notes	This is a collection of Namespaces that belong to this NVM Subsystem. Refer to the Volume schema for details of the instance information.	Reference NVMe Base Specification section 5.15.2.6 Allocated Namespace ID list (CNS 10h).

## 6.4 NVM Controllers

The Redfish/Swordfish StorageControllers schema is used to represent an NVM Controller.

There are three different types of NVM Controllers: Admin, Discovery, and IO.

### 6.4.1 Admin Controller

#### 6.4.1.1 Mockup

The following mockup shows a sample representation of the StorageController schema used to represent an Admin Controller.

```
{
  "@Redfish.Copyright": "Copyright 2014-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/OpaqueArray/Controllers/NVMeAdminController",
  "@odata.type": "#StorageController.v1_0_0.StorageController",

  "Name": "NVMe Admin Controller",
  "Description": "Single NVMe Admin Controller for in-band admin command access.",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "Id": "NVMeAdminController",
  "Manufacturer": "Best NVMe Vendor",

  "Model": "NVMe Connect Array",
  "SerialNumber": "NVME123456",
  "PartNumber": "NVM44",
  "FirmwareVersion": "1.0.0",
  "SupportedControllerProtocols": [
    "PCIe"
  ],
  "NVMeControllerProperties": {
    "ControllerType": "Admin",
    "NVMeVersion": "1.3",
    "NVMeControllerAttributes": {
      "SupportsSQAssociations": false,
      "SupportsTrafficBasedKeepAlive": false,
      "SupportsExceedingPowerOfNonOperationalState": false,
      "Supports128BitHostId": false
    }
  }
}
```

6.4.1.2 Property Mapping

6.4.1.2.1 Assembly

The mapping for Assembly is summarized in [Table 22](#).

Table 22: Assembly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Assembly	NVM Spec Property / Field: N/A NVM Spec: Section:Figure N/A
Type	ComplexType	N/A
Description	The Assembly schema defines an assembly. Assembly information contains details about a device, such as part number, serial number, manufacturer, and production date. It also provides access to the original data for the assembly.	N/A
LongDescription	This Resource shall represent an assembly for a Redfish implementation. Assembly information contains details about a device, such as part number, serial number, manufacturer, and production date. It also provides access to the original data for the assembly.	N/A
Mandatory	Do Not Implement for NVMe Drives.	
Notes		

6.4.1.2.2 AssetTag

The mapping for AssetTag is summarized in [Table 23](#).

Table 23: Assembly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	AssetTag	NVMSpec Property / Field: N/A NVMSpec: Section:Figure N/A
Type	Edm.String	N/A
Description	The user-assigned asset tag for this storage controller.	N/A
LongDescription	This property shall track the storage controller for inventory purposes.	N/A
Mandatory	Do Not Implement for NVMe Drives.	
Notes		



6.4.1.2.3 CacheSummary

The mapping for CacheSummary is summarized in [Table 24](#).

Table 24: CacheSummary mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CacheSummary	N/A
Type	ComplexType	N/A
Description	The cache memory of the storage controller in general detail.	N/A
LongDescription	This property shall contain properties that describe the cache memory for this resource.	N/A
Mandatory	Do Not Implement	
Notes		

6.4.1.2.4 ControllerRates

The mapping for ControllerRates is summarized in [Table 25](#).

Table 25: ControllerRates mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	ControllerRates	N/A
Type	ComplexType	N/A
Description	This property describes the various controller rates used for processes such as volume rebuild or consistency checks.	N/A
LongDescription	This object shall contain all the rate settings available on the controller.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.1.2.5 Description

The mapping for `Description` is summarized in [Table 26](#).

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	
Description	The description of this resource.	
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	
Mandatory	Optional	N/A
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: "An NVM Admin Controller exposes capabilities that allow a host to manage an NVM subsystem. Admin controllers support commands providing management capabilities but does not provide IO access."

Table: Table 26: Description mapping

## 6.4.1.2.6 FirmwareVersion

The mapping for `FirmwareVersion` is summarized in [Table 27](#).

Table 27: FirmwareVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	FirmwareVersion	<b>NVM Spec Property / Field:</b> IdentifyController: Firmare Revision (FR) <b>NVM Spec: Section:Figure</b> 249: 71:64
Type	String	
Description	The firmware version of this storage controller.	
LongDescription	This property shall contain the firmware version as defined by the manufacturer for the associated storage controller.	
Mandatory	Required.	
Notes		Return the currently active firmware revision information.

6.4.1.2.7 Identifiers

The mapping for `Identifiers` is summarized in [Table 28](#).

Table 28: Identifiers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers	Controller Identifier list
Type	Collection(Resource.Identifier)	A variable length Controller Identifier structures
Description	The Durable names for the storage controller.	
LongDescription	This property shall contain a list of all known durable names for the associated storage controller.	
Mandatory	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	No
Notes		

## 6.4.1.2.8 Identifiers.DurableName

The mapping for `Identifiers.DurableName` is summarized in [Table 29](#).

Table 29: Identifiers.DurableName mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableName	
Type	Variable - see notes	Variable - see notes
Description	The Durable names for the storage controller.	Durable Controller Identifier
LongDescription	T	
Mandatory	Recommend not implementing.	No
Notes	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	

## 6.4.1.2.9 Identifiers.DurableNameFormat

The mapping for `Identifiers.DurableNameFormat` is summarized in [Table 30](#).

Table 30: Identifiers.DurableNameFormat mapping

	Redfish/Swordfish	NVMe / NVMe- oF
Property	Identifiers.DurableNameFormat	
Type	enum (DurableNameFormat)	
Description	The Durable names for the storage controller.	
LongDescription	This property shall contain a list of the types for all known durable names for the associated storage controller. The type determines the length of the corresponding Namespace ID	
Mandatory	Recommend not implementing.	No
Notes	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	

6.4.1.2.10 Links.AttachedVolumes

The mapping for `Links.AttachedVolumes` is summarized in [Table 31](#).

Table 31: Links.AttachedVolumes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.AttachedVolumes	N/A
Type	Collection(Volume,Volume)	N/A
Description	An array of links to volumes that are attached to this controller instance.	
LongDescription	This property shall contain a link to the Resources of type Volume that are attached to this instance of storage controller.	
Mandatory	Do not implement (for admin controllers).	Yes
Notes		



6.4.1.2.11 Location

The mapping for Location is summarized in [Table 32](#).

Table 32: Location mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Location	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Collection(Resource.Location)	
Description	The location of the storage controller.	
LongDescription	This property shall contain location information of the associated storage controller.	N/A
Mandatory	Do Not Implement for NVM Drives.	
Notes		

## 6.4.1.2.12 Manufacturer

The mapping for `Manufacturer` is summarized in [Table 33](#).

Table 33: Manufacturer mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Manufacturer	
Type	String	
Description	The manufacturer of this storage controller.	
LongDescription	This property shall contain the name of the organization responsible for producing the storage controller. This organization might be the entity from whom the storage controller is purchased, but this is not necessarily true.	
Mandatory	Recommended	
Notes		End clients expect to see the name of the company (e.g.; Contoso, BestVendor). While the value may be filled from the <code>IdentifyController</code> PCI Vendor ID or <code>SubsystemID</code> field, it would be preferable to have this filled with the actual string value of the company name.

## 6.4.1.2.13 Model

The mapping for Model is summarized in [Table 34](#).

Table 34: Model mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Model	<b>NVM Spec Property / Field:</b> IdentifyController / Model Number (MN) <b>NVM Spec: Section: Figure</b> 249 byte 24:63
Type	String	N/A
Description	The model number for the storage controller.	
LongDescription	This property shall contain the name by which the manufacturer generally refers to the storage controller.	N/A
Mandatory	Recommended	
Notes		

## 6.4.1.2.14 Name

The mapping for Name is summarized in [Table 35](#).

Table 35: Name mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	<b>NVM Spec Property / Field:</b> Controller ID (CNTLID) <b>NVM Spec: Section: Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	String	<b>NVM Spec Property Type:</b> 16-bit hex value <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 79:78, IdentifyController data structure
Description	The name of the resource or array member.	
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	
Mandatory	Required	Mandatory
Notes	In Redfish, Name is a read-only field.	Map the CNTLID field to a string with the format: "oxABCD"

6.4.1.2.15 NVMeControllerProperties.ControllerType

The mapping for NVMeControllerProperties.ControllerType is summarized in [Table 36](#).

Table 36: NVMeControllerProperties.ControllerType mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ControllerType	N/A
Type	StorageController.v1_o_o.NVMeControllerType	NVM Spec Property Type:
Description	This property specifies the type of NVMe Controller.	
LongDescription	This property shall specify the type of NVMe Controller.	
Mandatory		
Notes	This property must be used to specify the type of NVMe Controller. For an admin controller, set to Admin.	Return “Admin”

## 6.4.1.2.16 NVMeControllerProperties.NVMeVersion

The mapping for NVMeControllerProperties.NVMeVersion is summarized in [Table 37](#).

Table 37: NVMeControllerProperties.NVMeVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeVersion	<b>NVM Spec Property / Field:</b> Version (VER) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	String	<b>NVM Spec Property Type:</b> Maps from register 3.1.2. <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 83:90
Description	The version of the NVMe Base Specification supported.	
LongDescription	This property shall specify the type of NVMe Controller.	
Mandatory		Mandatory
Notes		Implementations compliant to revision 1.2 or later of this specification shall report a non-zero value in this field. Map from corresponding value in register 3.1.2 to string as “1.0”, “1.1”, “1.2”, “1.2.1”, “1.3.0”, “1.4.0”, etc.

6.4.1.2.17 NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations

The mapping for NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations is summarized in [Table 38](#).

Table 38: NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 8 (SQ Associations) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 8 of Byte 99:96
Description	Indicates whether or not the controller supports SQ Associations.	
LongDescription	This property shall indicate whether or not the controller supports SQ Associations.	
Mandatory		
Notes		

## 6.4.1.2.18 NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive

The mapping for NVMeControllerProperties.NVMeControllerAttributes.TrafficBasedKeepAlive is summarized in [Table 39](#).

Table 39: NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 6 (Traffic Based Keep Alive Support – TBKAS) <b>NVM Spec:</b> <b>Section: Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 6 of Byte 99:96
Description	Indicates whether or not the controller supports restarting KeepAlive Timer if traffic is processed from an admin command or IO during KeepAlive Timeout interval.	
LongDescription	This property shall indicate whether or not the controller supports restarting KeepAlive Timer if traffic is processed from an admin command or IO during KeepAlive Timeout interval.	
Mandatory		
Notes		

## 6.4.1.2.19 NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState` is summarized in [Table 40](#).

Table 40: NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 1 (Non-Operational Power State Permissive Mode) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 1 of Byte 99:96
Description	Indicates whether or not the controller supports exceeding Power of NonOperational State in order to execute controller initiated background operations in a non-operational power state.	
LongDescription	This property shall indicate whether or not the controller supports exceeding Power of NonOperational State in order to execute controller initiated background operations in a non-operational power state.	
Mandatory		
Notes		



6.4.1.2.20 NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId

The mapping for NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId is summarized in [Table 41](#).

Table 41: NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 0 <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (Identify Controller), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 99:96
Description	Indicates whether or not the controller supports a 128-bit Host Identifier.	
LongDescription	This property shall indicate whether or not the controller supports a 128-bit Host Identifier.	
Mandatory		
Notes		

## 6.4.1.2.21 NVMeControllerProperties.MaxQueueSize

The mapping for NVMeControllerProperties.MaxQueueSize is summarized in [Table 42](#).

Table 42: NVMeControllerProperties.ANCharacteristics mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.MaxQueueSize	<b>NVM Spec</b> <b>Property / Field:</b> Maximum Queues Entries Supported (MQES) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a; Section 3.1.1 Controller Capabilities; Figure 69
Type	Int64	<b>NVM Spec</b> <b>Property Type:</b> <b>Additional NVM</b> <b>Spec Identifying</b> <b>Information:</b> ByteOffset: Bits 15:00
Description	Indicates the maximum individual queue size that an NVMe IO Controller supports.	
LongDescription	This property shall contain the maximum individual queue entry size supported per queue. This is a zero-based value, where the minimum value is one, indicating two entries. For PCIe, this applies to both submission and completion queues. For NVMe-oF, this applies to only submission queues.	
Mandatory		
Notes		

6.4.1.2.22 NVMeControllerProperties.MaxQueueSize

The mapping for NVMeControllerProperties.ANACharacteristics is summarized in [Table 43](#).

Table 43: NNVMeControllerProperties.ANACharacteristics mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ANACharacteristics	
Type	Collection(StorageController.v1_o_o.ANACharacteristics)	
Description	This property contains the combination of ANA type and volume information.	
LongDescription	This property shall contain the combination of ANA type and volume information.	
Mandatory		
Notes		

## 6.4.1.2.3 NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSystemDegraded

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSystemDegraded is summarized in [Table 44](#).

Table 44: NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSystemDegraded mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSystemDegraded	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 2 of Byte 00
Description	Indicates that the NVM subsystem reliability has been compromised.	
LongDescription	This property shall indicate that the NVM subsystem reliability has been compromised.	
Mandatory	Required	
Notes		

6.4.1.2.24 SKU

The mapping for SKU is summarized in [Table 45](#).

Table 45: SKU mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SKU	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Edm.String	N/A
Description	The SKU for this storage controller.	N/A
LongDescription	This property shall contain the stock-keeping unit number for this storage storage controller.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.1.2.25 SpeedGbps

The mapping for SpeedGbps is summarized in [Table 46](#).

Table 46: SpeedGbps mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SpeedGbps	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Decimal	N/A
Description	The maximum speed of the storage controller's device interface.	N/A
LongDescription	This property shall represent the maximum supported speed of the storage bus interface, in Gbit/s. The specified interface connects the controller to the storage devices, not the controller to a host. For example, SAS bus not PCIe host bus.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.1.2.26 Status.Health

The mapping for `Status.Health` is summarized in [Table 47](#).

Table 47: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	<b>NVM Spec Property / Field:</b> CSTS – Controller Status <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79 <b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Resource.Health	<b>NVM Spec Property Type:</b>
Description	The health state of this resource in the absence of its dependent resources.	
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	
Mandatory		
Notes	Possible Values: OK / Warning / Critical	This comes from CSTS Controller Failure Status, and from the SMART / health information log critical warning field.

## 6.4.1.2.27 Status.State

The mapping for `Status.State` is summarized in [Table 48](#).

Table 48: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	<b>NVM Spec Property / Field:</b> CSTS – Controller Status <b>NVM Spec: Section: Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79
Type	Resource.State (enum)	<b>NVM Spec Property Type:</b>
Description	The known state of the resource, such as, enabled.	
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but it can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory		Mandatory
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySpare / InTest / Starting / ABsent / UnavaialableOffline / Deferring / Quiesced / Updating / Qualified	Ready (CSTS.RDY) maps to Enabled, Shutdown (CSTS.SHST) value will tell you if shutdown is in progress or complete (StandbyOffline), ProcessingPaused (CSTS.PP) maps to Deferring. If both Ready and Shutdown are indicated, then the system should indicate StandbyOffline. If both Ready and ProcessingPaused are indicated, then the system should indicate Deferring.



6.4.1.2.28 SupportedControllerProtocols

The mapping for SupportedControllerProtocols is summarized in [Table 49](#).

Table 49: SupportedControllerProtocols mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SupportedControllerProtocols	N/A
Type	Collection(Protocol.Protocol)	NVM Spec Property Type: N/A
Description	The supported set of protocols for communicating to this storage controller.	
LongDescription	This property shall contain the supported set of protocols for communicating to this storage controller.	
Mandatory	Required.	
Notes	This is an array of protocols supported by the StorageController. This can be set to values including, but not limited to, PCIe, RDMA, NVMe-oF, RoCE, RoCEv2, and InfiniBand.	

6.4.1.2.29 SupportedDeviceProtocols

The mapping for SupportedDeviceProtocols is summarized in [Table 50](#).

Table 50: SupportedDeviceProtocols mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SupportedDeviceProtocols	N/A
Type	Collection(Protocol.Protocol)	NVM Spec Property Type: N/A
Description	The protocols that the storage controller can use to communicate with attached devices.	
LongDescription	This property shall contain the set of protocols this storage controller can use to communicate with attached devices.	
Mandatory		
Notes	Do not implement.	

## 6.4.2 Discovery Controller

### 6.4.2.1 Mockup

The following mockup shows a sample representation of the StorageController schema used to represent a Discovery Controller.

```
{
  "@Redfish.Copyright": "Copyright 2014-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem/Controllers/NVMeIOController",
  "@odata.type": "#StorageController.v1_0_0.StorageController",
  "Id": "9",
  "Name": "NVMe Logical Discovery Controller",
  "Description": "Single NVMe Discovery Controller presented to host.",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "Id": "NVMeDiscoveryController",

  "SupportedControllerProtocols": [
    "TCP", "RDMA", "FC"
  ],
  "SupportedDeviceProtocols": [
    "NVMeOverFabrics"
  ],

  "NVMeControllerProperties": {
    "ControllerType": "Discovery",
    "NVMeVersion": "1.3",
    "NVMeControllerAttributes": {
      "SupportsTrafficBasedKeepAlive": false,
      "SupportsExceedingPowerOfNonOperationalState": false,
      "Supports128BitHostId": false
    }
  }
}
```

6.4.2.2 Property Mapping

6.4.2.2.1 Assembly

The mapping for Assembly is summarized in [Table 51](#).

Table 51: Assembly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Assembly	NVM Spec Property / Field: N/A NVM Spec: Section:Figure N/A
Type	ComplexType	N/A
Description	The Assembly schema defines an assembly. Assembly information contains details about a device, such as part number, serial number, manufacturer, and production date. It also provides access to the original data for the assembly.	N/A
LongDescription	This Resource shall represent an assembly for a Redfish implementation. Assembly information contains details about a device, such as part number, serial number, manufacturer, and production date. It also provides access to the original data for the assembly.	N/A
Mandatory	Do Not Implement for NVMe Drives.	
Notes		

6.4.2.2.2 AssetTag

The mapping for AssetTag is summarized in [Table 52](#).

Table 52: Assembly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	AssetTag	NVM Spec Property / Field: N/A NVM Spec: Section:Figure N/A
Type	Edm.String	N/A
Description	The user-assigned asset tag for this storage controller.	N/A
LongDescription	This property shall track the storage controller for inventory purposes.	N/A
Mandatory	Do Not Implement for NVMe Drives.	
Notes		

6.4.2.2.3 CacheSummary

The mapping for CacheSummary is summarized in [Table 53](#).

Table 53: CacheSummary mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CacheSummary	N/A
Type	ComplexType	N/A
Description	The cache memory of the storage controller in general detail.	N/A
LongDescription	This property shall contain properties that describe the cache memory for this resource.	N/A
Mandatory	Do Not Implement	
Notes		

6.4.2.2.4 ControllerRates

The mapping for ControllerRates is summarized in [Table 54](#).

Table 54: ControllerRates mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	ControllerRates	N/A
Type	ComplexType	N/A
Description	This property describes the various controller rates used for processes such as volume rebuild or consistency checks.	N/A
LongDescription	This object shall contain all the rate settings available on the controller.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.2.2.5 Description

The mapping for `Description` is summarized in [Table 55](#).

Table 55: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	
Description	The description of this resource.	
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	
Mandatory	Optional	N/A
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: "An NVM Discovery Controller exposes capabilities that allow a host to retrieve information required to connect to one or more NVM Subsystems. Discovery controllers only support commands providing discovery capabilities; they do not provide IO or management access."



## 6.4.2.2.6 FirmwareVersion

The mapping for `FirmwareVersion` is summarized in [Table 56](#).

Table 56: FirmwareVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	FirmwareVersion	<b>NVM Spec Property / Field:</b> IdentifyController: Firmare Revision (FR) <b>NVM Spec: Section:Figure</b> 249: 71:64
Type	String	
Description	The firmware version of this storage controller.	
LongDescription	This property shall contain the firmware version as defined by the manufacturer for the associated storage controller.	
Mandatory	Required.	
Notes		Return the currently active firmware revision information.

## 6.4.2.2.7 Identifiers

The mapping for `Identifiers` is summarized in [Table 57](#).

Table 57: Identifiers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers	Controller Identifier list
Type	Collection(Resource.Identifier)	A variable length Controller Identifier structures
Description	The Durable names for the storage controller.	
LongDescription	This property shall contain a list of all known durable names for the associated storage controller.	
Mandatory	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	No
Notes		

## 6.4.2.2.8 Identifiers.DurableName

The mapping for `Identifiers.DurableName` is summarized in [Table 58](#).

Table 58: Identifiers.DurableName mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableName	
Type	Variable - see notes	Variable - see notes
Description	The Durable names for the storage controller.	Durable Controller Identifier
LongDescription	T	
Mandatory	Recommend not implementing.	No
Notes	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	

## 6.4.2.2.9 Identifiers.DurableNameFormat

The mapping for `Identifiers.DurableNameFormat` is summarized in [Table 59](#).

Table 59: Identifiers.DurableNameFormat mapping

	Redfish/Swordfish	NVMe / NVMe- oF
Property	Identifiers.DurableNameFormat	
Type	enum (DurableNameFormat)	
Description	The Durable names for the storage controller.	
LongDescription	This property shall contain a list of the types for all known durable names for the associated storage controller. The type determines the length of the corresponding Namespace ID	
Mandatory	Recommend not implementing.	No
Notes	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	

6.4.2.2.10 Links.AttachedVolumes

The mapping for `Links.AttachedVolumes` is summarized in [Table 60](#).

Table 60: Links.AttachedVolumes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.AttachedVolumes	N/A
Type	Collection(Volume,Volume)	N/A
Description	An array of links to volumes that are attached to this controller instance.	
LongDescription	This property shall contain a link to the Resources of type Volume that are attached to this instance of storage controller.	
Mandatory	Do not implement.	Yes
Notes		

6.4.2.2.11 Links.Endpoints

The mapping for `Links.Endpoints` is summarized in [Table 61](#).

Table 61: Links.Endpoints mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Endpoints	N/A
Type	Collection(Endpoint.Endpoint)	
Description	An array of links to the endpoints that connect to this controller.	
LongDescription	This property shall contain an array of links to the Resources of type Endpoint associated with this controller.	
Mandatory		
Notes		

## 6.4.2.2.12 Links.Connections

The mapping for `Links.Connections` is summarized in [Table 62](#).

Table 62: Links.Connections mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Connections	N/A
Type	Collection(Connection.Connection)	
Description	An array of links to volumes that are attached to this controller instance.	
LongDescription	This property shall contain a link to the Resources of type Volume that are attached to this instance of storage controller.	
Mandatory		
Notes	This contains the information used to represented the allowed hosts.	This property contains pointers to the Connections objects. The information about allowed hosts is mapped to the Connections objects for NVMe-oF configurations.

## 6.4.2.2.13 Location

The mapping for `Location` is summarized in [Table 63](#).

Table 63: Location mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Location	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Collection(Resource.Location)	
Description	The location of the storage controller.	
LongDescription	This property shall contain location information of the associated storage controller.	N/A
Mandatory	Do Not Implement for NVM Drives.	
Notes		

## 6.4.2.2.14 Manufacturer

The mapping for `Manufacturer` is summarized in [Table 64](#).

Table 64: Manufacturer mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Manufacturer	
Type	String	
Description	The manufacturer of this storage controller.	
LongDescription	This property shall contain the name of the organization responsible for producing the storage controller. This organization might be the entity from whom the storage controller is purchased, but this is not necessarily true.	
Mandatory	Optional	
Notes		End clients expect to see the name of the company (e.g.; Contoso, BestVendor). While the value may be filled from the <code>IdentifyController</code> PCI Vendor ID or <code>SubsystemID</code> field, it would be preferable to have this filled with the actual string value of the company name.



6.4.2.2.15 Model

The mapping for Model is summarized in [Table 65](#).

Table 65: Model mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Model	<b>NVM Spec Property / Field:</b> IdentifyController / Model Number (MN) <b>NVM Spec: Section: Figure</b> 249 byte 24:63
Type	String	N/A
Description	The model number for the storage controller.	
LongDescription	This property shall contain the name by which the manufacturer generally refers to the storage controller.	N/A
Mandatory	Optional	
Notes		

## 6.4.2.2.16 Name

The mapping for Name is summarized in [Table 66](#).

Table 66: Name mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	<b>NVM Spec Property</b> / <b>Field:</b> Controller ID (CNTLID) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	String	<b>NVM Spec Property Type:</b> 16-bit hex value <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 79:78, IdentifyController data structure
Description	The name of the resource or array member.	
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	
Mandatory	Required	Mandatory
Notes	In Redfish, Name is a read-only field.	Map the CNTLID field to a string with the format: "oxABCD"

## 6.4.2.2.17 NVMeControllerProperties.ControllerType

The mapping for `NVMeControllerProperties.ControllerType` is summarized in [Table 67](#).

Table 67: NVMeControllerProperties.ControllerType mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ControllerType	N/A
Type	StorageController.v1_o_o.NVMeControllerType	<b>NVM Spec Property Type:</b>
Description	This property specifies the type of NVMe Controller.	
LongDescription	This property shall specify the type of NVMe Controller.	
Mandatory	Required property when Discovery controller is implemented.	Discovery controllers are strongly recommended in Ethernet-Attached NVMe Drives.
Notes	This property must be used to specify the type of NVMe Controller. For a discovery controller, set to Discovery.	Return "Discovery"

## 6.4.2.2.18 NVMeControllerProperties.NVMeVersion

The mapping for NVMeControllerProperties.NVMeVersion is summarized in [Table 68](#).

Table 68: NVMeControllerProperties.NVMeVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeVersion	<b>NVM Spec Property / Field:</b> Version (VER) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	String	<b>NVM Spec Property Type:</b> Maps from register 3.1.2. <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 83:90
Description	The version of the NVMe Base Specification supported.	
LongDescription	This property shall specify the type of NVMe Controller.	
Mandatory		Mandatory
Notes		Implementations compliant to revision 1.2 or later of this specification shall report a non-zero value in this field. Map from corresponding value in register 3.1.2 to string as “1.0”, “1.1”, “1.2”, “1.2.1”, “1.3.0”, “1.4.0”, etc.

## 6.4.2.2.19 NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.TrafficBasedKeepAlive` is summarized in [Table 69](#).

Table 69: NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 6 (Traffic Based Keep Alive Support – TBKAS) <b>NVM Spec:</b> <b>Section: Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 6 of Byte 99:96
Description	Indicates whether or not the controller supports restarting KeepAlive Timer if traffic is processed from an admin command or IO during KeepAlive Timeout interval.	
LongDescription	This property shall indicate whether or not the controller supports restarting KeepAlive Timer if traffic is processed from an admin command or IO during KeepAlive Timeout interval.	
Mandatory	Required for Ethernet-Attach NVMe Drives.	
Notes		

## 6.4.2.2.20 NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState` is summarized in [Table 70](#).

Table 70: NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 1 (Non-Operational Power State Permissive Mode) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 1 of Byte 99:96
Description	Indicates whether or not the controller supports exceeding Power of NonOperational State in order to execute controller initiated background operations in a non-operational power state.	
LongDescription	This property shall indicate whether or not the controller supports exceeding Power of NonOperational State in order to execute controller initiated background operations in a non-operational power state.	
Mandatory		
Notes		

6.4.2.2.21 NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId

The mapping for NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId is summarized in [Table 71](#).

Table 71: NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 0 <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (Identify Controller), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 99:96
Description	Indicates whether or not the controller supports a 128-bit Host Identifier.	
LongDescription	This property shall indicate whether or not the controller supports a 128-bit Host Identifier.	
Mandatory		
Notes		

## 6.4.2.2.22 NVMeControllerProperties.MaxQueueSize

The mapping for NVMeControllerProperties.MaxQueueSize is summarized in [Table 72](#).

Table 72: NVMeControllerProperties.ANCharacteristics mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.MaxQueueSize	<b>NVM Spec</b> <b>Property / Field:</b> Maximum Queues Entries Supported (MQES) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a; Section 3.1.1 Controller Capabilities; Figure 69
Type	Int64	<b>NVM Spec</b> <b>Property Type:</b> <b>Additional NVM</b> <b>Spec Identifying</b> <b>Information:</b> ByteOffset: Bits 15:00
Description	Indicates the maximum individual queue size that an NVMe IO Controller supports.	
LongDescription	This property shall contain the maximum individual queue entry size supported per queue. This is a zero-based value, where the minimum value is one, indicating two entries. For PCIe, this applies to both submission and completion queues. For NVMe-oF, this applies to only submission queues.	
Mandatory		
Notes		



6.4.2.2.23 NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded is summarized in [Table 73](#).

Table 73: NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 2 of Byte 00
Description	Indicates that the NVM subsystem reliability has been compromised.	
LongDescription	This property shall indicate that the NVM subsystem reliability has been compromised.	
Mandatory	Required	
Notes		

## 6.4.2.2.24 NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut is summarized in [Table 74](#).

Table 74: NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 00
Description	Indicates that the available spare capacity has fallen below the threshold.	
LongDescription	This property shall indicate that the available spare capacity has fallen below the threshold.	
Mandatory	Required	
Notes		

## 6.4.2.2.25 Status.Health

The mapping for `Status.Health` is summarized in [Table 75](#).

Table 75: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	<b>NVM Spec Property / Field:</b> CSTS – Controller Status <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79 <b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Resource.Health	<b>NVM Spec Property Type:</b>
Description	The health state of this resource in the absence of its dependent resources.	
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	
Mandatory		
Notes	Possible Values: OK / Warning / Critical	This comes from CSTS Controller Failure Status, and from the SMART / health information log critical warning field.

## 6.4.2.2.26 Status.State

The mapping for `Status.State` is summarized in [Table 76](#).

Table 76: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	<b>NVM Spec Property / Field:</b> CSTS – Controller Status <b>NVM Spec: Section: Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79
Type	Resource.State (enum)	<b>NVM Spec Property Type:</b>
Description	The known state of the resource, such as, enabled.	
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but it can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory		Mandatory
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySpare / InTest / Starting / ABsent / UnavaialableOffline / Deferring / Quiesced / Updating / Qualified	Ready (CSTS.RDY) maps to Enabled, Shutdown (CSTS.SHST) value will tell you if shutdown is in progress or complete (StandbyOffline), ProcessingPaused (CSTS.PP) maps to Deferring. If both Ready and Shutdown are indicated, then the system should indicate StandbyOffline. If both Ready and ProcessingPaused are indicated, then the system should indicate Deferring.

6.4.2.2.27 SupportedControllerProtocols

The mapping for SupportedControllerProtocols is summarized in [Table 77](#).

Table 77: SupportedControllerProtocols mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SupportedControllerProtocols	N/A
Type	Collection(Protocol.Protocol)	NVM Spec Property Type: N/A
Description	The supported set of protocols for communicating to this storage controller.	
LongDescription	This property shall contain the supported set of protocols for communicating to this storage controller.	
Mandatory	Required.	
Notes	This is an array of protocols supported by the StorageController. This can be set to values including, but not limited to, PCIe, RDMA, NVMe-oF, RoCE, RoCEv2, and InfiniBand.	

6.4.2.2.28 SupportedDeviceProtocols

The mapping for SupportedDeviceProtocols is summarized in [Table 78](#).

Table 78: SupportedDeviceProtocols mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SupportedDeviceProtocols	N/A
Type	Collection(Protocol.Protocol)	NVM Spec Property Type: N/A
Description	The protocols that the storage controller can use to communicate with attached devices.	
LongDescription	This property shall contain the set of protocols this storage controller can use to communicate with attached devices.	
Mandatory		
Notes	Do not implement.	

## 6.4.3 IO Controller

### 6.4.3.1 Mockup

The following mockup shows a sample representation of the StorageController schema used to represent an IO Controller.

```
{
  "@Redfish.Copyright": "Copyright 2014-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem/Controllers/NVMeIOController",
  "@odata.type": "#StorageController.v1_0_0.StorageController",
  "Id": "9",
  "Name": "NVMe Logical I/O Controller",
  "Description": "Single NVMe I/O Controller presented to host.",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "Id": "NVMeIOController",

  "SupportedControllerProtocols": [
    "TCP", "RDMA", "FC"
  ],
  "SupportedDeviceProtocols": [
    "NVMeOverFabrics"
  ],

  "NVMeControllerProperties": {
    "NVMeVersion": "1.3",
    "NVMeControllerAttributes": {
      "ReportsUUIDList": false,
      "SupportsSQAssociations": false,
      "ReportsNamespaceGranularity": false,
      "SupportsTrafficBasedKeepAlive": false,
      "SupportsPredictableLatencyMode": false,
      "SupportsEnduranceGroups": false,
      "SupportsReadRecoveryLevels": false,
      "SupportsNVMSets": false,
      "SupportsExceedingPowerOfNonOperationalState": false,
      "Supports128BitHostId": false
    }
  },
  "ANACaracteristics": [{
    "AccessState": "Optimized",
    "Volume": {
      "@odata.id": "/redfish/v1/Systems/Sys-1/Storage/NVMeSSD-EG/Volumes/Namespacel"
    }
  }]
},
{
  "Links": {
    "AttachedVolumes": [{
      "@odata.id": "/redfish/v1/Systems/Sys-1/Storage/NVMeSSD-EG/Volumes/Namespacel"
    }],
    "Endpoints": [{
      "@odata.id": "/redfish/v1/Fabrics/NVMe-oF/Endpoints/NVMeEndpoint"
    },
    {
      "@odata.id": "/redfish/v1/Fabrics/NVMe-oF/Endpoints/Host"
    }
  ]
},
}
```

```
    "Connections": [{  
      "@odata.id": "/redfish/v1/Fabrics/NVMe-oF/Connections/Host1"  
    }]  
  }  
}
```



6.4.3.2 Property Mapping

6.4.3.2.1 Assembly

The mapping for Assembly is summarized in [Table 79](#).

Table 79: Assembly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Assembly	NVMSpec Property / Field: N/A NVMSpec: Section:Figure N/A
Type	ComplexType	N/A
Description	The Assembly schema defines an assembly. Assembly information contains details about a device, such as part number, serial number, manufacturer, and production date. It also provides access to the original data for the assembly.	N/A
LongDescription	This Resource shall represent an assembly for a Redfish implementation. Assembly information contains details about a device, such as part number, serial number, manufacturer, and production date. It also provides access to the original data for the assembly.	N/A
Mandatory	Do Not Implement for NVMe Drives.	
Notes		

6.4.3.2.2 AssetTag

The mapping for AssetTag is summarized in [Table 80](#).

Table 80: Assembly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	AssetTag	NVMSpec Property / Field: N/A NVMSpec: Section:Figure N/A
Type	Edm.String	N/A
Description	The user-assigned asset tag for this storage controller.	N/A
LongDescription	This property shall track the storage controller for inventory purposes.	N/A
Mandatory	Do Not Implement for NVMe Drives.	
Notes		

6.4.3.2.3 CacheSummary

The mapping for CacheSummary is summarized in [Table 81](#).

Table 81: CacheSummary mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CacheSummary	N/A
Type	ComplexType	N/A
Description	The cache memory of the storage controller in general detail.	N/A
LongDescription	This property shall contain properties that describe the cache memory for this resource.	N/A
Mandatory	Do Not Implement	
Notes		

6.4.3.2.4 ControllerRates

The mapping for ControllerRates is summarized in [Table 82](#).

Table 82: ControllerRates mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	ControllerRates	N/A
Type	ComplexType	N/A
Description	This property describes the various controller rates used for processes such as volume rebuild or consistency checks.	N/A
LongDescription	This object shall contain all the rate settings available on the controller.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.3.2.5 Description

The mapping for `Description` is summarized in [Table 83](#).

Table 83: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	
Description	The description of this resource.	
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	
Mandatory	Required	N/A
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: "An NVM IO controller is a general-purpose controller that provides access to logical block data and metadata stored on an NVM subsystem's non-volatile storage medium. IO Controllers may also support management capabilities."

## 6.4.3.2.6 FirmwareVersion

The mapping for `FirmwareVersion` is summarized in [Table 84](#).

Table 84: FirmwareVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	FirmwareVersion	<b>NVM Spec Property / Field:</b> IdentifyController: Firmare Revision (FR) <b>NVM Spec: Section:Figure</b> 249: 71:64
Type	String	
Description	The firmware version of this storage controller.	
LongDescription	This property shall contain the firmware version as defined by the manufacturer for the associated storage controller.	
Mandatory	Required.	
Notes		Return the currently active firmware revision information.

6.4.3.2.7 Identifiers

The mapping for `Identifiers` is summarized in [Table 85](#).

Table 85: Identifiers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers	Controller Identifier list
Type	Collection(Resource.Identifier)	A variable length Controller Identifier structures
Description	The Durable names for the storage controller.	
LongDescription	This property shall contain a list of all known durable names for the associated storage controller.	
Mandatory	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	No
Notes		

## 6.4.3.2.8 Identifiers.DurableName

The mapping for `Identifiers.DurableName` is summarized in [Table 86](#).

Table 86: Identifiers.DurableName mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableName	
Type	Variable - see notes	Variable - see notes
Description	The Durable names for the storage controller.	Durable Controller Identifier
LongDescription	T	
Mandatory	Recommend not implementing.	No
Notes	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	



## 6.4.3.2.9 Identifiers.DurableNameFormat

The mapping for `Identifiers.DurableNameFormat` is summarized in [Table 87](#).

Table 87: Identifiers.DurableNameFormat mapping

	Redfish/Swordfish	NVMe / NVMe- oF
Property	Identifiers.DurableNameFormat	
Type	enum (DurableNameFormat)	
Description	The Durable names for the storage controller.	
LongDescription	This property shall contain a list of the types for all known durable names for the associated storage controller. The type determines the length of the corresponding Namespace ID	
Mandatory	Recommend not implementing.	No
Notes	Recommend not implementing. There isn't a good mapping for these in the NVMe spec to a property that has an appropriate / mapping to a durable name format.	

6.4.3.2.10 Links.AttachedVolumes

The mapping for Links.AttachedVolumes is summarized in [Table 88](#).

Table 88: Links.AttachedVolumes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.AttachedVolumes	N/A
Type	Collection(Volume,Volume)	N/A
Description	An array of links to volumes that are attached to this controller instance.	
LongDescription	This property shall contain a link to the Resources of type Volume that are attached to this instance of storage controller.	
Mandatory	Required.	Yes
Notes	This contains a pointer to the set of namespaces attached to this IO Controller.	

6.4.3.2.11 Links.Endpoints

The mapping for `Links.Endpoints` is summarized in [Table 89](#).

Table 89: Links.Endpoints mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Endpoints	N/A
Type	Collection(Endpoint.Endpoint)	
Description	An array of links to the endpoints that connect to this controller.	
LongDescription	This property shall contain an array of links to the Resources of type Endpoint associated with this controller.	
Mandatory		
Notes	For NVMe-oF configurations.	

6.4.3.2.12 Links.Connections

The mapping for `Links.Connections` is summarized in [Table 90](#).

	Redfish/Swordfish   NVMe / NVMe-oF
----- ----- -----	Property   Links.Connections   N/A     Type   Collection(Connection.Connection)     Description   An array of links to volumes that are attached to this controller instance.     LongDescription   This property shall contain a link to the Resources of type Volume that are attached to this instance of storage controller.     Mandatory   N/A for NVMe Drives.     Notes   This contains the information used to represented the allowed hosts.   This property contains pointers to the Connections objects. The information about allowed hosts is mapped to the Connections objects for NVMe-oF configurations.

Table: Table 90: Links.Connections mapping

6.4.3.2.13 Location

The mapping for `Location` is summarized in [Table 91](#).

Table 91: Location mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Location	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Collection(Resource.Location)	
Description	The location of the storage controller.	
LongDescription	This property shall contain location information of the associated storage controller.	N/A
Mandatory	Do Not Implement for NVM Drives.	
Notes		

## 6.4.3.2.14 Manufacturer

The mapping for `Manufacturer` is summarized in [Table 92](#).

Table 92: Manufacturer mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Manufacturer	
Type	String	
Description	The manufacturer of this storage controller.	
LongDescription	This property shall contain the name of the organization responsible for producing the storage controller. This organization might be the entity from whom the storage controller is purchased, but this is not necessarily true.	
Mandatory	Required	
Notes		End clients expect to see the name of the company (e.g.; Contoso, BestVendor). While the value may be filled from the <code>IdentifyController</code> PCI Vendor ID or <code>SubsystemID</code> field, it would be preferable to have this filled with the actual string value of the company name.

6.4.3.2.15 Model

The mapping for Model is summarized in [Table 93](#).

Table 93: Model mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Model	<b>NVM Spec Property / Field:</b> IdentifyController / Model Number (MN) <b>NVM Spec: Section: Figure</b> 249 byte 24:63
Type	String	N/A
Description	The model number for the storage controller.	
LongDescription	This property shall contain the name by which the manufacturer generally refers to the storage controller.	N/A
Mandatory	Required	
Notes		

## 6.4.3.2.16 Name

The mapping for Name is summarized in [Table 94](#).

Table 94: Name mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	<b>NVM Spec Property</b> / <b>Field:</b> Controller ID (CNTLID) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	String	<b>NVM Spec Property Type:</b> 16-bit hex value <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 79:78, IdentifyController data structure
Description	The name of the resource or array member.	
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	
Mandatory	Required	Mandatory
Notes	In Redfish, Name is a read-only field.	Map the CNTLID field to a string with the format: "oxABCD"

6.4.3.2.17 NVMeControllerProperties.ControllerType

The mapping for NVMeControllerProperties.ControllerType is summarized in [Table 95](#).

Table 95: NVMeControllerProperties.ControllerType mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ControllerType	N/A
Type	StorageController.v1_o_o.NVMeControllerType	NVM Spec Property Type:
Description	This property specifies the type of NVMe Controller.	
LongDescription	This property shall specify the type of NVMe Controller.	
Mandatory	Required	
Notes	This property must be used to specify the type of NVMe Controller. For an IO controller, set to IO.	Return "IO"



## 6.4.3.2.18 NVMeControllerProperties.NVMeVersion

The mapping for NVMeControllerProperties.NVMeVersion is summarized in [Table 96](#).

Table 96: NVMeControllerProperties.NVMeVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeVersion	<b>NVM Spec Property / Field:</b> Version (VER) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	String	<b>NVM Spec Property Type:</b> Maps from register 3.1.2. <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 83:90
Description	The version of the NVMe Base Specification supported.	
LongDescription	This property shall specify the type of NVMe Controller.	
Mandatory	Required when NVMe version is 1.2 or higher.	Mandatory
Notes		Implementations compliant to revision 1.2 or later of this specification shall report a non-zero value in this field. Map from corresponding value in register 3.1.2 to string as “1.0”, “1.1”, “1.2”, “1.2.1”, “1.3.0”, “1.4.0”, etc.

## 6.4.3.2.19 NVMeControllerProperties.NVMeControllerAttributes.ReportsUUIDList

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.ReportsUUIDList` is summarized in [Table 97](#).

Table 97: NVMeControllerProperties.NVMeControllerAttributes.ReportsUUIDList mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.ReportsUUIDList	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): UUID List (Bit 9) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 9 of Byte 99:96
Description	Indicates whether or not the controller supports reporting of a UUID list.	
LongDescription	This property shall indicate whether or not the controller supports reporting of a UUID list.	
Mandatory		
Notes		

6.4.3.2.20 NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations

The mapping for NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations is summarized in [Table 98](#).

Table 98: NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsSQAssociations	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 8 (SQ Associations) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 8 of Byte 99:96
Description	Indicates whether or not the controller supports SQ Associations.	
LongDescription	This property shall indicate whether or not the controller supports SQ Associations.	
Mandatory		
Notes		

## 6.4.3.2.21 NVMeControllerProperties.NVMeControllerAttributes.ReportsNamespaceGranularity

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.ReportsNamespaceGranularity` is summarized in [Table 99](#).

Table 99: NVMeControllerProperties.NVMeControllerAttributes.ReportsNamespaceGranularity mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.ReportsNamespaceGranularity	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 7 (Namespace Granularity) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 7 of Byte 99:96
Description	Indicates whether or not the controller supports reporting of Namespace Granularity.	
LongDescription	This property shall indicate whether or not the controller supports reporting of Namespace Granularity.	
Mandatory	Recommended for NVM Drives.	
Notes		

## 6.4.3.2.22 NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.TrafficBasedKeepAlive` is summarized in [Table 100](#).

Table 100: NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsTrafficBasedKeepAlive	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 6 (Traffic Based Keep Alive Support – TBKAS) <b>NVM Spec:</b> <b>Section: Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 6 of Byte 99:96
Description	Indicates whether or not the controller supports restarting KeepAlive Timer if traffic is processed from an admin command or IO during KeepAlive Timeout interval.	
LongDescription	This property shall indicate whether or not the controller supports restarting KeepAlive Timer if traffic is processed from an admin command or IO during KeepAlive Timeout interval.	
Mandatory	Required for Ethernet-Attach Drives.	
Notes	For NVMe SSD Drives: If “Ethernet-Attach for NVMe Drives” feature is advertised, this is required. (This means EnduranceGroups and NVM Sets are supported.)	

## 6.4.3.2.23 NVMeControllerProperties.NVMeControllerAttributes.SupportsPredictableLatencyMode

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.SupportsPredictableLatencyMode` is summarized in [Table 101](#).

Table 101: NVMeControllerProperties.NVMeControllerAttributes.SupportsPredictableLatencyMode mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsPredictableLatencyMode	<b>NVM Spec Property</b> / <b>Field:</b> Controller Attributes (CTRATT): Bit 5 (Predictable Latency Mode) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property</b> <b>Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 5 of Byte 99:96
Description	Indicates whether or not the controller supports Predictable Latency Mode.	
LongDescription	This property shall indicate whether or not the controller supports Predictable Latency Mode.	
Mandatory		
Notes		

## 6.4.3.2.24 NVMeControllerProperties.NVMeControllerAttributes.SupportsEnduranceGroups

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.SupportsEnduranceGroups` is summarized in [Table 102](#).

Table 102: NVMeControllerProperties.NVMeControllerAttributes.SupportsEnduranceGroups mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsEnduranceGroups	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 4 (Endurance Groups) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 4 of Byte 99:96
Description	Indicates whether or not the controller supports Endurance Groups.	
LongDescription	This property shall indicate whether or not the controller supports Endurance Groups.	
Mandatory	Required when EnduranceGroups/Sets are supported.	
Notes	For NVMe SSD Drives: If “Advanced Features for NVMe Drives” feature is advertised, this is required. (This means EnduranceGroups and NVM Sets are supported.)	

## 6.4.3.2.25 NVMeControllerProperties.NVMeControllerAttributes.SupportsReadRecoveryLevels

The mapping for NVMeControllerProperties.NVMeControllerAttributes.SupportsReadRecoveryLevels is summarized in [Table 103](#).

Table 103: NVMeControllerProperties.NVMeControllerAttributes.SupportsReadRecoveryLevels mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsReadRecoveryLevels	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 3 (Read Recovery Levels) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (Identify Controller), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 3 of Byte 99:96
Description	Indicates whether or not the controller supports Read Recovery Levels.	
LongDescription	This property shall indicate whether or not the controller supports Read Recovery Levels.	
Mandatory		
Notes		



## 6.4.3.2.26 NVMeControllerProperties.NVMeControllerAttributes.SupportsNVMSets

The mapping for NVMeControllerProperties.NVMeControllerAttributes.SupportsNVMSets is summarized in [Table 104](#).

Table 104: NVMeControllerProperties.NVMeControllerAttributes.SupportsNVMSets mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsNVMSets	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 2 (NVM Sets) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 2 of Byte 99:96
Description	Indicates whether or not the controller supports NVM Sets.	
LongDescription	This property shall indicate whether or not the controller supports NVM Sets.	
Mandatory	Required when EnduranceGroups/Sets are supported.	
Notes	For NVMe SSD Drives: If “Advanced Features for NVMe Drives” feature is advertised, this is required. (This means EnduranceGroups and NVM Sets are supported.)	

## 6.4.3.2.27 NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState

The mapping for `NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState` is summarized in [Table 105](#).

Table 105: NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.SupportsExceedingPowerOfNonOperationalState	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 1 (Non-Operational Power State Permissive Mode) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (IdentifyController), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 1 of Byte 99:96
Description	Indicates whether or not the controller supports exceeding Power of NonOperational State in order to execute controller initiated background operations in a non-operational power state.	
LongDescription	This property shall indicate whether or not the controller supports exceeding Power of NonOperational State in order to execute controller initiated background operations in a non-operational power state.	
Mandatory		
Notes		

6.4.3.2.28 NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId

The mapping for NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId is summarized in [Table 106](#).

Table 106: NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeControllerAttributes.Supports128BitHostId	<b>NVM Spec Property / Field:</b> Controller Attributes (CTRATT): Bit 0 <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.2 (Identify Controller), Figure 249
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 99:96
Description	Indicates whether or not the controller supports a 128-bit Host Identifier.	
LongDescription	This property shall indicate whether or not the controller supports a 128-bit Host Identifier.	
Mandatory	Required	
Notes		

## 6.4.3.2.29 NVMeControllerProperties.MaxQueueSize

The mapping for `NVMeControllerProperties.MaxQueueSize` is summarized in [Table 107](#).

Table 107: NVMeControllerProperties.ANCharacteristics mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.MaxQueueSize	<b>NVM Spec</b> <b>Property / Field:</b> Maximum Queues Entries Supported (MQES) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a; Section 3.1.1 Controller Capabilities; Figure 69
Type	Int64	<b>NVM Spec</b> <b>Property Type:</b> <b>Additional NVM</b> <b>Spec Identifying</b> <b>Information:</b> ByteOffset: Bits 15:00
Description	Indicates the maximum individual queue size that an NVMe IO Controller supports.	
LongDescription	This property shall contain the maximum individual queue entry size supported per queue. This is a zero-based value, where the minimum value is one, indicating two entries. For PCIe, this applies to both submission and completion queues. For NVMe-oF, this applies to only submission queues.	
Mandatory		
Notes		

6.4.3.2.30 NVMeControllerProperties.MaxQueueSize

The mapping for NVMeControllerProperties.ANCharacteristics is summarized in [Table 108](#).

Table 108: NNVMeControllerProperties.ANCharacteristics mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ANCharacteristics	
Type	Collection(StorageController.v1_o_o.ANCharacteristics)	
Description	This property contains the combination of ANA type and volume information.	
LongDescription	This property shall contain the combination of ANA type and volume information.	
Mandatory		
Notes		

6.4.3.2.31 NVMeControllerProperties.ANCharacteristics.AccessState

The mapping for NVMeControllerProperties.ANCharacteristics.AccessState is summarized in [Table 109](#).

Table 109: NNVMeControllerProperties.ANCharacteristics.AccessState mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ANCharacteristics.AccessState	<b>NVM Spec Property / Field:</b> Asymmetric Namespace Access State <b>NVM Spec: Section:Figure</b> NVMe 1.4a; Section 5.14.1.12; Figure 211
Type	StorageController.v1_o_o.ANAAccessState	<b>NVM Spec Property Type:</b> <b>Additional NVM Spec Identifying Information:</b> ByteOffset: Bits 03:00 of Byte 16
Description	Reported ANA Access state.	
LongDescription	This property shall contain the reported ANA Access State.	
Mandatory		
Notes	Available values: Optimized / NonOptimized / Inaccessible / PersistentLoss	

## 6.4.3.2.32 NVMeControllerProperties.ANCharacteristics.Volume

The mapping for NVMeControllerProperties.ANCharacteristics.Volume is summarized in [Table 110](#).

Table 110: NVMeControllerProperties.ANCharacteristics.Volume mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.ANCharacteristics.Volume	<b>NVM Spec Property / Field:</b> Namespace Identifier X: <b>NVM Spec: Section:Figure</b> NVMe 1.4a; Section 5.14.1.12; Figure 211
Type	Volume.Volume	<b>NVM Spec Property Type:</b> <b>Additional NVM Spec Identifying Information:</b> Bits 35:32, 39:36, ..., ((n*4) + 35):
((n*4) + 32) - up to “n” namespace identifiers.		
Description	The specified volume.	
LongDescription	This property shall contain a link to the specified volume.	
Mandatory		
Notes	This field contains the pointer to the namespace for which the access state applies.	The namespace id should be redirected / linked to the corresponding namespace (volume) object with that namespace id. If this set of fields contains multiple namespaces (e.g., a group of namespaces), a unique entry in the ANCharacteristics array should be created for each namespace.

## 6.4.3.2.33 NVMeControllerProperties.NVMeSMARTCriticalWarnings.PMRUnreliable

The mapping for `NVMeControllerProperties.NVMeSMARTCriticalWarnings.PMRUnreliable` is summarized in [Table 111](#).

Table 111: NVMeControllerProperties.NVMeSMARTCriticalWarnings.PMRUnreliable mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.PMRUnreliable	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec: Section: Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 5 of Byte 00
Description	The Persistent Memory Region has become unreliable.	
LongDescription	This property shall indicate that the Persistent Memory Region has become unreliable. PCI Express memory reads may return invalid data or generate poisoned PCI Express TLP(s). Persistent Memory Region memory writes may not update memory or may update memory with undefined data. The Persistent Memory Region may also have become non-persistent.	
Mandatory	Recommended for NVM Drives	
Notes		



## 6.4.3.2.34 NVMeControllerProperties.NVMeSMARTCriticalWarnings.PowerBackupFailed

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.PowerBackupFailed is summarized in [Table 112](#).

Table 112: NVMeControllerProperties.NVMeSMARTCriticalWarnings.PowerBackupFailed mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.PowerBackupFailed	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 4 of Byte 00
Description	Indicates that the volatile memory backup device has failed.	
LongDescription	This property shall indicate that the volatile memory backup device has failed.	
Mandatory	Recommended for NVM Drives	
Notes		

6.4.3.2.35 NVMeControllerProperties.NVMeSMARTCriticalWarnings.MediaInReadOnly

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.MediaInReadOnly is summarized in [Table 113](#).

Table 113: NVMeControllerProperties.NVMeSMARTCriticalWarnings.MediaInReadOnly mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.MediaInReadOnly	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 3 of Byte 00
Description	Indicates the media has been placed in read only mode.	
LongDescription	This property shall indicate the media has been placed in read only mode. This is not set when the read-only condition on the media is a result of a change in the write protection state of a namespace.	
Mandatory	Required	
Notes		

6.4.3.2.36 NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSystemDegraded

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded is summarized in [Table 114](#).

Table 114: NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.OverallSubsystemDegraded	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 2 of Byte 00
Description	Indicates that the NVM subsystem reliability has been compromised.	
LongDescription	This property shall indicate that the NVM subsystem reliability has been compromised.	
Mandatory	Required	
Notes		

## 6.4.3.2.37 NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut

The mapping for NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut is summarized in [Table 115](#).

Table 115: NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeControllerProperties.NVMeSMARTCriticalWarnings.SpareCapacityWornOut	<b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 00
Description	Indicates that the available spare capacity has fallen below the threshold.	
LongDescription	This property shall indicate that the available spare capacity has fallen below the threshold.	
Mandatory	Required (for NVM Drives)	
Notes		

6.4.3.2.38 PCIeInterface.PCIeType

The mapping for PCIeInterface.PCIeType is summarized in [Table 116](#).

Table 116: PCIeInterface.PCIeType mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PCIeInterface.PCIeType	
Type	enum (PCIeDevice.PCIeType)	
Description	The version of the PCIe specification in use by this device.	
LongDescription	This property shall contain the negotiated PCIe interface version in use by this device.	N/A
Mandatory	Required for PCIe attach NVMe Drives; do not implement for ethernet-attach drives.	
Notes	Possible values: Gen1/Gen2/Gen3/Gen4/Gen5	

6.4.3.2.39 PCIeInterface.MaxPCIeType

The mapping for PCIeInterface.MaxPCIeType is summarized in [Table 117](#).

Table 117: PCIeInterface.MaxPCIeType mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PCIeInterface.MaxPCIeType	
Type	enum (PCIeDevice.PCIeType)	
Description	The highest version of the PCIe specification supported by this device.	N/A
LongDescription	This property shall contain the maximum PCIe specification that this device supports.	N/A
Mandatory	Required for PCIe attach NVMe Drives; do not implement for ethernet-attach drives.	
Notes	Possible values: Gen1/Gen2/Gen3/Gen4/Gen5	

6.4.3.2.40 PCIeInterface.LanesInUse

The mapping for PCIeInterface.LanesInUse is summarized in [Table 118](#).

Table 118: PCIeInterface.LanesInUse mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PCIeInterface.LanesInUse	
Type	int64	
Description	The number of PCIe lanes in use by this device.	
LongDescription	This property shall contain the number of PCIe lanes in use by this device, which shall be equal to or less than the MaxLanes property value.	
Mandatory	Required for PCIe attach NVMe Drives; do not implement for ethernet-attach drives.	
Notes		

6.4.3.2.41 PCIeInterface.MaxLanes

The mapping for PCIeInterface.LanesInUse is summarized in [Table 119](#).

Table 119: PCIeInterface.LanesInUse mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PCIeInterface.LanesInUse	
Type	int64	
Description	The number of PCIe lanes supported by this device.	
LongDescription	This property shall contain the maximum number of PCIe lanes supported by this device.	
Mandatory	Required for PCIe attach NVMe Drives; do not implement for ethernet-attach drives.	
Notes		



6.4.3.2.42 Ports

The mapping for Ports is summarized in [Table 120](#).

Table 120: Ports mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Ports	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	PortCollection.PortCollection	N/A
Description	The link to the collection of ports that exist on the storage controller.	N/A
LongDescription	This property shall contain a link to a resource collection of type PortCollection.	N/A
Mandatory	Do Not Implement	
Notes		

6.4.3.2.43 SKU

The mapping for SKU is summarized in [Table 121](#).

Table 121: SKU mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SKU	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Edm.String	N/A
Description	The SKU for this storage controller.	N/A
LongDescription	This property shall contain the stock-keeping unit number for this storage storage controller.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.3.2.44 SpeedGbps

The mapping for SpeedGbps is summarized in [Table 122](#).

Table 122: SpeedGbps mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SpeedGbps	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Decimal	N/A
Description	The maximum speed of the storage controller's device interface.	N/A
LongDescription	This property shall represent the maximum supported speed of the storage bus interface, in Gbit/s. The specified interface connects the controller to the storage devices, not the controller to a host. For example, SAS bus not PCIe host bus.	N/A
Mandatory	Do Not Implement	
Notes		

## 6.4.3.2.45 Status.State

The mapping for `Status.State` is summarized in [Table 123](#).

Table 123: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	<b>NVM Spec Property / Field:</b> CSTS – Controller Status <b>NVM Spec: Section: Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79
Type	Resource.State (enum)	<b>NVM Spec Property Type:</b>
Description	The known state of the resource, such as, enabled.	
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but it can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory		Mandatory
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySpare / InTest / Starting / ABsent / UnavaialableOffline / Deferring / Quiesced / Updating / Qualified	Ready (CSTS.RDY) maps to Enabled, Shutdown (CSTS.SHST) value will tell you if shutdown is in progress or complete (StandbyOffline), ProcessingPaused (CSTS.PP) maps to Deferring. If both Ready and Shutdown are indicated, then the system should indicate StandbyOffline. If both Ready and ProcessingPaused are indicated, then the system should indicate Deferring.

## 6.4.3.2.46 Status.Health

The mapping for `Status.Health` is summarized in [Table 124](#).

Table 124: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	<b>NVM Spec Property / Field:</b> CSTS – Controller Status <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79 <b>NVM Spec Property / Field:</b> Critical Warning <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Resource.Health	<b>NVM Spec Property Type:</b>
Description	The health state of this resource in the absence of its dependent resources.	
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	
Mandatory		
Notes	Possible Values: OK / Warning / Critical	This comes from CSTS Controller Failure Status, and from the SMART / health information log critical warning field.

6.4.3.2.47 SupportedControllerProtocols

The mapping for SupportedControllerProtocols is summarized in [Table 125](#).

Table 125: SupportedControllerProtocols mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SupportedControllerProtocols	N/A
Type	Collection(Protocol.Protocol)	NVM Spec Property Type: N/A
Description	The supported set of protocols for communicating to this storage controller.	
LongDescription	This property shall contain the supported set of protocols for communicating to this storage controller.	
Mandatory		
Notes	This is an array of protocols supported by the StorageController. This can be set to values including, but not limited to, PCIe, RDMA, NVMe-oF, RoCE, RoCEv2, and InfiniBand.	

6.4.3.2.48 SupportedDeviceProtocols

The mapping for SupportedDeviceProtocols is summarized in [Table 126](#).

Table 126: SupportedDeviceProtocols mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SupportedDeviceProtocols	N/A
Type	Collection(Protocol.Protocol)	NVM Spec Property Type: N/A
Description	The protocols that the storage controller can use to communicate with attached devices.	
LongDescription	This property shall contain the set of protocols this storage controller can use to communicate with attached devices.	
Mandatory		
Notes	Do not implement.	

## 6.5 Namespace

The Redfish/Swordfish Volume schema is used to represent an NVM Namespace.

### 6.5.1 Mockup

The following mockup shows a sample representation of the Volume schema used to represent an NVM Namespace.

```
{
  "@Redfish.Copyright": "Copyright 2014-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem/Volumes/LogicalNamespacel",
  "@odata.type": "#Volume.v1_5_0.Volume",
  "Id": "1",
  "Name": "Namespace 1",
  "LogicalUnitNumber": 1,
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "Identifiers": [{
    "DurableNameFormat": "NGUID",
    "DurableName": "FEDCBA9876543210h"
  }],
  "Capacity": {
    "Data": {
      "ConsumedBytes": 0,
      "AllocatedBytes": 10737418240
    },
    "Metadata": {
      "AllocatedBytes": 536870912
    }
  },
  "CapacitySources": [{
    "@odata.id": "/redfish/v1/Storage/NVMe-oF-Subsystem/Volumes/LogicalNamespacel/CapacitySources/Source1"
  }],
  "NVMeNamespaceProperties": {
    "NamespaceId": "0x014",
    "NamespaceFeatures": {
      "SupportsThinProvisioning": false,
      "SupportsAtomicTransactionSize": false,
      "SupportsDeallocatedOrUnwrittenLBError": false,
      "SupportsNGUIDReuse": false,
      "SupportsIOPerformanceHints": false
    },
    "NumberLBAFormats": 0,
    "FormattedLBASize": "LBAFormat0Support",
    "MetadataTransferredAtEndOfDataLBA": false,

    "NVMeVersion": "1.4"
  }
}
```

### 6.5.2 Property Mapping



6.5.2.1 BlockSizeBytes

The mapping for BlockSizeBytes is summarized in [Table 127](#).

Table 127: BlockSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	BlockSizeBytes	<b>NVM Spec Property / Field:</b> Formatted LBA Size (FLBAS) <b>NVM Spec: Section:Figure</b> 247: byte 26
Type	Int64	
Description	The size, in bytes, of the smallest addressable unit, or block.	
LongDescription	This property shall contain size of the smallest addressable unit of the associated drive.	
Mandatory	Required	
Notes		Follow index in 247: Byte 26 (bits 3:0) to the LBA format structure to get the metadata size and LBA data size combination. These combined values are BlockSizeBytes.

## 6.5.2.2 Capacity.Data.ConsumedBytes

The mapping for Capacity.Data.ConsumedBytes is summarized in [Table 128](#).

Table 128: Capacity.Data.ConsumedBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Capacity.Data.ConsumedBytes	<b>NVM Spec Property / Field:</b> Namespace Utilization (NUSE) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Int64	<b>NVM Spec Property Type:</b> int 64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 23:16, Identify Namespace data structure
Description	The number of bytes consumed in this data store for this data type.	The current number of logical blocks allocated in the namespace.
LongDescription	The value shall be the number of logical bytes currently consumed in this data store for this data type.	This field indicates the current number of logical blocks allocated in the namespace. This field is smaller than or equal to the Namespace Capacity. The number of logical blocks is based on the formatted LBA size.
Mandatory	Yes	Yes
Notes	Reporting capacity in bytes is the Redfish and Swordfish standard mechanism. Clients expect the capacity information to be reported consistently for these devices, so the calculation here is to convert the NVMe properties (in blocks) to bytes.	Returned in bytes 23:16 of the Identify Namespace Data Structure (NVM Command Set Specific). Reference NVMe Base Specification section n 5.15.2.1 and figure 247).

## 6.5.2.3 Capacity.Data.ProvisionedBytes

The mapping for Capacity.Data.ProvisionedBytes is summarized in [Table 129](#).

Table 129: Capacity.Data.ProvisionedBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Capacity.Data.ProvisionedBytes	<b>NVM Spec Property / Field:</b> NVM Capacity (NCAP) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Int64	<b>NVM Spec Property Type:</b> int 64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 15:08, Identify Namespace data structure
Description	The maximum number of bytes that can be allocated in this data store for this data type.	The total size of the namespace in logical blocks (LBA 0 through n-1).
LongDescription	The value shall be the maximum number of bytes that can be allocated in this data store for this data type.	This field indicates the total size of the namespace in logical bytes. The value is in bytes. A namespace of size n consists of LBA 0 through (n - 1). The number of logical blocks is based on the formatted LBA size. This field is undefined prior to the namespace being formatted.
Mandatory	No	No
Notes	This property is required when issuing a create namespace command. It is also required for "change namespace" when modifying the size of the namespace.	Returned in bytes 07:00 of the Identify Namespace Data Structure (NVM Command Set Specific). Reference NVMe Base Specification section in 5.15.2.1 and figure 247.

## 6.5.2.4 Capacity.Data.AllocatedBytes

The mapping for Capacity.Data.AllocatedBytes is summarized in [Table 130](#).

Table 130: Capacity.Data.AllocatedBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Capacity.Data.AllocatedBytes	<b>NVM Spec Property / Field:</b> Namespace Size (NSZE) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Int64	<b>NVM Spec Property Type:</b> int 64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 07:00, Identify Namespace data structure
Description	The number of bytes currently allocated by the storage system in this data store for this data type.	The total size of the NVM allocated to this namespace.
LongDescription	The value shall be the number of bytes currently allocated by the storage system in this data store for this data type.	The total size of the NVM allocated to this namespace. The value is in bytes. This field shall be supported if the Namespace Management capability (refer to NVMe Base Specification section 8.12) is supported. This field may not correspond to the logical block size multiplied by the Namespace Size field. Due to thin provisioning or other settings (e.g., endurance), this field may be larger or smaller than the Namespace Size reported.
Mandatory	No	No
Notes	Reporting capacity in bytes is the Redfish and Swordfish standard mechanism.	Returned in bytes 63:48 of the Identify Namespace Data Structure (NVM Command Set Specific). Reference NVMe Base Specification section in 5.15.2.1 and figure 247.

### 6.5.2.5 Capacity.Metadata

The mapping for Capacity.Metadata is summarized in [Table 131](#).

Table 131: Capacity.Metadata.AllocatedBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Capacity.Metadata.*	N/A
Type	Int64	N/A
Description	The number of bytes currently allocated by the storage system in this data store for this data type.	N/A
LongDescription	The value shall be the number of bytes currently allocated by the storage system in this data store for this data type.	N/A
Mandatory	No; not required for NVMe Drives.	No
Notes		Do not return metadata information for NVMe devices. This is included in the overall reported capacity information.

## 6.5.2.6 CapacitySources

The mapping for CapacitySources is summarized in [Table 132](#).

Table 132: CapacitySources mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacitySources	<b>NVM Spec Property / Field:</b> NVM Set Identifier (NVMSETID) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Collection(Capacity.CapacitySource)	<b>NVM Spec Property Type:</b> int 64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 101:100, Identify Namespace data structure
Description	An array of space allocations to this volume.	The NVM Set in which the namespace is allocated
LongDescription	Fully or partially consumed storage from a source resource. Each entry provides capacity allocation information from a named source resource.	
Mandatory	No	No
Notes	Contains the information about the entity providing capacity (e.g., EnduranceGroup) for this namespace. This property is a collection pointer; each CapacitySource instance contains a CapacitySource object. The CapacitySource contains the overall capacity (in bytes), the types and pointers to the underlying capacity sources.	For NVMe devices that do <i>not</i> implement Endurance Groups and NVM Sets, it is recommended that the CapacitySource not be implemented. For Implementations that do instantiate Endurance Groups and NVM Sets, the capacity source should be implemented as a pointer to the corresponding Endurance Group. (See mockups for examples.)

6.5.2.7 Description

The mapping for `Description` is summarized in [Table 133](#).

Table 133: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	N/A
Description	The description of this resource.	N/A
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	N/A
Mandatory	Yes	N/A
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: “A Namespace is a quantity of non-volatile memory that may be formatted into logical blocks. When formatted, a namespace of size n is a collection of logical blocks with logical block addresses from 0 to (n-1). NVMe systems can support multiple namespaces.”

6.5.2.8 DisplayName

The mapping for `DisplayName` is summarized in [Table 134](#).

Table 134: `DisplayName` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>DisplayName</code>	N/A
Type	String	N/A
Description	A user-configurable string to name the volume.	N/A
LongDescription	this property shall contain a user-configurable string to name the volume.	N/A
Mandatory	Recommended. (Recommended for NVMe Drives)	N/A
Notes	This contains an (end) user settable “friendly” name for the namespace. This may map to a property that shows up in the proprietary software, as long as it is configurable by the end-user, and is intended to contain a displayable string.	



### 6.5.2.9 Identifiers

The mapping for `Identifiers` is summarized in [Table 135](#).

Table 135: Identifiers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers	Namespace Identification Descriptor list
Type	Collection(Resource.Identifier)	A variable length Namespace Identification Descriptor structures
Description	The Durable names for the storage controller.	A list of Namespace Identification Descriptor structures containing Namespace Type, Namespace Identifier Length (NIDL), and Namespace ID (NID).
LongDescription	This property shall contain a list of all known durable names for the associated storage controller.	A list of any number of variable length Namespace Identification Descriptor structures that fit into the 4,096 byte Identify payload. All remaining bytes after the namespace identification descriptor structures should be cleared to oh, and the host shall interpret a Namespace Identifier Descriptor Length (NIDL) value of oh as the end of the list. The host should ignore any Namespace Identification Descriptor with a Namespace Identifier Type not supported by the host.
Mandatory	No	No
Notes	This is an array of unique identifiers for the NVM Subsystem including Namespace Type and Namespace ID.	Refer to NVMe Base Specification Figure 246 CNS 03h and Figure 251 (Identify – Namespace Identification Descriptor).

### 6.5.2.10 Identifiers.DurableName

The mapping for `Identifiers.DurableName` is summarized in [Table 136](#).

Table 136: Identifiers.DurableName mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableName	Namespace Identifier (NID)
Type	Variable - see notes	Variable - see notes
Description	The Durable names for the storage controller.	Durable Namespace Identifier
LongDescription	This property shall contain a list of all known durable names for the Namespace.	A list of globally unique values assigned to the Namespace when the Namespace is created. Values remain fixed throughout the life of the Namespace and are preserved across Namespace and Controller operations (e.g., Controller Level Reset, Namespace format, etc.).
Mandatory	No	No
Notes	This is an array of unique identifiers for the Namespace. Type and length of descriptor are in the corresponding <code>Identifiers.DurableNameFormat</code> property.	This is an array of unique identifiers for the NVM Namespace. Type and length of the descriptor are in the corresponding Namespace Identifier Type (NIDT). Refer to NVMe Base Specification Figure 246 CNS 03h and Figure 251 - Figure 251 Byte NID of Identify – Namespace Identification Descriptor.

### 6.5.2.11 Identifiers.DurableNameFormat

The mapping for `Identifiers.DurableNameFormat` is summarized in [Table 137](#).

Table 137: Identifiers.DurableNameFormat mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableNameFormat	Namespace Identifier Type (NIDT)
Type	Int64	Int64
Description	The Durable names for the storage controller.	The Namespace Identifier data type and length.
LongDescription	This property shall contain a list of the types for all known durable names for the associated storage controller. The type determines the length of the corresponding Namespace ID	the data type contained in the Namespace Identifier field and the length of that type as defined in the NVMe Base Specification Figure 251 - Identify (Namespace Identification Descriptor) byte 00. Allowed values are: 1 = an 8-byte IEEE Extended Unique Identifier . 2 = a 10-byte Namespace Globally Unique Identifier. 3 = an 8-byte Namespace UUID
Mandatory	No	No
Notes	This is an array of types for the unique identifiers for the NVM Subsystem. Values may be 'EUI64', 'NGUID', or 'UUID'.	Refer to NVMe Base Specification Figure 246 CNS 03h and Figure 251 - Figure 251 (NIDT) of Identify – Namespace Identification Descriptor.

### 6.5.2.12 InitializeMethod

The mapping for `InitializeMethod` is summarized in [Table 138](#).

Table 138: InitializeMethod mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	InitializeMethod	N/A
Type	Volume.InitializeMethod (enum)	
Description	Indicates the Initialization Method used for this volume. If InitializeMethod is not specified, the InitializeMethod should be Foreground.	
LongDescription	This property shall indicate the initialization method used for this volume. If InitializeMethod is not specified, the InitializeMethod should be Foreground. This value reflects the most recently used Initialization Method, and may be changed using the Initialize Action.	
Mandatory	Recommended for NVMe Drives.	
Notes	Available values: Fast / Slow	Not in NVMe Specification today.

6.5.2.13 Links.Drives

The mapping for Links.Drives is summarized in [Table 139](#).

Table 139: Links.Drives mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Drives	
Type	Collection(Drive.Drive)	
Description	An array of the drives to be used by the volume	
LongDescription	This parameter shall contain an array of the drives to be used by the volume.	
Mandatory	Required for NVMe Drives.	
Notes	This array shall contain links to the drive object for this namespace.	

### 6.5.2.14 LogicalUnitNumber

The mapping for LogicalUnitNumber is summarized in [Table 140](#).

Table 140: LogicalUnitNumber mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	LogicalUnitNumber	N/A
Type	Int64	N/A
Description	Indicates the host-visible LogicalUnitNumber assigned to this Volume.	N/A
LongDescription	This property shall contain host-visible LogicalUnitNumber assigned to this Volume. This property shall only be used when in a single connect configuration and no StorageGroup configuration is used.	N/A
Mandatory	No	N/A
Notes	Do not use with NVMe devices. This is represented more correctly with (NVMeNamespaceProperties).NamespaceId.	Do not implement.

### 6.5.2.15 MaxBlockSizeBytes

The mapping for MaxBlockSizeBytes is summarized in [Table 141](#).

Table 141: MaxBlockSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	MaxBlockSizeBytes	<b>NVM Spec Property / Field:</b> Formatted LBA Size (FLBAS) <b>NVM Spec: Section:Figure</b> 247: byte 26
Type	Int64	
Description	The size, in bytes, of the smallest addressable unit, or block.	
LongDescription	This property shall contain size of the smallest addressable unit of the associated drive.	
Mandatory	Recommended to not implement; however, if implemented this should have the same value as BlockSizeBytes.	
Notes		Follow index in 247: Byte 26 (bits 3:0) to the LBA format structure to get the metadata size and LBA data size combination. These combined values are BlockSizeBytes.

## 6.5.2.16 Name

The mapping for Name is summarized in [Table 142](#).

Table 142: Name mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	<b>NVM Spec Property / Field:</b> Namespace ID (NSID) <b>NVM Spec: Section:Figure</b> NVMe 1.4a
Type	String	
Description	The name of the resource or array member.	N/A
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	To determine the active NSIDs for a particular controller, the host may follow either of the following methods: 1. Issue an Identify command with the CNS field cleared to 0h for each valid NSID (based on the Number of Namespaces value (i.e., MNAM field or NN field) in the Identify Controller data structure). If a non-zero data structure is returned for a particular NSID, then that is an active NSID; or 2. Issue an Identify command with a CNS field set to 2h to retrieve a list of up to 1,024 active NSIDs. If there are more than 1,024 active NSIDs, continue to issue Identify commands with a CNS field set to 2h until all active NSIDs are retrieved.
Mandatory	Yes	N/A
Notes	In Redfish, Name is a read-only field.	Map the NSID field to a string with the format: "0xABCD"

## 6.5.2.17 NVMeNamespaceProperties.NamespaceId

The mapping for `NVMeNamespaceProperties.NamespaceId` is summarized in [Table 143](#).

Table 143: NVMeNamespaceProperties.NamespaceId mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NamespaceId	Namespace Identifier (NSID)
Type	String	8-byte value
Description	The NVMe Namespace Identifier for this namespace.	An identifier used by a controller to provide access to a namespace.
LongDescription	This property shall contain the NVMe Namespace Identifier for this namespace. This property shall be a hex value. Namespace identifiers are not durable and do not have meaning outside the scope of the NVMe subsystem. NSID 0x0, 0xFFFFFFFF, 0xFFFFFFFFFE are special purpose values.	An identifier used by a controller to provide access to a namespace or the name of the field in the SQE that contains the namespace identifier.
Mandatory	Yes	Yes
Notes		To determine the active NSIDs for a particular controller, the host may follow either of the following methods: 1. Issue an Identify command with the CNS field cleared to 0h for each valid NSID (based on the Number of Namespaces value (i.e., MNAM field or NN field) in the Identify Controller data structure). If a non-zero data structure is returned for a particular NSID, then that is an active NSID; or 2. Issue an Identify command with a CNS field set to 2h to retrieve a list of up to 1,024 active NSIDs. If there are more than 1,024 active NSIDs, continue to issue Identify commands with a CNS field set to 2h until all active NSIDs are retrieved.

## 6.5.2.18 NVMeNamespaceProperties.IsShareable

The mapping for NVMeNamespaceProperties.IsShareable is summarized in [Table 144](#).

Table 144: NVMeNamespaceProperties.IsShareable mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.IsShareable	<b>NVM Spec Property / Field:</b> Namespace Multi-path I/O and Namespace Sharing Capabilities (NMIC) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 30
Description	Indicates the namespace is shareable.	Specifies multi-path I/O and namespace sharing capabilities of the namespace.
LongDescription	This property shall indicate whether the namespace is shareable.	If set to '1', then the namespace may be attached to two or more controllers in the NVM subsystem concurrently (i.e., may be a shared namespace). Bits 7:1 are reserved. Bit 0, if cleared to '0', indicates the namespace is a private namespace and is able to be attached to only one controller at a time.
Mandatory	No	No
Notes		Returned in byte 30 of the Namespace Features (NSFEAT) of the of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247).



## 6.5.2.19 NVMeNamespaceProperties.NamespaceFeatures.SupportsThinProvisioning

The mapping for NVMeNamespaceProperties.NamespaceFeatures.SupportsThinProvisioning is summarized in [Table 145](#).

Table 145: NVMeNamespaceProperties.NamespaceFeatures.SupportsThinProvisioning mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NamespaceFeatures.SupportsThinProvisioning	<b>NVM Spec Property / Field:</b> THINP <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 0 of Byte 24
Description	This property indicates whether or not the NVMe Namespace supports thin provisioning.	Indicates that the namespace supports thin provisioning
LongDescription	This property shall indicate whether or not the NVMe Namespace supports thin provisioning. Specifically, the namespace capacity reported may be less than the namespace size.	if set to '1' indicates that the namespace supports thin provisioning. If cleared to '0' indicates that thin provisioning is not supported. Refer to NVMe Base Specification section 6.1.7 for details on the usage of this field.
Mandatory	Yes	Yes
Notes		Returned in byte 24, bit 0 of the Namespace Features (NSFEAT) of the of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247).

## 6.5.2.20 NVMeNamespaceProperties.NamespaceFeatures.SupportsDeallocatedOrUnwrittenLLError

The mapping for `NVMeNamespaceProperties.NamespaceFeatures.SupportsDeallocatedOrUnwrittenLLError` is summarized in [Table 146](#).

Table 146: NVMeNamespaceProperties.NamespaceFeatures.SupportsDeallocatedOrUnwrittenLLError mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NamespaceFeatures.SupportsDeallocatedOrUnwrittenLLError	<b>NVM Spec Property / Field:</b> DAE <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 2 of Byte 24
Description	This property indicates that the controller supports deallocated or unwritten logical block error for this namespace.	Indicates that the controller supports the Deallocated or Unwritten Logical Block error for this namespace.
LongDescription	This property shall indicate that the controller supports deallocated or unwritten logical block error for this namespace.	If set to '1' indicates that the controller supports the Deallocated or Unwritten Logical Block error for this namespace. If cleared to '0', then the controller does not support the Deallocated or Unwritten Logical Block error for this namespace. Refer to NVMe Base Specification section 6.7.1.1
Mandatory	Yes	Yes

	Redfish/Swordfish	NVMe / NVMe-oF
Notes		Returned in byte 24, bit 2 of the Namespace Features (NSFEAT) of the of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247.

## 6.5.2.21 NVMeNamespaceProperties.NamespaceFeatures.SupportsNGUIDReuse

The mapping for NVMeNamespaceProperties.NamespaceFeatures.SupportsNGUIDReuse is summarized in [Table 147](#).

Table 147: NVMeNamespaceProperties.NamespaceFeatures.SupportsNGUIDReuse mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NamespaceFeatures.SupportsNGUIDReuse	<b>NVM Spec Property / Field:</b> UIDREUSE <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 3 of Byte 24
Description	This property indicates that the namespace supports the use of an NGUID (namespace globally unique identifier) value.	Indicates if the value in the NGUID field and the value in the EUI64 field for this namespace may be reused by the controller for a new namespace created after this namespace is deleted.
LongDescription	This property shall indicate that the namespace supports the use of an NGUID (namespace globally unique identifier) value.	If set to '1' indicates that the value in the NGUID field for this namespace, if non-zero, is never reused by the controller and that the value in the EUI64 field for this namespace, if non-zero, is never reused by the controller. If cleared to '0', then the NGUID value may be reused and the EUI64 value may be reused by the controller for a namespace created after this namespace is deleted. This bit shall be cleared to '0' if both NGUID and EUI64 fields are cleared to 0h. Refer to NVMe Base Specification, section 7.11.
Mandatory	Yes	Yes
Notes		Returned in byte 24, bit 3 of the Namespace Features (NSFEAT) of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247).

## 6.5.2.22 NVMeNamespaceProperties.NamespaceFeatures.SupportsAtomicTransactionSize

The mapping for NVMeNamespaceProperties.NamespaceFeatures.SupportsAtomicTransactionSize is summarized in [Table 148](#).

Table 148: NVMeNamespaceProperties.NamespaceFeatures.SupportsAtomicTransactionSize mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NamespaceFeatures.SupportsAtomicTransactionSize	<b>NVM Spec Property /</b> <b>Field:</b> OPTPERF <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec</b> <b>Identifying Information:</b> Bit 4 of Byte 24
Description	Indicates whether or not the NVM fields for Namespace preferred write granularity (NPWG), write alignment (NPWA), deallocate granularity (NPDG), deallocate alignment (NPDA) and optimal write size (NOWS) are defined for this namespace and should be used by the host for I/O optimization.	Indicates support for the fields NPWG, NPWA, NPDG, NPDA, and NOWS for this namespace; and optimal Write Size field in NVM Sets Attributes Entry
LongDescription	This property shall indicate whether or not the NVM fields for Namespace preferred write granularity (NPWG), write alignment (NPWA), deallocate granularity (NPDG), deallocate alignment (NPDA) and optimal write size (NOWS) are defined for this namespace and should be used by the host for I/O optimization.	If set to '1' indicates that the fields NAWUN, NAWUPF, and NACWU are defined for this namespace and should be used by the host for this namespace instead of the AWUN, AWUPF, and ACWU fields in the Identify Controller data structure. If cleared to '0', then the controller does not support the fields NAWUN, NAWUPF, and NACWU for this namespace. In this case, the host should use the AWUN, AWUPF, and ACWU fields defined in the Identify Controller data structure in Figure 247. Refer to NVMe Base Specification section 6.4.
Mandatory	Yes	Yes
Notes		Returned in byte 24, bit 4 of the Namespace Features (NSFEAT) of the of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247).

## 6.5.2.23 NVMeNamespaceProperties.NamespaceFeatures.SupportsIOPerformanceHints

The mapping for `NVMeNamespaceProperties.NamespaceFeatures.SupportsIOPerformanceHints` is summarized in [Table 149](#).

Table 149: NVMeNamespaceProperties.NamespaceFeatures.SupportsIOPerformanceHints mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NamespaceFeatures.SupportsIOPerformanceHints	<b>NVM Spec Property / Field:</b> NSABP <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	<b>NVM Spec Property Type:</b> Single bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 1 of Byte 24
Description	Indicates that the Namepsace Atomic Write Unit Normal (NAWUN), Namespace Atomic Write Unit Power Fail (NAWUPF), and Namespace Atomic Compare and Write Unit (NACWU) fields are defined for this namespace and should be used by the host for this namespace instead of the controller-level properties AWUN, AWUPF, and ACWU.	indicates whether or not the fields NAWUN, NAWUPF, and NACWU are defined for this namespace and should be used by the host for this namespace instead of the AWUN, AWUPF, and ACWU fields in the Identify Controller data structure.
LongDescription	This property shall indicate that the Namepsace Atomic Write Unit Normal (NAWUN), Namespace Atomic Write Unit Power Fail (NAWUPF), and Namespace Atomic Compare and Write Unit (NACWU) fields are defined for this namespace and should be used by the host for this namespace instead of the controller-level properties AWUN, AWUPF, and ACWU.	If set to '1' indicates that the fields NAWUN, NAWUPF, and NACWU are defined for this namespace and should be used by the host for this namespace instead of the AWUN, AWUPF, and ACWU fields in the Identify Controller data structure. If cleared to '0', then the controller does not support the fields NAWUN, NAWUPF, and NACWU for this namespace. In this case, the host should use the AWUN, AWUPF, and ACWU fields defined in the Identify Controller data structure in NVMe Base Specification Figure 247. Refer to NVMe Base Specification section 6.4.
Mandatory	Yes	Yes
Notes		Returned in byte 24, bit 1 of the Namespace Features (NSFEAT) of the of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247).

## 6.5.2.24 NVMeNamespaceProperties.NumberLBAFormats

The mapping for NVMeNamespaceProperties.NumberLBAFormats is summarized in [Table 150](#).

150: NVMeNamespaceProperties.NumberLBAFormats mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NumberLBAFormats	<b>NVM Spec Property / Field:</b> Number of LBA Formats (NLBAF) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Int64	Type:** Int64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 25
Description	The number of LBA data size and metadata size combinations supported by this namespace. The value of this property is between 0 and 16.	The number of supported LBA data size and metadata size combinations supported by the namespace.
LongDescription	This property shall contain the number of LBA data size and metadata size combinations supported by this namespace. The value of this property is between 0 and 16. LBA formats with an index set beyond this value will not be supported.	This property shall contain the number of LBA formats allocated in order starting with 0 and packed sequentially. This is a 0's based value. The maximum number of LBA formats that may be indicated as supported is 16. The supported LBA formats are indicated in bytes 128 to 191 in this data structure. The LBA Format fields with an index beyond the value set in this field are invalid and not supported. LBA Formats that are valid, but not currently available may be indicated by setting the LBA Data Size for that LBA Format to 0h.
Mandatory	Yes	Yes
Notes		Returned in byte 25 (Number of LBA Formats) of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 & figure 247.

## 6.5.2.25 NVMeNamespaceProperties.FormattedLBASize

The mapping for NVMeNamespaceProperties.FormattedLBASize is summarized in [Table 151](#).

Table 151: NVMeNamespaceProperties.FormattedLBASize mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.FormattedLBASize	<b>NVM Spec Property / Field:</b> Formatted LBA Size (FLBAS) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Int64	Type:** Int64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 26
Description	The LBA data size and metadata size combination that the namespace has been formatted with.	The LBA data size and metadata size combination that the namespace has been formatted with.
LongDescription	This property shall contain the LBA data size and metadata size combination that the namespace has been formatted with. This is a 4-bit data structure.	This field indicates the LBA data size & metadata size combination that the namespace has been formatted with (refer to section 5.23). Bits 3:0 indicates one of the 16 supported LBA Formats indicated in this data structure.
Mandatory	Yes	Yes
Notes		Returned in byte 26 (Formatted LBA Size), bits 3:0 of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247).



## 6.5.2.26 NVMeNamespaceProperties.MetadataTransferredAtEndOfDataLBA

The mapping for NVMeNamespaceProperties.MetadataTransferredAtEndOfDataLBA is summarized in [Table 152](#).

Table 152: NVMeNamespaceProperties.MetadataTransferredAtEndOfDataLBA mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.MetadataTransferredAtEndOfDataLBA	<b>NVM Spec Property / Field:</b> Metadata transferred at end of LBA <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Boolean	Type:** Bit (bool) <b>Additional NVM Spec Identifying Information:</b> Bit 4 of Byte 26
Description	This property indicates whether or not the metadata is transferred at the end of the LBA creating an extended data LBA.	This property indicates whether or not the metadata is transferred at the end of the data LBA.
LongDescription	This property shall indicate whether or not the metadata is transferred at the end of the LBA creating an extended data LBA.	If set to '1' indicates that metadata is transferred at the end of the data LBA, creating an extended data LBA. Bit 4 if cleared to '0' indicates that all of the metadata for a command is transferred as a separate contiguous buffer of data.
Mandatory	Yes	Yes
Notes		Returned in byte 26 (Formatted LBA Size), bit 4 of the Identify Namespace Data Structure (Reference NVMe Base Specification section 5.15.2.1 and figure 247. Bit 4 is not applicable when there is no metadata.

## 6.5.2.27 NVMeNamespaceProperties.NVMeVersion

The mapping for NVMeNamespaceProperties.NVMeVersion is summarized in [Table 153](#).

Table 153: NVMeNamespaceProperties.NVMeVersion mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeNamespaceProperties.NVMeVersion	Version (VER)
Type	String	Int64
Description	The version of the NVMe Base Specification supported.	This property shall contain the version of the NVMe Base Specification supported.
LongDescription		Indicates the major, minor, and tertiary version of the NVM Express base specification that the controller implementation supports. Valid versions of the specification are: 1.0, 1.1, 1.2, 1.2.1, 1.3, and 1.4.
Mandatory	Yes	Yes
Notes		Returned in bytes 83:80 of the Identify Controller data structure - CNS 01h (reference NVMe Base Specification section 5.15.2.2 and figure 249).

## 6.5.2.28 OptimumIOSizeBytes

The mapping for OptimumIOSizeBytes is summarized in [Table 154](#).

Table 154: OptimumIOSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	OptimumIOSizeBytes	<b>NVM Spec Property / Field:</b> Namespace Optimal Write Size (NOWS) <b>NVM Spec: Section:Figure</b> Figure 247: Bytes 73:72
Type	Int64	
Description	The size in bytes of this Volume's optimum IO size.	N/A
LongDescription	This property shall contain the optimum IO size to use when performing IO on this volume. For logical disks, this is the stripe size. For physical disks, this describes the physical sector size.	This field indicates the size in logical blocks for optimal write performance for this namespace. This is a 0's based value.
Mandatory	Recommended for implementations with Endurance Groups and NVM Sets.	
Notes		Convert from blocks to bytes.

6.5.2.29 ProvisioningPolicy

The mapping for ProvisioningPolicy is summarized in [Table 155](#).

Table 155: OptimumIOSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	ProvisioningPolicy	<b>NVM Spec Property / Field:</b> Identify Namespace / THINP <b>NVM Spec: Section:Figure</b> 247: Byte 24, Bit 0
Type	enum (DataStorageLoSCapabilities.ProvisioningPolicy)	
Description	This property specifies the volume's storage allocation, or provisioning policy.	N/A
LongDescription	This property shall specify the volume's supported storage allocation policy.	
Mandatory	Recommended for implementations that support thin provisioning.	Figure 247: Byte 24, Bit 0 indicates thin provisioning support for the namespace
Notes	possible values: Fixed / Thin	

## 6.5.2.30 Status.State

The mapping for `Status.State` is summarized in [Table 156](#).

Table 156: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	Enable (EN)
Type	Resource.State (enum)	Boolean
Description	The known state of the resource, such as, enabled.	Indicates if the controller is in 'enabled' state.
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	When set to '1', then the controller shall process commands based on Submission Queue Tail doorbell writes. When cleared to '0', then the controller shall not process commands nor post completion queue entries to Completion Queues. When this bit transitions from '1' to '0', the controller is reset (i.e., a Controller Reset). That reset deletes all I/O Submission Queues and I/O Completion Queues, resets the Admin Submission Queue and Completion Queue, and brings the hardware to an idle state.
Mandatory	Yes	Yes
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySare / InTest / Starting / Absent / UnavailableOffline / Deferring / Quiesced / Updating / Qualified	Reference Controller Configuration (CC), offset 14h, bit 00 of the NVMe Base Specification (figure 78)

### 6.5.2.31 Status.Health

The mapping for `Status.Health` is summarized in [Table 157](#).

Table 157: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	Controller Fatal Status (CSTS.CFS)
Type	Resource.Health	Bit
Description	The health state of this resource in the absence of its dependent resources.	Indicates if the controller is able to communicate with host software via completion queue entries in the Admin Completion Queue or I/O Completion Queues.
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	If the controller has a serious error condition and is unable to communicate with host software via completion queue entries in the Admin Completion Queue or I/O Completion Queues, then the controller may set the Controller Fatal Status (CSTS.CFS) bit to '1' (refer to section 3.1.6). This indicates to host software that a serious error condition has occurred. When this condition occurs, host software should attempt to reset and then re-initialize the controller. The Controller Fatal Status condition is not indicated with an interrupt. If host software experiences timeout conditions and/or repeated errors, then host software should consult the Controller Fatal Status (CSTS.CFS) bit to determine if a more serious error has occurred.
Mandatory	Yes	Yes
Notes	Possible Values: OK / Warning / Critical	Reference Figure 222 (NVM Subsystem Hardware Error Event Codes) bit 09h of the NVMe Base Specification.

6.5.2.32 Status.HealthRollup

The mapping for `Status.HealthRollup` is summarized in [Table 158](#).

Table 158: Status.HealthRollup mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.HealthRollup	N/A
Type	Resource.Health	N/A
Description	The overall health state from the view of this resource.	N/A
LongDescription	This property shall represent the health state of the resource and its dependent resources. The values shall conform to those defined in the Redfish Specification.	N/A
Mandatory	No	N/A
Notes	Do not use for Namespace. There are no dependent resources.	Do not implement.

6.5.2.33 StorageGroups

The mapping for StorageGroups is summarized in [Table 159](#).

Table 159: StorageGroups mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	StorageGroups	NVMSpec Property / Field: N/A NVMSpec: Section:Figure N/A
Type	StorageGroupCollection.StorageGroupCollection	N/A
Description	An array of references to Storage Groups that includes this volume.	N/A
LongDescription	The value of this property shall contain references to all storage groups that include this volume.	N/A
Mandatory	Do Not Implement	
Notes		

### 6.5.2.34 WriteCachePolicy

The mapping for WriteCachePolicy is summarized in [Table 160](#).

Table 160: WriteCachePolicy mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	WriteCachePolicy	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	StorageGroupCollection.StorageGroupCollection	N/A
Description	Indicates the write cache policy setting for the Volume	N/A
LongDescription	This property shall contain a boolean indicator of the write cache policy for the Volume.	N/A
Mandatory	Recommended.	
Notes	Possible Values: WriteThrough, ProtectedWriteBack, UnprotectedWriteBack, Off. Set to “Off” when write cache disabled; set to other values when enabled.	



## 6.6 Endurance Group

The Redfish/Swordfish Storage Pool schema is used to represent an NVM Endurance Group.

### 6.6.1 Mockup

The following mockup shows a sample representation of the Storage Pool schema used to represent an NVM Endurance Group.

```
{
  "@Redfish.Copyright": "Copyright 2015-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/FabricAttachArray/StoragePools/EnduranceGroup1",
  "@odata.type": "#StoragePool.v1_4_0.StoragePool",
  "Id": "1",
  "Name": "Endurance Group 1",
  "Description": "Single Endurance Group",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },

  "NVMeEnduranceGroupProperties": {
    "EndGrpLifetime": {
      "PercentUsed": 0,
      "EnduranceEstimate": 0,
      "DataUnitsRead": 0,
      "DataUnitsWritten": 0,
      "MediaUnitsWritten": 0,
      "HostReadCommandCount": 0,
      "HostWriteCommandCount": 0,
      "MediaAndDataIntegrityErrorCount": 0,
      "ErrorInformationLogEntryCount": 0
    }
  },

  "Capacity": {
    "Data": {
      "AllocatedBytes": 10995116277760,
      "ConsumedBytes": 10995116277760
    }
  },

  "CapacitySources": [{
    "@odata.id": "/redfish/v1/Storage/FabricAttachArray/StoragePools/EnduranceGroup1/CapacitySources/Source1"
  }]
}
```

## 6.6.2 Property Mapping

### 6.6.2.1 AllocatedPools

The mapping for `AllocatedPools` is summarized in [Table 161](#).

Table 161: `AllocatedPools` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>AllocatedPools</code>	
Type	<code>StoragePoolCollection.StoragePoolCollection</code>	
Description	A reference to the collection of storage pools allocated from this storage pool.	
LongDescription	The value of this property shall contain a reference to the collection of storage pools allocated from this storage pool.	
Mandatory	Required.	
Notes	Contains a pointer to the NVM Set allocated from this Endurance Group.	

### 6.6.2.2 Capacity.Data.AllocatedBytes

The mapping for `Capacity.Data.AllocatedBytes` is summarized in [Table 162](#).

Table 162: `Capacity.Data.AllocatedBytes` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>Capacity.Data.AllocatedBytes</code>	The Total Endurance Group Capacity. Just the “Total Endurance Group Capacity” in the Endurance Group Log. See 5.14.1.9 + TP 4009
Type	Int64	
Description	The number of bytes currently allocated by the storage system in this data store for this data type.	
LongDescription	The value shall be the number of bytes currently allocated by the storage system in this data store for this data type.	
Mandatory	Required for NVMe Drives.	
Notes		Note: This is not in 1.4a because TP 4009 was not integrated.

## 6.6.2.3 Capacity.Data.ConsumedBytes

The mapping for Name is summarized in [Table 163](#).

Table 163: Capacity.Data.ConsumedBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Capacity.Data.ConsumedBytes	The Consumed (allocated to NVM Sets) Endurance Group Capacity. Just the “Total Endurance Group Capacity” (TEGCAP) minus the Uallocated Endurance Group Capacity (UEGCAP) in the Endurance Group Log. See 5.14.1.9 + TP 4009
Type	Int64	
Description	The number of bytes consumed in this data store for this data type.	
LongDescription	The value shall be the number of logical bytes currently consumed in this data store for this data type.	
Mandatory	Required for NVMe Drives.	
Notes		Note: This is not in 1.4a because TP 4009 was not integrated.

#### 6.6.2.4 CapacitySources

The mapping for CapacitySources is summarized in [Table 164](#).

Table 164: CapacitySources mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacitySources	
Type	Collection(Capacity.CapacitySource)	
Description	An array of space allocations to this volume.	
LongDescription	Fully or partially consumed storage from a source resource. Each entry provides capacity allocation information from a named source resource.	
Mandatory	Required for NVMe Drives.	
Notes	Contains the information about the providing capacity (e.g. EnduranceGroup) for this namespace.	

### 6.6.2.5 CapacitySources@odata.count

The mapping for CapacitySources@odata.count is summarized in [Table 165](#).

Table 165: CapacitySources@odata.count mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacitySources@odata.count	
Type	(odata property)int64	
Description	Count of the number of items in the CapacitySources array.	
LongDescription		
Mandatory	Required	
Notes		This should be the same as the number of NVM Sets in the endurance group.

6.6.2.6 Description

The mapping for `Description` is summarized in [Table 166](#).

Table 166: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	N/A
Description	The description of this resource.	
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	
Mandatory		
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: “An Endurance Group consists of zero or more NVM Sets. Endurance Groups divide the media into distinct wear-leveling domains.”

### 6.6.2.7 Links.OwningStorageResource

The mapping for `Links.OwningStorageResource` is summarized in [Table 167](#).

Table 167: `Links.OwningStorageResource` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>Links.OwningStorageResource</code>	
Type	<code>Storage.Storage</code>	
Description	A pointer to the Storage resource that owns or contains this StoragePool.	
LongDescription	This shall be a pointer to the Storage resource that owns or contains this StoragePool.	
Mandatory	Required.	
Notes	Contains a pointer to the NVM Subsystem that contains this Endurance Group.	



### 6.6.2.8 Name

The mapping for Name is summarized in [Table 168](#).

Table 168: Name mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	Endurance Group ID NVM Spec: Section:Figure NVMe 1.4a: Section 5.14,1,9, Get Log Page - Endurance Group Log
Type	String	16-bit value
Description	The name of the resource or array member.	
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	
Mandatory		
Notes	In Redfish, Name is a read-only field.	Map the Endurance Group ID field to a string with the format: "0xABCD"

6.6.2.9 NVMeProperties.NVMePoolType

The mapping for NVMeProperties.NVMePoolType is summarized in [Table 169](#).

Table 169: NVMeProperties.NVMePoolType

	Redfish/Swordfish	NVMe / NVMe-oF
Property	StoragePool.NVMePoolType	
Type	Enum	
Description	Indicates whether the StoragePool is used as an EnduranceGroup or an NVMeSet.	
LongDescription	This property shall indicate whether the StoragePool is used as an EnduranceGroup or an NVMeSet.	
Mandatory	Required	
Notes	Set as “EnduranceGroup”	

### 6.6.2.10 NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent

The mapping for `NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent` is summarized in [Table 170](#).

Table 170: NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent	“Percentage Used” in the Endurance Group Log. See 5.14.1.9
Type	Decimal %	
Description	The percentage of reads and writes that are predicted to be available for the media.	
LongDescription	This property shall contain an indicator of the percentage of life remaining in the drive’s media.	
Mandatory	Required	
Notes		Inverse of “Percentage Used” in the Endurance Group Log. See 5.14.1.9 . Subtract the percentage used from 100% to report this value.

## 6.6.2.11 NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed is summarized in [Table 171](#).

Table 171: NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed	"Percentage Used" in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	A vendor-specific estimate of the percent life used for the endurance group based on the actual usage and the manufacturer prediction of NVM life.	
LongDescription	This property shall contain A vendor-specific estimate of the percent life used for the endurance group based on the actual usage and the manufacturer prediction of NVM life. A value of 100 indicates that the estimated endurance of the NVM in the Endurance Group has been consumed, but may not indicate an NVM failure. According to the NVMe and JEDEC specs, the value is allowed to exceed 100. Percentages greater than 254 shall be represented as 255.	
Mandatory	Required	
Notes		

### 6.6.2.12 NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate is summarized in [Table 172](#).

Table 172: NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate	“Endurance Estimate” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains an estimate of the total number of data bytes that may be written to the Endurance Group over the lifetime of the Endurance Group assuming a write amplification of 1.	
LongDescription	This property shall contain an estimate of the total number of data bytes that may be written to the Endurance Group over the lifetime of the Endurance Group assuming a write amplification of 1. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates endurance estimates are unsupported.	
Mandatory	Required	
Notes		

### 6.6.2.13 NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead` is summarized in [Table 173](#).

Table 173: NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead mapping

	Redfish/Swordfish	NVMe / NVMe- oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead	
Type	Int64	
Description	The property contains the total number of data units read from this endurance group.	
LongDescription	The property shall contain the total number of data units read from this endurance group. This value does not include controller reads due to internal operations such as garbage collection. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates the property is unsupported.	
Mandatory	Required	
Notes		

#### 6.6.2.14 NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten` is summarized in [Table 174](#).

Table 174: NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten	“Data Units Written” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	The property contains the total number of data units written from this endurance group.	
LongDescription	The property shall contain the total number of data units written from this endurance group. This value does not include controller writes due to internal operations such as garbage collection. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates the property is unsupported.	
Mandatory	Required	
Notes		

## 6.6.2.15 NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten` is summarized in [Table 175](#).

Table 175: NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten	“Media Units Written” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	The property contains the total number of data units written from this endurance group.	
LongDescription	The property shall contain the total number of data units written from this endurance group. This value includes host and controller writes due to internal operations such as garbage collection. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates the property is unsupported.	
Mandatory	Required	
Notes		



### 6.6.2.16 NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount` is summarized in [Table 176](#).

Table 176: NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount	“Host Read Commands” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of read commands completed by all controllers in the NVM subsystem for the Endurance Group.	
LongDescription	This property shall contain the number of read commands completed by all controllers in the NVM subsystem for the Endurance Group. For the NVM command set, the is the number of compare commands and read commands.	
Mandatory	Required	
Notes		

### 6.6.2.17 NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount` is summarized in [Table 177](#).

Table 177: NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount	“Host Write Commands” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of write commands completed by all controllers in the NVM subsystem for the Endurance Group.	
LongDescription	This property shall contain the number of write commands completed by all controllers in the NVM subsystem for the Endurance Group. For the NVM command set, the is the number of compare commands and write commands.	
Mandatory	Required	
Notes		

### 6.6.2.18 NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount` is summarized in [Table 178](#).

Table 178: NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount	“Media and Data Integrity Errors” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of occurrences where the controller detected an unrecovered data integrity error for the Endurance Group.	
LongDescription	This property shall contain the number of occurrences where the controller detected an unrecovered data integrity error for the Endurance Group. Errors such as uncorrectable ECC, CRC checksum failure, or LBA tag mismatch are included in this field.	
Mandatory	Required	
Notes		

## 6.6.2.19 NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount is summarized in [Table 179](#).

Table 179: NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount	“Number of Error Information Log Entries” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of error information log entries over the life of the controller for the endurance group.	
LongDescription	This property shall contain the number of error information log entries over the life of the controller for the endurance group.	
Mandatory	Required	
Notes		

## 6.6.2.20 NVMeSetProperties.SetIdentifier

The mapping for NVMeSetProperties.SetIdentifier is summarized in [Table 180](#).

Table 180: NVMeSetProperties.SetIdentifier

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.SetIdentifier	<b>NVM Spec Property / Field:</b> NVMSETID <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	String	<b>NVM Spec Property Type:</b> 16-bit value <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 01:00
Description	A 16-bit hex value that contains the NVMe Set identifier.	
LongDescription	This property shall contain a 16-bit hex value that contains the NVMe Set identifier. The NVM Set identifier is unique within a subsystem. Reserved values include 0.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeSetProperties as part of an EnduranceGroup.

## 6.6.2.21 NVMeSetProperties.OptimalWriteSizeBytes

The mapping for NVMeSetProperties.OptimalWriteSizeBytes is summarized in [Table 181](#).

Table 181: NVMeSetProperties.OptimalWriteSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.OptimalWriteSizeBytes	<b>NVM Spec Property / Field:</b> OptimalWriteSize <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property Type:</b> Bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 15:12
Description	This property contains the Optimal Write Size in Bytes for this NVMe Set.	
LongDescription	This property shall contain the Optimal Write Size in Bytes for this NVMe Set.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeSetProperties as part of an EnduranceGroup.

## 6.6.2.22 NVMeSetProperties.EnduranceGroupIdentifier

The mapping for NVMeSetProperties.EnduranceGroupIdentifier is summarized in [Table 182](#).

Table 182: NVMeSetProperties.EnduranceGroupIdentifier mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.EnduranceGroupIdentifier	<b>NVM Spec Property / Field:</b> EnduranceGroupIdentifier <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	String	<b>NVM Spec Property Type:</b> 2 bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 03:02
Description	A 16-bit hex value that contains the endurance group identifier.	
LongDescription	This property shall contain a 16-bit hex value that contains the endurance group identifier. The endurance group identifier is unique within a subsystem. Reserved values include 0.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeSetProperties as part of an EnduranceGroup.

## 6.6.2.23 NVMeSetProperties.Random4kReadTypicalNanoSeconds

The mapping for NVMeSetProperties.Random4kReadTypicalNanoSeconds is summarized in [Table 183](#).

Table 183: NVMeSetProperties.Random4kReadTypicalNanoSeconds mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.Random4kReadTypicalNanoSeconds	<b>NVM Spec Property /</b> <b>Field:</b> Random 4 KiB Read Typical <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property</b> <b>Type:</b> 4 bytes <b>Additional NVM Spec</b> <b>Identifying</b> <b>Information:</b> ByteOffset: 11:08
Description	Indicates the typical time to complete a 4k read in 100 nano-second units when the NVM Set is in a Predictable Latency Mode Deterministic Window and there is 1 outstanding command per NVM Set.	
LongDescription	This property shall contain the typical time to complete a 4k read in 100 nano-second units when the NVM Set is in a Predictable Latency Mode Deterministic Window and there is 1 outstanding command per NVM Set.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeSetProperties as part of an EnduranceGroup.

6.6.2.24 Status.Health

The mapping for Name is summarized in [Table 184](#).

Table 184: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	N/A
Type	Resource.Health	N/A
Description	The health state of this resource in the absence of its dependent resources.	
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	
Mandatory		Do not implement
Notes	Possible Values: OK / Warning / Critical	There is not a clear mapping for health of an Endurance Group. Do not implement this property.



## 6.6.2.25 Status.State

The mapping for `Status.State` is summarized in [Table 185](#).

Table 185: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	N/A
Type	Resource.State (enum)	N/A
Description	The known state of the resource, such as, enabled.	
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but it can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory		Do not implement
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySare / InTest / Starting / ABsent / UnavaialableOffline / Deferring / Quiesced / Updating / Qualified	There is not a clear mapping for State of an Endurance Group. Do not implement this property.

## 6.7 NVM Set

The Redfish/Swordfish Storage Pool schema is used to represent an NVM Set.

### 6.7.1 Mockup

The following mockup shows a sample representation of the Storage Pool schema used to represent an NVM Set.

```
{
  "@Redfish.Copyright": "Copyright 2015-2020 SNIA. All rights reserved.",
  "@odata.id": "/redfish/v1/Storage/FabricAttachArray/StoragePools/NVMeSet1",
  "@odata.type": "#StoragePool.v1_4_0.StoragePool",
  "Id": "1",
  "Name": "Set 1",
  "Description": "First Set",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "NVMeSetProperties": {
    "SetIdentifier": "0x1F",
    "EnduranceGroupIdentifier": "0x1",
    "Random4kReadTypicalNanoSeconds": 34534345348,
    "UnallocatedNVMMNamespaceCapacityBytes": 5497558138880,
    "OptimalWriteSizeBytes": 512
  },
  "Capacity": {
    "Data": {
      "AllocatedBytes": 10995116277760,
      "ConsumedBytes": 5497558138880
    }
  },
  "AllocatedVolumes": {
    "@odata.id": "/redfish/v1/Storage/FabricAttachArray/StoragePools/NVMeSet1/AllocatedVolumes"
  }
}
```

## 6.7.2 Property Mapping

### 6.7.2.1 AllocatedVolumes

The mapping for `AllocatedVolumes` is summarized in [Table 186](#).

Table 186: `AllocatedVolumes` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>AllocatedVolumes</code>	<b>NVM Spec Property / Field:</b> <b>NVM Spec: Section:Figure</b>
Type	<code>VolumeCollection.VolumeCollection</code>	
Description	A reference to the collection of volumes allocated from this storage pool.	
LongDescription	The value of this property shall contain a reference to the collection of volumes allocated from this storage pool.	
Mandatory	Required.	
Notes	A pointer to the set of namespaces allocated from this NVM Set.	The allocated volumes contains pointers to the allocated volumes objects. These are the set of namespaces created from this NVM Set.

## 6.7.2.2 Capacity.Data.AllocatedBytes

The mapping for Name is summarized in [Table 187](#)

Table 187: Capacity.Data.AllocatedBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Capacity.Data.AllocatedBytes	<b>NVM Spec Property / Field:</b> Total NVM Set Capacity <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property Type:</b> bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 31:16 for Total NVM Set Capacity
Description	The number of bytes currently allocated by the storage system in this data store for this data type.	
LongDescription	The value shall be the number of bytes currently allocated by the storage system in this data store for this data type.	
Mandatory	Required	
Notes		

### 6.7.2.3 Capacity.Data.ConsumedBytes

The mapping for `Capacity.Data.ConsumedBytes` is summarized in [Table 188](#).

Table 188: `Capacity.Data.ConsumedBytes` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>Capacity.Data.ConsumedBytes</code>	<b>NVM Spec Property / Field:</b> Total NVM Set Capacity, Unallocated NVM Set Capacity <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property Type:</b> bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 31:16 for Total NVM Set Capacity
Byte 47:32 for Unallocated NVM Set Capacity.		
Description	The maximum number of bytes that can be allocated in this data store for this data type.	
LongDescription	The value shall be the maximum number of bytes that can be allocated in this data store for this data type.	
Mandatory	Required	
Notes		This is calculated as “Total NVM Set Capacity” - “Unallocated NVM Set Capacity”.

6.7.2.4 CapacitySources

The mapping for CapacitySources is summarized in [Table 189](#).

Table 189: CapacitySources mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacitySources	
Type	Collection(Capacity.CapacitySource)	
Description	An array of space allocations to this volume.	
LongDescription	Fully or partially consumed storage from a source resource. Each entry provides capacity allocation information from a named source resource.	
Mandatory	Recommended to not implement for NVMe Drives.	
Notes	Contains the information about the providing capacity (e.g. memory) for this namespace.	

6.7.2.5 CapacitySources@odata.count

The mapping for CapacitySources@odata.count is summarized in [Table 190](#).

Table 190: CapacitySources@odata.count mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacitySources@odata.count	
Type	(odata property)int64	
Description	Count of the number of items in the CapacitySources array.	
LongDescription		
Mandatory	Do not implement for NVMe Drives.	
Notes		

6.7.2.6 Description

The mapping for `Description` is summarized in [Table 191](#).

Table 191: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	NVM Spec Property / Field: N/A
Type	String	N/A
Description	The description of this resource.	See note below.
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	
Mandatory		
Notes	In Redfish, <code>Description</code> is a read-only field.	Return the common description: “An NVM Set is a collection of NVM that is separate (logically and potentially physically) from NVM in other NVM Sets. One or more namespaces may be created within an NVM Set and those namespaces inherit the attributes of the NVM Set. A namespace is wholly contained within a single NVM Set and shall not span more than one NVM Set.”



6.7.2.7 Links.OwningStorageResource

The mapping for Links.OwningStorageResource is summarized in [Table 192](#).

Table 192: Links.OwningStorageResource mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.OwningStorageResource	
Type	Storage.Storage	
Description	A pointer to the Storage resource that owns or contains this StoragePool.	
LongDescription	This shall be a pointer to the Storage resource that owns or contains this StoragePool.	
Mandatory	Required.	
Notes	Contains a pointer to the NVM Subsystem that contains this NVM Set.	

6.7.2.8 Name

The mapping for Name is summarized in [Table 193](#)

Table 193: Name mapping		
	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	<b>NVM Spec Property / Field:</b> NVMSETID <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	String	<b>NVM Spec Property Type:</b> 16-bit value <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 01:00
Description	The name of the resource or array member.	
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	
Mandatory	Required	
Notes	In Redfish, Name is a read-only field.	Map the NVMSETID field to a string with the format: "0xABCD"

6.7.2.9 NVMeProperties.NVMePoolType

The mapping for NVMeProperties.NVMePoolType is summarized in [Table 194](#).

Table 194: NVMeProperties.NVMePoolType

	Redfish/Swordfish	NVMe / NVMe-oF
Property	StoragePool.NVMePoolType	
Type	Enum	
Description	Indicates whether the StoragePool is used as an EnduranceGroup or an NVMeSet.	
LongDescription	This property shall indicate whether the StoragePool is used as an EnduranceGroup or an NVMeSet.	
Mandatory	Required	
Notes	Set as "NVMeSet"	

### 6.7.2.10 NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent

The mapping for NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent is summarized in [Table 195](#).

Table 195: NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.PredictedMediaLifeLeftPercent	"Percentage Used" in the Endurance Group Log. See 5.14.1.9
Type	Decimal %	
Description	The percentage of reads and writes that are predicted to be available for the media.	
LongDescription	This property shall contain an indicator of the percentage of life remaining in the drive's media.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.11 NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed is summarized in [Table 196](#).

Table 196: NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.PercentUsed	“Percentage Used” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	A vendor-specific estimate of the percent life used for the endurance group based on the actual usage and the manufacturer prediction of NVM life.	
LongDescription	This property shall contain A vendor-specific estimate of the percent life used for the endurance group based on the actual usage and the manufacturer prediction of NVM life. A value of 100 indicates that the estimated endurance of the NVM in the Endurance Group has been consumed, but may not indicate an NVM failure. According to the NVMe and JEDEC specs, the value is allowed to exceed 100. Percentages greater than 254 shall be represented as 255.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.12 NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate is summarized in [Table 197](#).

Table 197: NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.EnduranceEstimate	“Endurance Estimate” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains an estimate of the total number of data bytes that may be written to the Endurance Group over the lifetime of the Endurance Group assuming a write amplification of 1.	
LongDescription	This property shall contain an estimate of the total number of data bytes that may be written to the Endurance Group over the lifetime of the Endurance Group assuming a write amplification of 1. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates endurance estimates are unsupported.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

### 6.7.2.13 NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead` is summarized in [Table 198](#).

Table 198: NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsRead	
Type	Int64	
Description	The property contains the total number of data units read from this endurance group.	
LongDescription	The property shall contain the total number of data units read from this endurance group. This value does not include controller reads due to internal operations such as garbage collection. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates the property is unsupported.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.14 NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten` is summarized in [Table 199](#).

Table 199: NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.DataUnitsWritten	“Data Units Written” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	The property contains the total number of data units written from this endurance group.	
LongDescription	The property shall contain the total number of data units written from this endurance group. This value does not include controller writes due to internal operations such as garbage collection. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates the property is unsupported.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.



## 6.7.2.15 NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten is summarized in [Table 200](#).

Table 200: NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.MediaUnitsWritten	“Media Units Written” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	The property contains the total number of data units written from this endurance group.	
LongDescription	The property shall contain the total number of data units written from this endurance group. This value includes host and controller writes due to internal operations such as garbage collection. The value is reported in billions, where a value of 1 corresponds to 1 billion bytes written, and is rounded up. A value of zero indicates the property is unsupported.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

### 6.7.2.16 NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount` is summarized in [Table 201](#).

Table 201: NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.HostReadCommandCount	“Host Read Commands” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of read commands completed by all controllers in the NVM subsystem for the Endurance Group.	
LongDescription	This property shall contain the number of read commands completed by all controllers in the NVM subsystem for the Endurance Group. For the NVM command set, the is the number of compare commands and read commands.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.17 NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount

The mapping for `NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount` is summarized in [Table 202](#).

Table 202: NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.HostWriteCommandCount	“Host Write Commands” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of write commands completed by all controllers in the NVM subsystem for the Endurance Group.	
LongDescription	This property shall contain the number of write commands completed by all controllers in the NVM subsystem for the Endurance Group. For the NVM command set, the is the number of compare commands and write commands.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.18 NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount is summarized in [Table 203](#).

Table 203: NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.MediaAndDataIntegrityErrorCount	“Media and Data Integrity Errors” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of occurrences where the controller detected an unrecovered data integrity error for the Endurance Group.	
LongDescription	This property shall contain the number of occurrences where the controller detected an unrecovered data integrity error for the Endurance Group. Errors such as uncorrectable ECC, CRC checksum failure, or LBA tag mismatch are included in this field.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.19 NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount

The mapping for NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount is summarized in [Table 204](#).

Table 204: NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeEnduranceGroupProperties.EndGrpLifetime.ErrorInformationLogEntryCount	“Number of Error Information Log Entries” in the Endurance Group Log. See 5.14.1.9
Type	Int64	
Description	This property contains the number of error information log entries over the life of the controller for the endurance group.	
LongDescription	This property shall contain the number of error information log entries over the life of the controller for the endurance group.	
Mandatory	Do Not Implement.	
Notes		Do not implement NVMeEnduranceGroupProperties as part of an NVM Set.

## 6.7.2.20 NVMeSetProperties.SetIdentifier

The mapping for NVMeSetProperties.SetIdentifier is summarized in [Table 205](#).

Table 205: NVMeSetProperties.SetIdentifier

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.SetIdentifier	<b>NVM Spec Property / Field:</b> NVMSETID <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	String	<b>NVM Spec Property Type:</b> 16-bit value <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 01:00
Description	A 16-bit hex value that contains the NVMe Set identifier.	
LongDescription	This property shall contain a 16-bit hex value that contains the NVMe Set identifier. The NVM Set identifier is unique within a subsystem. Reserved values include 0.	
Mandatory	Required	
Notes		Return as hex value as described in the Swordfish schema.

6.7.2.21 NVMeSetProperties.OptimalWriteSizeBytes

The mapping for NVMeSetProperties.OptimalWriteSizeBytes is summarized in [Table 206](#).

Table 206: NVMeSetProperties.OptimalWriteSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.OptimalWriteSizeBytes	<b>NVM Spec Property / Field:</b> OptimalWriteSize <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property Type:</b> Bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 15:12
Description	This property contains the Optimal Write Size in Bytes for this NVMe Set.	
LongDescription	This property shall contain the Optimal Write Size in Bytes for this NVMe Set.	
Mandatory	Required	
Notes		

## 6.7.2.22 NVMeSetProperties.EnduranceGroupIdentifier

The mapping for NVMeSetProperties.EnduranceGroupIdentifier is summarized in [Table 207](#).

Table 207: NVMeSetProperties.EnduranceGroupIdentifier mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.EnduranceGroupIdentifier	<b>NVM Spec Property / Field:</b> EnduranceGroupIdentifier <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	String	<b>NVM Spec Property Type:</b> 2 bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 03:02
Description	A 16-bit hex value that contains the endurance group identifier.	
LongDescription	This property shall contain a 16-bit hex value that contains the endurance group identifier. The endurance group identifier is unique within a subsystem. Reserved values include 0.	
Mandatory	Required	
Notes		

## 6.7.2.23 NVMeSetProperties.Random4kReadTypicalNanoSeconds

The mapping for `NVMeSetProperties.Random4kReadTypicalNanoSeconds` is summarized in [Table 208](#).

Table 208: NVMeSetProperties.Random4kReadTypicalNanoSeconds mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NVMeSetProperties.Random4kReadTypicalNanoSeconds	<b>NVM Spec Property / Field:</b> Random 4 KiB Read Typical <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property Type:</b> 4 bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 11:08
Description	Indicates the typical time to complete a 4k read in 100 nano-second units when the NVM Set is in a Predictable Latency Mode Deterministic Window and there is 1 outstanding command per NVM Set.	
LongDescription	This property shall contain the typical time to complete a 4k read in 100 nano-second units when the NVM Set is in a Predictable Latency Mode Deterministic Window and there is 1 outstanding command per NVM Set.	
Mandatory	Required	
Notes		Convert from 100 nanosecond units to nanosecond units.



#### 6.7.2.24 NVMeSetProperties.UnallocatedNVMNamespaceCapacityBytes

The mapping for `NVMeSetProperties.UnallocatedNVMNamespaceCapacityBytes` is summarized in [Table 209](#).

Table 209: `NVMeSetProperties.Random4kReadTypicalNanoSeconds` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>NVMeSetProperties.UnallocatedNVMNamespaceCapacityBytes</code>	<b>NVM Spec Property / Field:</b> Random 4 KiB Read Typical <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.5, Figure 253: NVM Set Attributes Entry
Type	Int64	<b>NVM Spec Property Type:</b> 4 bytes <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 47:32
Description	Indicates the unallocated capacity of the NVMe Set in bytes.	
LongDescription	This property shall contain the unallocated capacity of the NVMe Set in bytes.	
Mandatory	Required	
Notes		Convert from 100 nanosecond units to nanosecond units.

#### 6.7.2.25 Status.State

The mapping for `Status.State` is summarized in [Table 210](#).

Table 210: `Status.State` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	<code>Status.State</code>	<b>NVM Spec Property / Field:</b> N/A
Type	Resource.State (enum)	N/A
Description	The known state of the resource, such as, enabled.	
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but it can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory		Do not implement.
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySpare / InTest / Starting / Absent / UnavailableOffline / Deferring / Quiesced / Updating / Qualified	There is not a clear mapping for State of an NVM Set. Do not implement this property.

6.7.2.26 Status.Health

The mapping for Status.Health is summarized in [Table 211](#).

Table 211: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	NVM Spec Property / Field: N/A
Type	Resource.Health	N/A
Description	The health state of this resource in the absence of its dependent resources.	
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	
Mandatory		Do not implement.
Notes	Possible Values: OK / Warning / Critical	There is not a clear mapping for health of an NVM Set. Do not implement this property.

## 6.8 Drive

The Redfish/Swordfish Drive schema represent the physical attributes of an NVMe drive object.

### 6.8.1 Mockup

The following mockup shows a sample representation of the Volume schema used to represent an NVM Namespace.

```
{
  "@odata.id": "/redfish/v1/Chassis/SimplestNVMeSSD/Drives/SimplestNVMeSSD",
  "@odata.type": "#Drive.v1_9_0.Drive",
  "IndicatorLED": "Lit",
  "Model": "ST9146802SS",
  "Revision": "S20A",
  "Status": {
    "State": "Enabled",
    "Health": "OK"
  },
  "CapacityBytes": 899527000000,
  "FailurePredicted": false,
  "Protocol": "NVMe",
  "MediaType": "SSD",
  "Manufacturer": "Contoso",
  "SerialNumber": "72D0A037FRD26",
  "PartNumber": "SG0GP8811253178M02GJA00",
  "Identifiers": [{
    "DurableNameFormat": "NAA",
    "DurableName": "500003942810D13A"
  }],
  "CapableSpeedGbs": 12,
  "NegotiatedSpeedGbs": 12,
  "Links": {
    "Volumes": [{
      "@odata.id": "/redfish/v1/Systems/Sys-1/Storage/SimplestNVMeSSD/Volumes/SimpleNamespace"
    }]
  },
  "Actions": {
    "#Drive.Reset": {
      "target": "/redfish/v1/Chassis/SimplestNVMeSSD/Drives/SimplestNVMeSSD/Actions/Drive.Reset"
    }
  }
}
```

### 6.8.2 Property Mapping

## 6.8.2.1 Actions.#Drive.Reset

The mapping for `Actions.#Drive.Reset` is summarized in [Table 212](#).

Table 212: Actions.#Drive.Reset mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Actions.#Drive.Reset	<b>NVM Spec Property / Field:</b> Shutdown Notification (SHN) <b>NVM Spec: Section:Figure</b> Figure 78: Offset 14h, Bits 15:14
Type	Action (Special form of POST)	
Description	This action resets this drive.	
LongDescription	This action shall reset this drive.	
Mandatory	Required for NVMe Drives	
Notes	This action has a mandatory property of “ResetType”, which can be any of On/ForceOff/GracefulShutdown/GracefulRestart/Nmi/ForceRestart/ForceOn/PowerCycle.	Usage: A normal NVM Subsystem shutdown maps to GracefulShutdown; Subsystem Reset maps to ForceRestart; abrupt Subsystem Shutdown maps to ForceOff. If an implementation that supports the functionality, then they may implement PowerCycle.

6.8.2.2 Actions.#Drive.SecureErase

The mapping for Actions.#Drive.SecureErase is summarized in [Table 213](#).

Table 213: Actions.#Drive.SecureErase mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Actions.#Drive.SecureErase	<b>NVM Spec Property / Field:</b> <b>NVM Spec: Section:Figure</b> Section 5.24 Sanitize Command
Type	Action (Special form of POST)	
Description	This action securely erases the contents of the drive.	
LongDescription	This action shall securely erase the drive.	TD
Mandatory	Yes	
Notes		Maps to sanitize. Implementation can support any variant.

## 6.8.2.3 Assembly.BinaryDataURI

The mapping for `Assembly.BinaryDataURI` is summarized in [Table 214](#).

Table 214: Assembly.BinaryDataURI mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Assembly.BinaryDataURI	<b>NVMe-MI Spec Property / Field:</b> Vital Product Data (VPD) <b>NVM Spec: Section:Figure</b> NVMe-MI: Section 9.2
Type	String	
Description	The URI at which to access an image of the assembly information.	
LongDescription	This property shall contain the URI at which to access an image of the assembly information, using the Redfish protocol and authentication methods. The Service provides this URI for the download of the OEM-specific binary image of the assembly data. An HTTP GET from this URI shall return a response payload of MIME type <code>application/octet-stream</code> . If the service supports it, an HTTP PUT to this URI shall replace the binary image of the assembly.	
Mandatory	Recommended	
Notes		Use to map binary blob via NVMe MI to the VPD.

6.8.2.4 BlockSizeBytes

The mapping for BlockSizeBytes is summarized in [Table 215](#).

Table 215: BlockSizeBytes mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	BlockSizeBytes	<b>NVM Spec Property / Field:</b> Formatted LBA Size (FLBAS) <b>NVM Spec: Section:Figure</b> 247: byte 26
Type	Int64	
Description	The size, in bytes, of the smallest addressable unit, or block.	
LongDescription	This property shall contain size of the smallest addressable unit of the associated drive.	
Mandatory	Required	
Notes		Follow index in 247: Byte 26 (bits 3:0) to the LBA format structure to get the metadata size and LBA data size combination. These combined values are BlockSizeBytes.

6.8.2.5 CapableSpeedGpbs

The mapping for CapableSpeedGpbs is summarized in [Table 216](#).

Table 216: CapableSpeedGpbs mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapableSpeedGpbs	NVM Spec Property / Field: PXCAP+Ch NVM Spec: Section:Figure 53
Type	Decimal	
Description	The speed, in gigabit per second (Gbit/s), at which this drive can communicate to a storage controller in ideal conditions.	
LongDescription	This property shall contain fastest capable bus speed, in gigabit per second (Gbit/s), of the associated drive.	
Mandatory	Required	
Notes		For PCIe, this is in the PCIe link capabilities (PXCAP+Ch). Figure 53. For NVMe-oF this is not specified; use the value for the highest supported native capability.



### 6.8.2.6 CapacityBytes

The mapping for CapacityBytes is summarized in [Table 217](#).

For drives supporting only a single namespace (no or default endurance group / set only):

Table 217: CapacityBytes for single namespace mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacityBytes	<b>NVM Spec Property / Field:</b> Namespace Size (NSZE) <b>NVM Spec: Section:Figure</b> NVMe 1.4a: Section 5.15.2.1 (Identify Namespace), Figure 247
Type	Int64	<b>NVM Spec Property Type:</b> int 64 <b>Additional NVM Spec Identifying Information:</b> ByteOffset: 07:00, Identify Namespace data structure
Description	The size, in bytes, of this drive.	The total size of the NVM allocated to this namespace.
LongDescription	This property shall contain the raw size, in bytes, of the associated drive.	The total size of the NVM allocated to this namespace. The value is in bytes. This field shall be supported if the Namespace Management capability (refer to NVMe Base Specification section 8.12) is supported. This field may not correspond to the logical block size multiplied by the Namespace Size field. Due to thin provisioning or other settings (e.g., endurance), this field may be larger or smaller than the Namespace Size reported.
Mandatory	Required	No
Notes	Reporting capacity in bytes is the Redfish and Swordfish standard mechanism.	Returned in bytes 63:48 of the Identify Namespace Data Structure (NVM Command Set Specific). Reference NVMe Base Specification section in 5.15.2.1 and figure 247.

For drives supporting multiple namespaces:

Table 217: CapacityBytes for single namespace mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	CapacityBytes	The Total Endurance Group Capacity. Just the “Total Endurance Group Capacity” in the Endurance Group Log. See 5.14.1.9 + TP 4009
Type	Int64	
Description	The number of bytes currently allocated by the storage system in this data store for this data type.	
LongDescription	The value shall be the number of bytes currently allocated by the storage system in this data store for this data type.	
Mandatory		
Notes		Note: This is not in 1.4a because TP 4009 was not integrated.

6.8.2.7 Description

The mapping for `Description` is summarized in [Table 218](#).

Table 218: Description mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Description	N/A
Type	String	N/A
Description	The description of this resource.	N/A
LongDescription	This object represents the description of this resource. The resource values shall comply with the Redfish Specification-described requirements.	N/A
Mandatory	Yes	N/A
Notes	In Redfish, <code>Description</code> is a read-only field.	

### 6.8.2.8 EncryptionAbility

The mapping for `EncryptionAbility` is summarized in [Table 219](#).

Table 219: EncryptionAbility mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	EncryptionAbility	N/A
Type	Enum (EncryptionAbility)	
Description	The encryption ability of this drive.	
LongDescription	This property shall contain the encryption ability for the associated drive.	
Mandatory	Required	
Notes	Required when encryption is supported. Available values: None/SelfEncryptingDrive/Other	Maps to vendor capabilities.

### 6.8.2.9 EncryptionStatus

The mapping for EncryptionStatus is summarized in [Table 220](#).

Table 220: EncryptionStatus mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	EncryptionStatus	N/A
Type	Drive.EncryptionStatus	
Description	The status of the encryption of this drive.	
LongDescription	This property shall contain the encryption status for the associated drive.	
Mandatory	DependsOn EncryptionAbility != None	
Notes	Must be implemented and set when Encryption is enabled (EncryptionAbility will indicate encryption capability type.) Possible values: Unlocked/locked/foreign/unencrypted	Set according to vendor specs / mapping.

### 6.8.2.10 FailurePredicted

The mapping for FailurePredicted is summarized in [Table 221](#).

Table 221: FailurePredicted mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	FailurePredicted	<b>NVM Spec Property / Field:</b> SmartHealthLog <b>NVM Spec: Section:Figure</b> 196
Type	Boolean	
Description	An indication of whether this drive currently predicts a failure in the near future.	
LongDescription	This property shall indicate whether this drive currently predicts a manufacturer-defined failure.	
Mandatory	Required	
Notes	Implements the results of the SMART log data.	Trigger when the smart health errors indicate an issue (e.g.,): media and data integrity errors, and self-check.

### 6.8.2.11 Identifiers

The mapping for `Identifiers` is summarized in [Table 222](#).

Table 222: Identifiers mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	Collection(Resource.Identifier)	An array of identifiers
Description	The Durable names for the subsystem.	An array of identifiers
LongDescription	This property shall contain a list of all known durable names for the associated subsystem.	This specifies the NVM Subsystem NVMe Qualified Name as a UTF-8 null-terminated string. Refer to NVMe Base Specification, section 7.9, for the definition of NVMe Qualified Name. Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2).
Mandatory	Yes	Yes
Notes	This is an array of unique identifiers for the NVM Subsystem.	There will only be one instance in this array for Subsystem. Refer to the Identify Controller data structure (CNS 01h) bits 1023:768 in figure 249 (Identify – Identify Controller Data Structure) of the NVMe Base Specification.

## 6.8.2.12 Identifiers.DurableNameFormat

The mapping for `Identifiers.DurableNameFormat` is summarized in [Table 223](#).

Table 223: Identifiers.DurableNameFormat mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableNameFormat	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	Resource.v1_1_0.DurableNameFormat	There is a single value for this array in Subsystem. The property type is of type NVMe Qualified Name (NQN).
Description	The format of the Durable names for the subsystem.	NVM Subsystem NVMe Qualified Name (SUBNQN)
LongDescription	This specifies the format of the associated NVM Subsystem NVMe Qualified Name of type NQN. Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2).	
Mandatory	No	Yes
Notes	This is an enum with multiple potential values. For this particular usage in Subsystem, there will only be one instance populated, of type NQN.	There will only be one instance in this array for Subsystem. Refer to the Identify Controller data structure (CNS 01h) bits 1023:768 in figure 249 (Identify – Identify Controller Data Structure) of the NVMe Base Specification.

## 6.8.2.13 Identifiers.DurableName

The mapping for `Identifiers.DurableName` is summarized in [Table 224](#).

Table 224: Identifiers.DurableName mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Identifiers.DurableName	NVM Subsystem NVMe Qualified Name (SUBNQN)
Type	Edm.String	The NVM Subsystem NVMe Qualified Name as a UTF-8 null-terminated string
Description	The format of the Durable names for the subsystem.	NVM Subsystem NVMe Qualified Name (SUBNQN)
LongDescription	This specifies the NVM Subsystem NVMe Qualified Name as a UTF-8 null-terminated string. Refer to NVMe Base Specification, section 7.9, for the definition of NVMe Qualified Name. Support for this field is mandatory if the controller supports revision 1.2.1 or later as indicated in the Version register (refer to section 3.1.2).	
Mandatory	No	Yes
Notes	For this particular usage in Subsystem, there will only be one instance populated in the identifiers array.	There will only be one instance in this array for Subsystem. Refer to the Identify Controller data structure (CNS 01h) bits 1023:768 in figure 249 (Identify – Identify Controller Data Structure) of the NVMe Base Specification.



6.8.2.14 IndicatorLED

The mapping for IndicatorLED is summarized in [Table 225](#).

Table 225: IndicatorLED mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	IndicatorLED	N/A
Type	Boolean	N/A
Description	An indication of whether this drive currently predicts a failure in the near future.	
LongDescription	This property shall indicate whether this drive currently predicts a manufacturer-defined failure.	N/A
Mandatory	Do Not Implement	
Notes	This property has been deprecated. See guidance / implement the LocationIndicatorActive property instead.	

### 6.8.2.15 Links.Volumes

The mapping for `Links.Volume` is summarized in [Table 226](#).

Table 226: Links.Volume mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Volume	
Type	Collection(Volume.Volume)	
Description	An array of links to the volumes that this drive either wholly or only partially contains.	
LongDescription	This property shall contain an array of links to resources of type Volume with which this drive is associated. This property shall include all volume resources of which this drive is a member and all volumes for which this drive acts as a spare if the hot spare type is <code>Dedicated</code> .	
Mandatory	Required	
Notes	This array shall contain links to all namespaces associated with this physical drive.	One way to do this would be get all of the controllers, iterate through the list and get all of the namespace ids.

6.8.2.16 Links.Volumes@odata.count

The mapping for `Links.Volumes@odata.count` is summarized in [Table 227](#).

Table 227: Links.Volumes@odata.count mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Links.Volumes@odata.count	
Type	(odata property)int64	N/A
Description	Count of the number of items in the Links.Volume array.	
LongDescription		
Mandatory	Required	
Notes		The number of namespaces is available from NVMe on a per controller basis.

6.8.2.17 Location

The mapping for Location is summarized in [Table 228](#).

Table 228: Location mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Location	N/A
Type	Collection(Resource.Location)	
Description	The location of the drive.	
LongDescription	This property shall contain location information of the associated drive.	N/A
Mandatory	Do Not Implement	
Notes	This property has been deprecated. See guidance / implement the PhysicalLocation property instead.	

### 6.8.2.18 LocationIndicatorActive

The mapping for LocationIndicatorActive is summarized in [Table 229](#).

Table 229: LocationIndicatorActive mapping

	Redfish/Swordfish	NVMe / NVMe- oF
Property	LocationIndicatorActive	N/A
Type	Boolean	N/A
Description	An indicator allowing an operator to physically locate this resource.	
LongDescription	This property shall contain the state of the indicator used to physically identify or locate this resource. A write to this property shall update the value of IndicatorLED in this resource, if supported, to reflect the implementation of the locating function.	N/A
Mandatory	Recommended	
Notes	This property replaces the IndicatorLED, which has been deprecated.	Comes from vendor.

### 6.8.2.19 Manufacturer

The mapping for `Manufacturer` is summarized in [Table 230](#).

Table 230: Manufacturer mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Manufacturer	<b>NVM Spec Property / Field:</b> <b>NVM Spec: Section: Figure</b>
Type	String	
Description	The manufacturer of this drive.	
LongDescription	This property shall contain the name of the organization responsible for producing the drive. This organization might be the entity from whom the drive is purchased, but this is not necessarily true.	
Mandatory	Required	
Notes		End clients expect to see the name of the company (e.g.; Contoso, BestVendor). While the value may be filled from the <code>IdentifyController</code> PCI Vendor ID or <code>SubsystemID</code> field, it would be preferable to have this filled with the actual string value of the company name.

6.8.2.20 MediaType

The mapping for `MediaType` is summarized in [Table 231](#).

Table 231: `MediaType` mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	MediaType	N/A
Type	enum (MediaType)	
Description	The type of media contained in this drive.	
LongDescription	This property shall contain the type of media contained in the associated drive.	N/A
Mandatory	Required	
Notes	Possible values: HDD/SSD/SMR.	NVMe SSD Drives to report SSD.

6.8.2.21 Model

The mapping for Model is summarized in [Table 232](#).

Table 232: Model mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Model	<b>NVM Spec Property / Field:</b> IdentifyController / Model Number (MN) <b>NVM Spec: Section: Figure</b> 249 byte 24:63
Type	String	N/A
Description	The model number for the drive.	
LongDescription	This property shall contain the name by which the manufacturer generally refers to the drive.	N/A
Mandatory	Required	
Notes		



6.8.2.22 Multipath

The mapping for Multipath is summarized in [Table 233](#).

Table 233: Multipath mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Multipath	<b>NVM Spec Property / Field:</b> IdentifyNamespace: NMIC <b>NVM Spec: Section:Figure</b> 247: Byte 30, bit 0
Type	Boolean	N/A
Description	An indication of whether the drive is accessible from multiple paths.	
LongDescription	This property shall indicate whether the drive is accessible by an initiator from multiple paths allowing for failover capabilities upon a path failure.	N/A
Mandatory	Recommended to implement. Required property if drive is dual-ported.	
Notes		

6.8.2.23 Name

The mapping for Name is summarized in [Table 234](#).

Table 234: Name mapping		
	Redfish/Swordfish	NVMe / NVMe-oF
Property	Name	<b>NVM Spec</b> <b>Property / Field:</b> Namespace ID (NSID) <b>NVM Spec:</b> <b>Section:Figure</b> NVMe 1.4a
Type	String	
Description	The name of the resource or array member.	N/A
LongDescription	This object represents the name of this resource or array member. The resource values shall comply with the Redfish Specification-described requirements. This string value shall be of the 'Name' reserved word format.	
Mandatory	Yes	N/A
Notes	In Redfish, Name is a read-only field.	

## 6.8.2.24 NegotiatedSpeedGbps

The mapping for NegotiatedSpeedGbps is summarized in [Table 235](#).

Table 235: NegotiatedSpeedGbps mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	NegotiatedSpeedGbps	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	Decimal	N/A
Description	The speed, in gigabit per second (Gbit/s), at which this drive currently communicates to the storage controller.	
LongDescription	This property shall contain current bus speed, in gigabit per second (Gbit/s), of the associated drive.	N/A
Mandatory	Required	
Notes		For PCIe, this is in the PCIe link capabilities (PXCAP+12h). Figure 55. For NVMe-oF this is not specified; use the value for the native capability.

### 6.8.2.25 PhysicalLocation.Info

The mapping for `PhysicalLocation.Info` is summarized in [Table 236](#).

Table 236: PhysicalLocation.Info mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PhysicalLocation.Info	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	String	
Mandatory	Do Not Implement	
Notes	This property has been deprecated.	

### 6.8.2.26 PhysicalLocation.InfoFormat

The mapping for `PhysicalLocation.InfoFormat` is summarized in [Table 237](#).

Table 237: PhysicalLocation.InfoFormat mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PhysicalLocation.InfoFormat	<b>NVM Spec Property / Field:</b> N/A <b>NVM Spec: Section:Figure</b> N/A
Type	String	
Mandatory	Do Not Implement	
Notes	This property has been deprecated.	

## 6.8.2.27 PhysicalLocation.PartLocation

The mapping for `PhysicalLocation.PartLocation` is summarized in [Table 238](#).

Table 238: PhysicalLocation.PartLocation mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PhysicalLocation.PartLocation	<b>NVMeSpec</b> <b>Property /</b> <b>Field:</b> N/A <b>NVMeSpec:</b> <b>Section:Figure</b> N/A
Type	Boolean	N/A
Description	An indication of whether the drive is accessible from multiple paths.	
LongDescription	This property shall indicate whether the drive is accessible by an initiator from multiple paths allowing for failover capabilities upon a path failure.	N/A
Mandatory	Recommended to implement. Required property if drive is dual-ported.	
Notes	The drive should support this property to be filled in by a layered process (e.g., BMC). Support for any other properties in PhysicalLocation are at the discretion of the vendor.	

## 6.8.2.28 PredictedMediaLifetimeLeftPercent

The mapping for PredictedMediaLifetimeLeftPercent is summarized in [Table 239](#).

Table 239: PredictedMediaLifetimeLeftPercent mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	PredictedMediaLifetimeLeftPercent	<b>NVM Spec Property / Field:</b> Get Log Page – SMART / Health Information Log <b>NVM Spec: Section:Figure</b> Figure 196: 05
Type	Decimal	
Description	The percentage of reads and writes that are predicted to be available for the media.	
LongDescription	This property shall contain an indicator of the percentage of life remaining in the drive's media.	N/A
Mandatory	Required.	
Notes	Maps to percentage used in SMART information log	Calculate as 100 - value reported (PercentageUsed).

6.8.2.29 Protocol

The mapping for `Protocol` is summarized in [Table 240](#).

Table 240: Protocol mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Protocol	
Type	Protocol.Protocol	
Description	The protocol that this drive currently uses to communicate to the storage controller.	
LongDescription	This property shall contain the protocol that the associated drive currently uses to communicate to the storage controller for this system.	
Mandatory	Required.	
Notes	Possible values (long list)	NVMe Drives shall report “NVMe”.



6.8.2.30 Revision

The mapping for Revision is summarized in [Table 241](#).

Table 241: Revision mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Revision	<b>NVM Spec Property / Field:</b> IdentifyController: Firmware Revision (FR) <b>NVM Spec: Section:Figure</b> 249: 71:64
Type	String	
Description	The revision of this drive. This is typically the firmware or hardware version of the drive.	
LongDescription	This property shall contain the manufacturer-defined revision for the associated drive.	
Mandatory	Required.	
Notes		Return the currently active firmware revision information.

### 6.8.2.31 RotationSpeedRPM

The mapping for RotationSpeedRPM is summarized in [Table 242](#).

Table 242: RotationSpeedRPM mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	RotationSpeedRPM	
Type	Decimal	
Description	An indication of whether the drive is accessible from multiple paths.	
LongDescription	This property shall indicate whether the drive is accessible by an initiator from multiple paths allowing for failover capabilities upon a path failure.	
Mandatory	DependsOn MediaType value. If MediaType == SSD, (not required to) do not implement.	
Notes	Future proofing - will be a relevant property for NVMe HDDs.	

6.8.2.32 SKU

The mapping for SKU is summarized in [Table 243](#).

Table 243: SKU mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SKU	N/A
Type	String	
Description	The SKU for this drive.	
LongDescription	This property shall contain the stock-keeping unit (SKU) number for this drive.	
Mandatory	Required.	
Notes	The drive should support this property to be filled in by a layered process (e.g., OEM manufacturing).	

6.8.2.33 SerialNumber

The mapping for SerialNumber is summarized in [Table 244](#).

Table 244: SerialNumber mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SerialNumber	<b>NVM Spec Property / Field:</b> IdentifyController / SerialNumber (SN) <b>NVM Spec: Section: Figure</b> 249 byte 04:23
Type	String	
Description	The serial number for this drive.	
LongDescription	This property shall contain the manufacturer-allocated number that identifies the drive.	
Mandatory	Required.	
Notes		

## 6.8.2.34 Status.State

The mapping for `Status.State` is summarized in [Table 245](#).

Table 245: Status.State mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.State	Enable (EN)
Type	Resource.State (enum)	
Description	The known state of the resource, such as, enabled.	
LongDescription	This property shall indicate whether and why this component is available. Enabled indicates the resource is available. Disabled indicates the resource has been intentionally made unavailable but can be enabled. Offline indicates the resource is unavailable intentionally and requires action to make it available. InTest indicates that the component is undergoing testing. Starting indicates that the resource is becoming available. Absent indicates the resource is physically unavailable.	
Mandatory	Required (for NVM Drives)	
Notes	Possible values: Enabled / Disabled / StandbyOffline / StandbySpare / InTest / Starting / Absent / UnavailableOffline / Deferring / Quiesced / Updating / Qualified	The drive should support this property to be filled in by a higher level client (e.g., BMC). The drive can self-set this drive to Enabled / Disabled / InTest / Updating. If any controller in the drive is set to Enabled, set to "Enabled". If all controllers are set to disabled, set to "Disabled". If a firmware update is in progress, set to "Updating". If the drive is running a self-test, set to "InTest".

## 6.8.2.35 Status.Health

The mapping for `Status.Health` is summarized in [Table 246](#).

Table 246: Status.Health mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	Status.Health	<b>NVMeSpec Property / Field:</b> CSTS – Controller Status <b>NVMeSpec: Section:Figure</b> NVMe 1.4a: Section 3.1.6, Figure 79 <b>NVMeSpec Property / Field:</b> Critical Warning <b>NVMeSpec: Section:Figure</b> NVMe 1.4a: Section 5.14.1.2, SMART / Health Information, Figure 196
Type	Resource.Health	
Description	The health state of this resource in the absence of its dependent resources.	
LongDescription	This property shall represent the health state of the resource without considering its dependent resources. The values shall conform to those defined in the Redfish Specification.	
Mandatory	Required for NVM Drives.	
Notes	Possible Values: OK / Warning / Critical	Report to same value as set for worst-case controller <code>Status.Health</code> .

### 6.8.2.36 StatusIndicator

The mapping for `StatusIndicator` is summarized in [Table 247](#).

Table 247: StatusIndicator mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	StatusIndicator	N/A
Type	enum (StatusIndicator)	
Description	An indication of whether the drive is accessible from multiple paths.	
LongDescription	This property shall indicate whether the drive is accessible by an initiator from multiple paths allowing for failover capabilities upon a path failure.	
Mandatory	Required.	
Notes	Multiple values possible. Relevant values for NVMe standalone drives: OK, Fail, PredictiveFailureAnalysis.	The drive should support this property to be filled in by a higher level client (e.g., BMC). The drive can self-set this drive only to OK (or potentially fail, but only if the property has not been set by higher-level software).

6.8.2.37 WriteCacheEnabled

The mapping for WriteCacheEnabled is summarized in [Table 248](#).

Table 248: WriteCacheEnabled mapping

	Redfish/Swordfish	NVMe / NVMe-oF
Property	SerialNumber	<b>NVM Spec Property / Field:</b> Volatile Write Cache Enable (WCE) <b>NVM Spec: Section:Figure</b> 283: 00
Type	Boolean	
Description	An indication of whether the drive write cache is enabled.	
LongDescription	This property shall indicate whether the drive write cache is enabled.	
Mandatory	Required (for NVMe Drives).	
Notes		Bits 00 of WCE indicate whether the WCE is enabled or disabled.



## 7 Other Feature Mapping

### 7.1 Introduction

There are additional features and functionality that are also desirable to be exposed via the Redfish/Swordfish management ecosystems; however, there is not necessarily a clear mapping for these to a specific portion of the NVMe specification, or the functionality has a large component provided by the NVMe device implementer. This section provides an overview of the required functionality and presentation required to present a common, standardized interface to the Redfish/Swordfish clients.

### 7.2 Firmware Update

Firmware update is a required function to present comprehensive management. This is presented in Redfish through the “Update” service. The Update Service provides a standardized interface to all software and firmware update mechanisms throughout the server, storage, and networking environment, and as such, provides an abstracted, standardized interface that largely manages the acquisition from the client of the image files (and subsequent distribution of those to the designated targets), as well as very coarse-grained scheduling.

Note that this mechanism does not include any “active image” management capability (e.g., rollback).

#### 7.2.1 Firmware update for NVMe Drives

NVMe drives shall support a standard implementation of the Redfish Update service. This is fundamentally a single-step invocation process on the update service that gets the image file from a specified URI using the SimpleUpdate action.

One parameter that shall be specified is the OperationApplyTime; this indicates when to apply the image. If not explicitly specified, the implementation should assume the request is to be applied immediately.

The values of the OperationApplyTime that shall be supported by NVMe drives are: - Immediate - OnReset

Example simple update request:

```
POST /redfish/v1/UpdateService/Actions/UpdateService.SimpleUpdate HTTP/1.1
Content-Type: application/json
Content-Length: <computed-length>

{
  "ImageURI": "https://192.168.1.250/images/dev1_update.bin"
  "@Redfish.OperationApplyTime": "OnReset"
}
```

The following additional parameters may be required to access the image. Implementations should support these:

Username | String | The user name to access the URI specified by the ImageURI parameter. |  
Password | String | The password to access the URI specified by the ImageURI parameter. |

Additionally, the implementation may support the Targets parameter to specify the list of devices on which to apply the image. If Targets is not specified, the image will be applied to all applicable devices.

Targets | Array | An array of strings that are URIs to resources that indicate where to apply the image. |

The SimpleUpdate mechanism is fundamentally a “pull” mechanism (the implementation pulls a file from a target); the UpdateService also supports a “push” mechanism (the client “pushes” the image to the implementation as part of the request payload) that may also be implemented. For more information this mechanism, using the MultipartHttpPushUri property, is documented in the Redfish Specification.

##### 7.2.1.1 Mapping Images to NVMe Capabilities

It will be up to the implementation to determine the NVMe specific parameters to use upon receipt of the image from the update service. However, the following general guidelines should be used to ensure behavioral consistency across implementations:

When receiving image: - If open slots, the implementation can choose what open slot to use, and load the image to that slot. - If all slots are full, the implementation can choose (typically any slot except the currently active image).

After loaded to a slot, the implementation will mark the image as active. Based on the “apply time” setting, the implementation setting will activate the image either immediately, or set to activate on (the next) reset.

# Annex A: Objects without a direct mapping to the NVMe model

## A.1: Overview

There are a number of objects that are required for the proper integration of NVMe support within Redfish and Swordfish, but which are not supported by an entity that can be mapped directly from the various NVM Specifications. Information about these related but un-mapped objects are defined elsewhere in the documentation provided with each Swordfish release.

They are summarized in [Table A.1](#) for ease of use, including:

- Object Name
- NVMe Device Expected Usage

Table A.1: Related Objects

Object	NVMe Device Expected Usage
NetworkAdapter	NVMe-oF Subsystems, Network-Attach Drives
Port	NVMe-oF Subsystems, Network-Attach Drives
NetworkDeviceFunction	NVMe-oF Subsystems, Network-Attach Drives

Required usage of objects and their properties are contained in the relevant [Swordfish profiles \(https://www.snia.org/forums/smi/swordfish\)](https://www.snia.org/forums/smi/swordfish).

For example, for Ethernet-Attach drives, the NetworkAdapter, Port, and NetworkDeviceFunction required properties are specified as part of the “Ethernet-Attach NVMe Drive” profile.

## A.2: Related Use Cases

The [Swordfish Scalable Storage Management API User’s Guide \(https://www.snia.org/forums/smi/swordfish\)](https://www.snia.org/forums/smi/swordfish) contains real-world examples of how clients will interact with an implementation. [Table A.2](#) summarizes the NVMe use cases as of 2 March 2021.

Table A.2: NVMe Use Case Summary

Title	Description
Attach a Namespace	Attach a Namespace
Deprovision a Namespace	Deprovision a Namespace
Detach a Namespace	Detach a Namespace
Provision a Namespace	Provision a Namespace
Provision an NVMeSet with a Namespace	Provision an NVMeSet associated with a Namespace
Report capacity for a Namespace	Report capacity for a Namespace
Report remaining life for a Namespace	Report remaining life for a Namespace

# Annex B: Bibliography

## B.1 Overview

The following referenced documents provide important support for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

## B.2 Informational references

The informational references are summarized in [Table B.1](#).

Table B.1: Informational References, cont.

Tag	Title (Version)	Author	URL
Profiles	Swordfish Profile Bundle Working Draft	SNIA	<a href="https://www.snia.org/forums/smi/swordfish">https://www.snia.org/forums/smi/swordfish</a> ( <a href="https://www.snia.org/forums/smi/swordfish">https://www.snia.org/forums/smi/swordfish</a> )
UsersGuide	wordfish Scalable Storage Management API User’s Guide	SNIA	<a href="https://www.snia.org/forums/smi/swordfish">https://www.snia.org/forums/smi/swordfish</a> ( <a href="https://www.snia.org/forums/smi/swordfish">https://www.snia.org/forums/smi/swordfish</a> )